Catalog No. 551 Issued July, 1951

GRAY-BONNEY

The Canadian Made Hand Tool Line

for ...

AUTOMOTIVE

AVIATION REFRIGERATION

INDUSTRIAL

AGRICULTURAL

MARINE

BONNEY

GRAY-BONNEY TOOL COMPANY, LIMITED

St. Clarens and Dupont TORONTO - CANADA

Subsidiary of GRAY FORGINGS AND STAMPINGS LIMITED

Statements of Policy

=0=

WARRANTY REPLACEMENTS

All Gray-Bonney Tools are made from the finest obtainable steels to meet the normal conditions to which the tool will be subjected. Every Gray-Bonney Tool is individually inspected before leaving the factory, and is guaranteed against defects in workmanhip and/or materials. All tools that do not live up to this Guarantee will be replaced or repaired free of charge.

Free replacement cannot be made if inspection shows that tools have been hammered or used with any device for adding any extra leverage — tools have been ground thinner or changed in design — have been used for any purpose other than that for which they have been designed.

Gray-Bonney Tools cannot be replaced free of charge that show normal wear and tear — damage from contact with hot wires — damage resulting from alterations or tampering — breakage from abuse or overload.

Gray-Bonney Pliers, Punches, Chisels or Screw Drivers cannot be replaced free of charge that show they have been used for other than their intended purpose, or show damage to the teeth or cutting edges resulting from use on hardened materials or tempered steel wire. Chrome plating on Plier cutting edges not guaranteed. Punches and Chisels which have been reground cannot be replaced.

The following Tools not subject to free replacement—Nos. 00A, 001, 308, 499, 517, 525, 654, 2586, E02, E03, FT57, M5, RF6, RF16, RF17, RF18, RF71, RF72, RF73, T34. Defective Ratchets will be serviced on basis of No Charge Repair. Flexible Handles, Punches, Chisels and Screw Drivers will be repaired or replaced at our discretion.


WHOLESALER RETURNS

Gray-Bonney Tools acceptable for return under conditions stated hereunder will be confined to those hand tools listed in this catalog or subsequent issues thereof. Such tools will be of current design, finishes and markings.

Gray-Bonney Tools ordered in error are acceptable for return without handling charge if returned to factory within 30 days of original shipping date by way of prepaid transportation.

During each October or November wholesalers may submit written information on tools eligible for return and considered surplus in inventory. Written return authorization will be forwarded to the wholesaler subject only to prepaid transportation and other conditions stated herein. Valuation of tools for return will not exceed at current factory cost any amount greater than ten per cent of purchases from us during the previous twelve month period. All returns are to be made during December only and a handling charge of ten per cent will apply. Factory allowance will be in form of book credit to apply against current or future purchases from us.

The Home of GRAY-BONNEY Tools



GRAY-BONNEY Tools have a wide acceptance among the mechanics in every branch of industry. Every Gray-Bonney Tool is specially designed for a particular application—combines light weight with strength and enables the user to do each job well — quickly — easily.

Made by Canadian Tool Craftsmen with pride in their ability to produce fine hand tools, backed by 39 years of manufacturing experience and proved on the testing ground of time—these tools have earned the reputation "the Finest that money can buy".

GRAY - BONNEY TOOL COMPANY, LIMITED

Subsidiary of GRAY FORGINGS and STAMPINGS LIMITED

TORONTO

CANADA



ALPHABETICAL TOOL

0.00	PAGI
PAGE	Handles and Attachments for Sockets
Adaptors-Reducing, Increasing 8	Tanules and Accacimients for Sounds
Adjustable Pliers 31, 32, 33 Adjustable Wrenches 25	For 1/4" Square Drive For 3/8" Square Drive
Ball Pein Hammers 44	For 1/2" Square Drive 8, 1
Battery Tools 32, 38	For 3/4" Square Drive1
Body and Fender Tools, 44, 45, 46, 47	For 1" Square Drive 1
Box Wrenches	For 1 Square Drive
Brake Cylinder Hone 31	For British-Same as above
Brake Wrenches and Pliers 30-31	Head Screw Wrenches2
British Size Wrenches 48, 49, 50, 51	Heavy Duty Box Wrenches 2
Bumping Hammers 44-45	Holding Tools4
Bushing Removers 26	Hones 31, 4
Cabinets 58	Hub Cap Remover 3
Carburetor Wrench for Ford 24	Hydraulic Brake Tools 30, 3
Carbon Scraper29	Ignition Pliers 3
Caster Camber Wrenches 24	Ignition Wrenches 2
Chart of Wrench and Socket	Industrial Box Wrenches 2
Openings Back Cover	Industrial Sockets1
Chisels 35	Industrial Socket Wrenches
Clutch Alignment Set 29	9, 10, 16, 17, 1
Clutch Head Screw Drivers	Lining Up Punches 3
Combination Pliers 32	T I. Ding Poplacer
Con. Rod Sockets for Ford7	Task Ding Pliere
Cutting Pliers32, 33	
Cylinder Ridge Reamer 29	Manifold Wrenches
Dinging Hammers44	Magnetic Hammer 4
Dolly Blocks45-46	Numerical Index
Door Panel Spoons46	Offeet Screw Drivers 4
Drag Link Sockets4, 7	Oil Drain Plug Wrench
Drain Plug Wrenches 39	Panel Spoons
Electrical Wrenches 21, 51	Philline' Screw Drivers
Engineers' Wrenches 19, 20, 51	Pilots for Reamers
Extra Deep Sockets 4, 6, 15, 50	Pinch-off Tool
Extra Deep Sockets 4, 6, 10, 00	Pipe Wrenches
Expansion Reamers26	Piston Tools31, 32, 33,
Extractors 27	Pliers31, 32, 33,
Feeler Gauges 36, 37	
Fender Mallet 45	Dullara 27.
Files and Holders 46	Punches and Chisels
Flare Nut Wrenches 30, 54	Reamers
Flaring Tool 56	Refrigeration Tools 52, 53, 54,
Gasket Cutter Set40	Pidge Reamer
Gear Pullers 27	Right Angle Wrenches
Gear Pullers	Rim Wrenches
Grease Bar 38	Ding Compressors
Hacksaw Blades and Frame 57	Ping Groove Cleaner
Hammers:	Rivet Buster
Ball Pein 44	Robertson Screw Driver
Body and Fender 44-45	Roller Cabinet
Body and render 44-40	Saw Frames and Blades
Magnetic45	Screw Drivers 41, 42,
Soft Face44	Screw Driver Sockets
Tire and Rim 39	Screw Extractors
Upholsterers' 45	Screw Starters

JEA	
	PAGE
Seamers	57
Sat Saraw Wranches	25
Shop Knife	29
Shop KnifeSnap-lock Pliers	56
Snap Ring Pliers	31
Snips	57
Casket Wronch Sate:	
1 /4" Courses Drive	9
1/4" Square Drive 3/8" Square Drive 12/8 Square Drive 11, 12, 13/4" Square Drive 11, 12, 13/4" Square Drive 1 1" Square Drive 1 1 1 1 1 1 1 1 1	o
3/8 Square Drive	9 14
1/2 Square Drive 11, 12, 1	0, 14
3/4" Square Drive	6, 17
1" Square Drive	18
British Sizes 48, 4	19, 50
Combination 9, 1 Industrial 10, 11, 16, 1	0, 11
Industrial 10, 11, 16, 1	17, 18
Master	9
Master Refrigeration	52. 53
1/4" Square Drive	
Sockets:	4 2
3/8 Square Drive	6
1/2 Square Drive	1,
3/4 Square Drive	A4
1" Square Drive	10
British Sizes	51
Drag Link	4,
British Sizes Drag Link Extra Deep	6, 1
Ford Con. Rod	
Power Type	
Spark Plug	.4,
Weatherhead Type	
Extra Deep *, Ford Con. Rod Power Type Spark Plug Weatherhead Type Soft Face Hammers	4
Spark Plug Chart Spark Plug Sockets Spinner Wrenches Split Washer Replacer	
Carele Plum Sockets	4.
Spark Flug Sockets	5
Spinner wrenches	9
Split Washer Replacer	- 5
Starter Wrenches	0 1
Split Washer Replacer Starter Wrenches Stud Removers Tappet Wrenches Thread Restorers Time and Rim Hammer	04 5
Tappet Wrenches	24, 0
Thread Restorers	2
Thread Restorers Tire and Rim Hammer Tire sand Rim Irons Tire Spreader Tool Boxes Torque Wrenches	3
Tire and Rim Irons	3
Tire Spreader	3
Tool Boxes	b
Torque Wrenches	1
Tube Benders	5
Tube Benders Tube Cutters Tu-Type Wrenches Universal Joints Universal Joint Sockets	5
Tu-Type Wrenches	2
Universal Joints4	, 8, 1
Universal Joint Sockets	4.
Valve Tools	9
Valve Tools Water Pump Pliers Wheel Puller Wire Brush	2
Wheel Puller	9
Wiles Panels	
Wire Brush	3

GRAY-BONNEY EXTRA SMALL SERIES 1/4" DRIVE SOCKET SETS

These Gray-Bonney 1/4" drive midget sockets and attachments are the ultimate in precision design and manufacture. The new improved small head reversible ratchet, tiny handles and extra thin wall lock-on sockets are produced from the finest alloy steels and all are chrome plated. Created for motor tuneup specialists and those who service starting—lighting—ignition—instruments and radio. They will prove a welcome addition to any tool equipment. Each individual piece available separately from open stock.

No. VS14 Set

Contains 14 Pieces-3/16" to 3/8" Approx. Weight 1-1/4 lbs.



A dandy pocket size kit of sockets and attachments with reversible ratchet for turning small nuts. All pieces are made of the finest alloy steel, fully chrome plated. Packed complete in strong attractively finished metal box measuring 6-3/16" x 2" x 1/2". Contents listed in the table below.

No.	Description		Description No.	
V6	3/16" S.H.	Socket	V14	7/16" D.H. Socket
V7	7/32" "		VS8	1/4" D. Sq. "
V8	1/4" "	* .	VS10	5/16" " "
V9	9/32" "	- 4	VS12	3/8" " "
V10	5/16" D.H.		*V25	Rev. Ratchet 4-3/8"
V11	11/32" "	- 4	V26	Flex. Handle 5-3/4"
V12	3/8" "		V27	Cross Bar 3-1/2"

No. VS13 Set

Contains 13 Pieces-3/16" to 3/8"

Approx. Weight - 1 lb. 2 oz.


This pocket size set is for those that wish to start with the most essential units and build up to a larger skit. Packed in attractively finished metal box measuring 6-3/16" x 2" x 1/2". Other than being minus the ratchet, the contents of this set are identical to the VS14 listed above.

Other Attachments for Extra Small Series

V17—Slide T Handle V18—6" Extension V22—6" Insulated Handle V19—2" Extension "V25—Repair Kit for V25 Ratchet

No. VS30 Set

Contains 30 Pieces-3/16" to 1/2" Approx. Weight 2-3/4 lbs.



An unusually complete set of extra small sockets and attachments, plus an assortment of miniature box and open end wrenches, feeler gauge, ignition plier and pocket size screw driver that any mechanic will find useful for electrical, radio and other small work. Packed in attractively finished metal box measuring 8-7/16" x 3-7/16" x 1". Included in this set are one each of the following:

No.	Description	No.	Description			
V6	3/16" S.H. Socket	E16	Ignition Wrench			
V7	7/32" " "	E18	# #			
V8	1/4" " "	E20				
V9	9/32" " "	E22				
V10	5/16" D.H. "	E24	4 4			
V11	11/32" " "	E26				
V12	3/8" " "	E28				
V14	7/16" " "	E30				
VS8	1/4" D.Sq. "	E40	Ex. Small Box Wrench			
VS10	5/16" " "	E42				
VS12	3/8" " "	E44				
*V25	Rev. Ratchet 4-3/8"	E46				
V26	Flex Handle 5-3/4"	001	Ignition Screw Driver			
V27	Cross Bar 3-1/2"	517	Ignition Plier			
E14	Ignition Wrench	K52	Ignit. Feeler Gauge			

Ignition Wrench Specifications on Page 21

No. VS24 Set


Contains 24 Pieces-3/16" to 1/2" Approx. Weight 2-1/2 lbs.

This is a modified version of the VS30 Set illustrated above. The only difference between them is the VS24 Set does not include a feeler gauge, screw driver or the Midget box wrenches,

3/8" DRIVE SOCKETS AND ATTACHMENTS

The 3/8" drive sockets and attachments have become a must for all good mechanics' tool kits. The new chrome plated, thin wall alloy steel sockets, extra slim handles and attachments, plus lock-non feature, are designed to allow the modern mechanic to get at the tightest spots on modern motors, aircraft and refrigeration units with ease.

Handles and Attachments



No.	Description	No.	Description	No.	Description
T30 T32 *T35 T36	9-3/4" Flexible Handle Cross Bar 6-1/2" Reversible Ratchet 7-3/4" Slide T Handle	T9 T27 T1 T31	16-1/4" Speeder Drag Link Socket 1-1/2" Extension 3"	T5 AT4 AT5 T42	11" Extension 6" Wobble Dr. Extension 12" " " " " " " " " " " " " " " " " " "

^{*} No. T35 Repair Kit for Ratchet No. T35.

3/8" Square Drive Sockets

Open.	Single Hexagon	Open.	Double Hexagon	Open.	Double Square	Open.	Deep Single Hexagon	Open.	Deep Double Hexagon	Open.	Deep Double Square
5/16" 3/8" 7/16" 1/2" 9/16" 5/8"	TH10 TH12 TH14 TH16 TH18 TH20	5/16" 3/8" 7/16" 1/2" 9/16" 19/32"	T10 T12 T14 T16 T18 T19	1/4" 5/16" 3/8" 7/16" 1/2" 9/16"	TS8 TS10 TS12 *TS14 *TS16 *TS18	7/16" 1/2" 9/16" 5/8" 11/16" 3/4"	T140 T160 T180 T200 T220 T240	3/8" 7/16" 1/2" 9/16" 5/8" 11/16"	LT12 LT14 LT16 LT18 LT20 LT22	3/8" 7/16" 1/2" 9/16" 5/8" Dble. Hex.	LTS12 LTS14 LTS16 LTS18 LTS20
11/16* 3/4*	TH22 TH24	5/8" 11/16" 3/4" 13/16" 7/8"	T20 T22 T24 T26 T128	5/8"	*TS20	13/16" 7/8"	T260 T280	3/4" 13/16" 7/8"	LT22 LT24 LT26 LT28	7/16" 1/2" 9/16" 5/8"	TU14 TU16 TU18 TU20

^{*} Semi-deep sockets

No. LT9 Extra Deep Socket Set



Packed in fibre box.

Contains 9 Sockets 3/8" to 7/8"

Weatherhead Sockets

Designed for removing and replacing Weatherhead Fittings without damaging th

nese soft metal par	rts.
No.	Fttg. Size
HW6 HW8 HW10	3/16" 1/4" 5/16"

%" sq. dr. Head Screw Wrenches listed on page No. 25.







This handy attachment permits the use of a speeder or ratchet as a screw driver. The tool is $3-1/2^{\prime\prime}$ long with a $3/8^{\prime\prime}$ wide blade and a $3/64^{\prime\prime}$ thick tip. Not guaranteed.

Money Can Buy The Finest That

GRAY-BONNEY SMALL SERIES 3/8" DRIVE SOCKET SETS

TG21 Set

This set has the straight wall sockets with the pepular double hexagon openings. It has been designed especially for those who want quality with a minimum investment. Contains 21 pieces each selected for the large number of uses to which it may be put. All pieces are made of high quality alloy steel, chrome plated. Packed complete in attractively finished metal container measuring 17-1/4" x 5" x 1".

The TG21 Set includes one each of the following

Size	No.	Description		No. Description Size	No.	Description	
3/8"	T12	D.H.	Socket	11/16"	T22 T24	D.H.	Socket
7/16"	T14 T16	46	44	1/4"	TS8	D.S.	#
9/16"	T18	#	"	5/16"	TS10	44	a
9/32"	T19	- 4	"	3/8"	TS12		"
15/8"	T20	- 44	**				

and the following attachments

No.	Description	No.	Description
T3	Universal Joint 3" Extension 6" " 11" " Speeder	T27	Drag Link Socket
T31		T30	Flexible Handle
T4		T32	Cross Bar
T5		T35	Reversible Ratchet
T9		T36	Sliding Tee Handle

TGI5 Set

This TG15 Set includes the 8 most popular 3/8" drive Single Hexagon Sockets together with two extensions, Universal joint, Reversible Ratchet, Sliding "T" Handle, Flexible Handle and Cross Bar. This selection is ideally suited to aviation and light automotive service work. Supplied in metal box.

Content includes one each of the following

Size	No.	Description		Size	No.	Description
5/16" 3/8" 7/16" 1/2" 9/16" 5/8" 11/16" 3/4"	TH10 TH12 TH14 TH16 TH18 TH20 TH22 TH24	S.H.:	Socket " " " " "		T31 T4 T30 T32 T35 T36 T3	3" Extension 6" " Flex. Handle Cross Bar Rev. Ratchet Sl. "T" Hdle Univ. Joint

TG12 Set

This inexpensive chrome plated set, packed in a neat metal box, is an ideal beginning towards a complete 3/8" drive socket set. True quality with a minimum investment.

Contents of TG12

Size	No.	Desc	ription	Size	No.	Desc	ription
3/8"	T12	D.H.	Socket	3/4"	T24		Socket
7/16"	T14	"		1/4"	TS8	D.S.	44
1/2"	T16	- 44	46	5/16"	TS10	**	4
9/16"	T18	4		3/8"	TS12	#	ш
5/8"	T20	4	4		T30	Flex.	Handle
11/16"	T22	#	"	177	T32	Cross	s Bar

TG21 Set Contains 21 Pieces — 1/4" to 3/4"

Approx. Weight 8 lbs.

TGI5 Set

Contains 15 Pieces — 5/16" to 3/4"
Approximate Weight 33/4 lbs.



TG12 Set

Contains 12 Pieces — 1/4" to 3/4" Approx. Weight 2 lbs.



GRAY-BONNEY EXTRA DEEP SOCKETS 1/2" SQUARE DRIVE SERIES

Gray-Bonney extra-deep sockets find many applications in automotive service work, but are especially suitable for removing and replacing spark plugs. Their overall length, 3-1/4 inches, and the exceptional depth of their openings, give them an advantage over ordinary sockets of similar type. They are made of selected alloy steel, are carefully heat-treated, heavily chrome plated and polished to a high and permanent lustre.







EXTRA - DEEP DOUBLE HEXAGON SOCKETS

Opening	Socket Number	Length	Opening	Socket Number	Lengtl
1/2" 9/16" 5/8" 11/16" 3/4"	LD16 LD18 LD20 LD22 LD24	3-1/4" 3-1/4" 3-1/4" 3-1/4" 3-1/4"	13/16" 7/8" 15/16" 1" 1-1/16" 1-1/8"	LD26 LD28 LD30 LD32 LD34 LD36	3-1/4" 3-1/4" 3-1/4" 3-1/4" 3-1/4'

LD5 Spark Plug Set

This five piece extra-deep Socket Set provides for removal and installation of spark plugs in most car, truck and other engines.

One each of the following sockets included:

LD22 (11/16") LD28 (7/8") LD32 (1") LD26 (13/16") LD30 (15/16")

Supplied in metal box as illustrated.

LDIO Extra - Deep Socket Set

This deluxe set of ten extra-deep double hexagon sockets is ideal equipment for all good mechanics. It provides the full size range needed to service all spark plugs and the deep set nuts used on shackle and most other spring bolts. Supplied in a special steel tray as illustrated.

Sockets for 10MM Plugs

Make of Plug	Socket	Make of Plug	Socket
AC 108, 106, 104-, 104	LD20	Champion Y8, Y6, Y4A	LD20
AC 103	LD18	Champion Y4, Y5	LD20
AC M8, 103-S	LD22	Auto-Lite P6, P4	LD20

Chart of Spark Plug Sockets for Popular Passenger Cars

Make	1946	1947	1948	1949	1950	1951	Make	1946	1947	1948	1949	1950	1951
Buick Cadillac Chevrolet			LD26 see 10mm see10mm	LD26 LD26 LD26	LD26 LD26 LD26	LD26 LD26 LD26	Meteor Monarch Nash	LD26 LD26	LD26	LD26 LD26	LD26 LD26 LD26	LD26 LD26 LD26	LD26 LD26 LD26
Chrysler	LD26	LD26	LD26	LD26	LD26	LD26	Olds.	LD26	LD26	LD26	LD26	LD26 LD26	LD26 LD26
DeSoto Dodge	LD26 LD26	LD26 LD26	LD26 LD26	LD26 LD26	LD26 LD26	LD26 LD26	Packard Plymouth	LD26	LD26	LD26	LD26	LD26	LD26
Ford	LD26 LD26	LD26 LD26	LD26 LD26	LD26 LD26	LD26 LD26	LD26 LD26	Pontiac Stu.Cham.	LD26 LD26	LD26 LD26	LD26 LD26	LD26 LD26	LD26 LD26	LD26 LD26
Hudson Linc.Zeph		LD26	LD26	LD26	LD26	LD26	Stud.Com.	LD26	LD26	LD26	LD28 LD26	LD26 LD26	LD26
Mercury	LD26	LD26	LD26	LD26	LD26	LD26	Willys	LD26	LD26	LD26	LD20	LDZ6	LD26

GRAY-BONNEY 1/2" SQUARE DRIVE SERIES STANDARD AND IMPACT TYPE SOCKETS

Gray-Bonney Standard Series 1/2" Square Drive Sockets are thinner and tougher than ordinary scikets of the same design because each is individually hot forged from the finest electric furnace alloy steel. This ensures accuracy and greater strength. Gray-Bonney sockets are correct in design and size, carefully heat treated for longer wear. They are equipped with the lock-on feature and each is highly polished and heavily chrome plated.

STANDARD TYPE SOCKETS

Double Hexagon		Double	Square	Single	Hexagon
Opening	Number	Opening	Number	Opening	Number
3/8" 7/16"	1406 1407	3/8"	D406S	7/16"	407
1/2"	1408	0/0	174005	7/16	407
9/16"	1409	7/16"	D407S	1/2"	408
19/32" 5/8"	1419		Diana	0.00	
21/32"	1410 1421	1/2"	D408S	9/16"	409
11/16"	1411	9/16"	D409S	5/8"	410
3/4"	1412				1000
25/32" 13/16"	1425 1413	5/8"	D410S	11/16"	411
7/8"	1414	11/16"	D411S	3/4"	412
15/16"	1415				
31/32"	1431	3/4"	D412S	13/16"	413
1-1/16"	1432 1433	7/8"	D414S	7/8"	414
1-1/8"	1434	1/8	D4145	1/0	414
1-3/16"	1435	1"	D432S	15/16"	415
1-1/4"	1436		TO STORY OF THE PARTY OF THE PA	A 100 MAN	

FORD CONNECTING ROD SOCKETS





No. 499-A 1/2" Square Drive 9/16" No. 499—A 1/2 Square Drive 9/16" Single Hexagon Socket for use when adjusting Ford V-8 motor connecting rod bearing cap nuts. The nose of this socket is thin to make this adjustment easy. Not guaranteed.

No. 1421—A 1/2" Square Drive Socket with 21/32" double hexagon opening, used when adjusting Ford Model A motor connecting rod bearing cap nuts.

SINGLE HEXAGON UNIVERSAL JOINT SOCKET

Opening	Number
7/16"	29UJ
1/2"	33UJ
9/16"	37UJ
5/8"	41UJ
11/16"	45UJ
3/4"	49UJ

Drag Link Sockets



Width of Blade	Socket Number	Drive	Application
15/16"	405	1/2" Sq.	Pass. Cars
1-1/4"	4002	.1/2" Sq.	Trucks

No. SW15T Set contains fifteen straight wall sockets: 7/16", 1/2", 9/16", 5/8", 21/32", 11/16", 3/4", 25/32", 13/16", 7/8", 15/16", 1", 1-1/16", 1-1/8" and 1-1/4".

Industrial Sockets for use on Impact Wrenches and Power Runners

Single Hexagon Square Drive Series

These Industrial Square Drive Single Hexagon Sockets are for use with power driven impact wrenches and power nut runners. They are made of select Chrome-Vanadium alloy steel, are heat treated and nickel plated. These Industrial Sockets have additional wall strength needed for maximum life service under extreme operating conditions.

THE REAL PROPERTY.				
A STATE OF THE PARTY OF	STATE OF THE PARTY.	THE REAL PROPERTY.	-	POST ACTION

Not Nick	cel Plated
Opening	Number
13/16" 7/8" 1"	3413 3414 3432
1-1/8"	3434
	*


CT 1 TT 0 1



GRAY-BONNEY STANDARD SERIES 1/2" DRIVE ATTACHMENTS AND ADAPTORS

Gray-Bonney handles and attachments are forged slimmer and lighter for your convenience, due to the use of high carbon alloy steel, scientifically heat-treated to assure maximum strength. All Gray-Bonney attachments are highly polished and heavily chrome plated.

Handles and Attachments



HANDLES AND ATTACHMENTS

ADAPTORS

No.	Description	No.	Description	No.	Openings Female Male
403 603 652 653 653L 655	Connector for 603 Ratchet & Connector 12" Flex. Handle 15" " " 18" " "	709 718S 718 719A 719 720	Universal Joint 2" Forged Extension 5" " 10" " "Rev. Grip 10" " "	4206 4211 4213 4215 4298 4299	1/2" Sq. & 3/4" Sq. 3/4" Sq. & 1" Sq. 1" Sq. & 3/4" Sq. 3/4" Sq. & 3/2" Sq. 1/4" Sq. & 3/2" Sq. 3/4" Sq. & 3/2" Sq.
685 686 687	12" T. Hdl. Rv. Grp. 19" Speeder Rv. Grip. 1416" "	*1497 *4897 2591	10" Reversible Ratchet 10" " " Stud Remvr. (56"-36")	No.	Openings Male Male
699	11" Slide T. Handle atchet Repair Kits under n	umbon anni	ving to retchet	4202	1/2" Sq. & 3/4" Sq.

No. SWI Master Stud Remover



A super-powerful Stud Remover guaranteed to handle the toughest jobs. Fits studis ¼" to ½" diameter. (Has ½"female square drive for use wiscoket attachments and 1" male hexagon for application of wrench if extra leverage required). Oughly dependable in every respect. No more fighting to get stud out of the wrench. Maximum dia. 2". Removes studie located 1" or more apart.

No. 4897 Ratchet



1/2" Square Drive Length 10" Weight 1-1/4 lbs.

This deluxe free wheeling reversible Ratchet was developed for close quarter positive engagement with minimum drag. Its quiet operating mechanism ratchets on every 7½ degrees of turning travel. Chrome plated and guaranteed.

GRAY-BONNEY MASTER SETS

MS102MB82 Set

Contains 102 Pieces

Approx. Weight 112 lbs.

This Master Set MS102MB82 contains the finest and most complete set of Gray-Bonney Tools ever assembled in one kit. 102 pieces — including one of almost every description to do practically any job encountered. Complete sets of sockets and attachments, box wrenches, open end wrenches, tappet wrenches, pliers, hammers, punches, chisels and screw drivers — all are included. The complete assortment is packed in a massive six-drawer metal chest finished in dark blue. It has strong carrying handles and is equipped with a barrel type lock with key. Chest measures 26–7/8" x 13–1/4" x 14–1/4".

NOTE—Tools contained in this set also available in set MS102SB. The SB, MB82 and CC Cabinets illustrated on page 58.



COMPLETE LIST OF CONTENTS LISTED BELOW

Open.	No.	Description	Open.	No.	Description	No.	Description	No I	Description
34	Square I	Orive (See page 3)	1/2" Square Drive			Engi	neers Wrenches	Screw Drivera	
100	VS13	Socket Set	7/16" 1/2"	D407S D408S	Dble, Sq. Socket	1723 1725B	36" X 18"	04	4 ' Rd. Shark
	36° S	quare Drive	9/16"	D409S 405	Drag Link •	1027 1729	194. X 11 18.	08	8 · - 6 · Electricians
3/8" 7/16"	T12 T14	Dble, Hex. Socket	13/16" 7/8"	LD26 LD28 LD30	Deep	1731B 11/6 × 1/8	114 x 1/8	S01	1% * Adjusting
1/2" 9/16"	T16 T18	1: ::	15/16" 1" 1-1/8"	LD30 LD32 LD36		T	opet Wrenches		Pliers
5/8" 11/16"	T20 T22	: :	1-1/0	653 699	15 * Flexible Handle Slide T Handle			B17 258	6 * Diagonal Water Pump
3/4"	T24 T31 T4	3 Extension		655 687	Cross Bar 1414* Speeder	122 2 of 124 2 of	2 of 1/4" x 1/4" 2 of 3/4" x 11/4"	513 7 Combine 517 Ignition Ty	7 Combination Ignition Type
	T5 T9 T35	11 - Speeder Reversible Ratchet		686 19. 718S 2. Extension 718 5. "			Box Wrenches		Battery *
	T36	Sliding T Handle		709 4897	Universal Joint Reversible Ratchet	2384 2386	36" x 16"	212G 212K	1 lb. Ball Pein 4 oz.
	36" Sq	uare Drive			530FF-1-	2387 2388	% x % .	PH15	1/2 lb Soft Face
7/16"	1407 1408	Dble. Hex. Socket		34 . 5	quare Drive			Cont	tainer Options
9/16" 19/32"	1409 1419						Chisels		eference above.
5/8" 21/32" 11/16" 3/4"	1410 1421 1411 1412		1-1/16" 1-1/8" 1-1/4"	HD34 HD36 HD40	Dble. Hex. Socket	C2 C3 C4	Flat 14' x 514'	conta	iner selected. I.E. SB (Set in SB
25/32" 13/16" 7/8"	1425 1413 1414	: :	1-3/8" 1-7/16" 1-1/2" 1-5/8"	HD44 HD46 HD48 HD52	3		Punches	Box) MS102N	AB82 (Set in
15/16" 31/32" 1"	1415 1431 1432	i : :	2.5/6	86 88S 88	Slido T Handle 4 Extension 8	C22 C28 C30	Solid 14 "Pt x 6"1. Pin 16 "Pt x 5"1.	MS102M in C	MB82CC (Set hest with CC r Cabinet)

GRAY-BONNEY COMBINATION SETS

MS79 Combination Set
Contains 79 Pieces—3/16" to 1-5/8"
Approx. Weight 60 lbs.



Gray-Bonney MS79 Set is ideal for the millwright or plant engineer who requires a general purpose wrench set. Tools supplied are identical with sockets and attachments plus open and box end wrenches supplied in set No. MS102 illustrated on page 9. Content includes 3/8" square drive double hexagon sockets and attachments, 1/2" square drive double hexagon, extra deep double hexagon, and double square sockets and attachments, 3/4" square drive double hexagon sockets and attachments, miniature 1/4" square drive sockets and attachments, open end and double hexagon box wrenches. These Chrome-Vanadium alloy steel tools supplied in a strong metal box with removable tray as illustrated. Size of box 21" L x 7-1/2" H x 8-1/8" W.

CS48 Combination Set
Contains 48 Pieces—3/8" to I-5/8"
Approx. Weight 50 lbs.



This CS48 Combination Set was created for the service man who does all types of general repairs on cars, trucks and tractors. It contains a good range of 3/4" square drive double hexagon sockets and attachments including a deluxe heavy duty reversible type ratchet in addition to entire content of SW35 1/2" square drive socket set listed on page 11. This set is recommended to millwrights, construction and plant engineers. Supplied in strong metal box as illustrated.

The CS48 Set includes the following

Open	No.	Description	Open	No.	Description
3/8"	1406	D.H. Socket	15/16"	1415	D.H. Socket
7/16"	1407		31/32"	1431 1432	
9/16"	1409		1-1/16"	1433	
9/32"	1419		1-1/8"	1434	
5/8"	1410		1-3/16"	1435	
21/32"	1421	4 4	1-1/4"	1436	
11/16"	1411	4 4	3/8"	D406S	D.S. Socket
3/4"	1412		7/16"	D407S	
25/32"	1425		1/2"	D408S	
13/16"	1413		9/16"	D409S	
7/8"	1414		5/8"	D410S	" "

3/4" Square Drive Sockets and Attachments

1/2" Square Drive Attachments

Open.	No.	Description	Open.	No.	Description	No.	Description	No.	Description
1" 1-1/16" 1-1/8" 1-1/4" 1-3/8" 1-7/16"	HD36 HD40 HD44	D.H. Socket " " " " " " "	1-1/2" 1-5/8"	HD48 HD52 86 88 87 4285	D.H. Socket " " " 17-1/2" S.T. Hdle. 8" Extension 15-1/2" " Rev. Ratchet	685 687 686 655 709 718S	Tee Handle 14-1/2" Speeder 19" " Cross Bar Universal Joint 2" Extension	718 719 653 699 4897 2591	5" Extension 10" = 15" Flex. Handle 11" Sl. "T" Handle 10" Rev. Ratchet Stud Remover

GRAY-BONNEY COMBINATION AND STANDARD SERIES 1/2" SQUARE DRIVE STRAIGHT WALL SOCKET SETS

Here is a set for the mechanic starting out, containing an assortment of 44 pieces including 1/2" square drive sockets, handles and attachments, pliers, screwdrivers and other miscellaneous tools for which the greatest everyday need will be found. It is inexpensive, yet every piece is of the highest quality. The contents were carefully selected to enable the handling of the greatest variety of repair jobs with the minimum number of tools. The large roomy box measures 21" x 7" x 6" and has ample room for the addition of more tools from time to time. It is equipped with a carrying handle, and a padlock hasp.

The SW44 Set includes one each of the following

Size	No.	Description	Size	No.	Description
7/16" 1/2" 9/16" 19/32" 5/8" 21/32" 11/16" 3/4" 25/32" 13/16"	1407 1408 1409 1419 1410 1421 1411 1412 1425 1413	D.H. Sock.	7/8" 15/16" 1" 1- 1/16" 1- 1/8" 1- 1/4" 13/16" 7/8" 15/16"	1414 1415 1432 1433 1434 1436 LD26 LD28 LD30 LD32	D.H. Sock.


No.	Description	No.	D	escriptio	n	
003 04 08 C3 C5 B17 C23	3" Screwdriver 4" " 8" " Chisel Chisel Chisel Diagonal Plier Punch	686 709 718 719 4897 3114 3116		al Joint		
212G	Ball Pein Hammer	3118	9/16"		*	
513 522 653	Combination Plier Battery Plier 15" Flexible Handle	3120 3122	5/8" 11/16"	:	#	
655	Cross Bar	3124 3128	3/4" 7/8"		-	

This 35 piece socket set is an ideal selection for the mechanic that does general repair work. It is a tool kit any man will be glad to own. It includes all the popular regular design double hexagon and double square straight wall sockets, with a worthwhile assortment of the popular attachments. All pieces are made of the finest alloy steel, heavily chrome plated and will retain their original finish indefinitely. The complete set, large with carrying handle and padlock hasp. Case measures 21" x 7" x 6".

The SW35 Set includes one each of the following

Size	No.	Description	Size	No.	Description
3/8"	1406	D.H. Sock.	15/16"	1415	D.H. Sock.
7/16"	1407	* *	31/32"	1431	4 4
1/2"	1408		1"	1432	
9/16"	1409	4 4	1- 1/16"	1433	
19/32"	1419		1- 1/8"	1434	
5/8"	1410		1- 3/16"	1435	
21/32"	1421	* "	1- 1/4"	1436	
11/16"	1411		3/8"	D406S	D.Sq. Sock.
3/4"	1412		7/16*	D407S	s s
25/32"	1425		1/2"	D408S	
13/16"	1413	* *	9/16*	D409S	
7/8"	1414		5/8"	D410S	

No.	Description	No.	Description	No.	Description
686	Tee Handle 14–1/2" Spdr. 19" " Cross Bar	709 718S 718 719	Univ. Joint 2" Extension 5" "	653 699 4897	15" Flex. Handle 11" S.T. Handle 10" Deluxe Ratchet



Approx. Weight 37-1/4 lbs.



SW 35 Set

Contains 35 Pieces—3/8" to 1-1/4"
Approx. Weight 31 lbs.



GRAY-BONNEY STANDARD SERIES 1/2" SQUARE DRIVE STRAIGHT WALL SOCKET SETS

SW23 Set

Contains 23 Pieces-7/16" to 1-1/4". Approx. Weight 15-3/4 lbs.

This SW23 set has straight wall sockets with the popular double hexagon openings. It contains sockets with openings that find the most general use plus an excellent assortment of handles and attachments. Each piece is made from carefully selected alloy steel, scientifically heat treated and heavily chrome plated. The substantial metal box has a carrying handle and measures 20-1/4" x 6-1/2" x 1-11/16".



Contents of SW23

Contents of Sw25							
Size	No.	Sockets	Size	No.			
7/16" 1/2" 9/16" 19/32" 5/8" 21/32" 11/16" 3/4"	1407 1408 1409 1419 1410 1421 1411 1412	one each	25/32" 13/16" 7/8" 15/16" 1" 1- 1/16" 1- 1/8" 1- 1/4"	1425 1413 1414 1415 1432 1433 1434 1436			

No.	Description	No.	Description
653 655 686 709	15" Flexible Handle Cross Bar 19" Speeder Universal Joint	718 719 4897	5" Extension 10" Extension 10" Deluxe Reversible Ratchet

SW20 Set

Contains 20 Pieces-7/16" to 1". Approx. Weight 14 lbs.

This SW20 set has thirteen straight wall double hexagon sockets and an assortment of the most desirable attachments. Packed in attractive metal case measuring 20-1/4" x 1-11/16". All pieces are of high quality alloy steel heavily chrome plated. It makes an ideal set for use either in the shop or on the job.



Contents of SW20

Size	No.	Sockets	Size	No.
7/16"	1407	one each	3/4"	1412
1/2"	1408	4	13/16"	1413
9/16"	1409		25/32"	1425
19/32"	1419		7/8"	1414
5/8"	1410		15/16"	1415
21/32"	1421	4	1"	1432
11/16"	1411	- 4		

No.	Description
653 655 686 709 718 719 4897	15" Flexible Handle Cross Bar 19" Speeder Universal Joint 5" Extension 10" Extension 10" Deluxe Reversible Ratchet

GRAY-BONNEY STANDARD SERIES 1/2" SQUARE DRIVE STRAIGHT WALL SOCKET SETS

This SW18 set has ten popular size regular straight wall sectets and three of the extra deep sockets, all with double hexagon openings. It also includes a high quality deluxe reversible ratchet and other attachments as listed below. These tools are supplied in a sturdy metal case large enough to accommodate additional tools. The case complete with handle and lock hasp measures $21^{\circ}\times 7^{\circ}\times 6^{\circ}$.

The SW18 Set includes one each of the following

Open	No.	Description	Open	No.	Description
7/16" 1/2 " 9/16" 19/32" 5/8 " 21/32" 11/16"	1407 1408 1409 1419 1410 1421 1411	D.H. Socket	3/4 " 13/16" 7/8 " 13/16" 7/8 " 15/16"	1412 1413 1414 LD26 LD28 LD30	D.H. Socket " " Ex. Dp. Sock " " "

Plus one each of the following

No.	Description	No.	Description		
686 699 4897	19" Speeder 11" Slide T Handle Deluxe Reversible Ratchet	718 719	5" Extension 10" "		

This SW15 is an inexpensive set for the beginner or the man who wishes to do his own repairs. The set contains the same high quality straight wall sockets, handles and deluxe ratchet as the larger sets. It is packed in an attractive metal box which has ample room for additional tools.

The SW15 Set includes one each of the following

Open.	No.	Description	Open.	No.	Description	
7/16"	1407 1408	D.H. Socket	21/32" 11/16"	1421 1411	D.H. :	Socket
9/16"	1409		3/4 "	1412	- 11	- 65
19/32"	1419	4 4	13/16"	1413	#	"
5/8"	1410		7/8"	1414	44	46

Plus one each of the following Handles and attachments

No.	Description	No.	Description		
686 699 4897	19" Speeder 11" Slide T Handle Deluxe Reversible Ratchet	718 719	5" Extension		

This SW14 Nut Spinner Set contains twelve thin straight was sockets, and a 15° flexible handle and cross bar. It is an ideal set for the service station or service man doing light repairs. All pieces are made of the finest quality alloy steel and are finished in chromium. This set comes in a metal box.

The following Sockets and Handles are included.

Open.	No.	Description		Open.	No.	Descr	ription
7/16"	1407 1408	D.H.	Socket "	11/16"	1411 1412	D.H.	Socket
9/16"	1409		4	13/16"	1413	44	44
19/32"	1419		4	7/8"	1414		44
5/8"	1410		"	15/16"	1415		- 44
21/32"	1421	44	4	1"	1432	#	44

Plus No. 653 15" Flexible Handle and No. 655 Cross Bar.

SW18 Set

Contains 18 Pieces-7/16" to 7/8" Approx, Weight 19-3/4 lbs.



SW15 Set

Contains 15 Pieces—7/16" to 7/8" Approx. Weight 12-1/2 lbs.



SW14 Nut Spinner Set Contains 14 Pieces—7/16" to 1"



GRAY-BONNEY SPECIAL SOCKET SET AND TORQUE WRENCHES

HY10 Set

Contains 10 Pieces
Hydraulic Transmission Set
Approx. Weight 434 lbs.



The HY10 Set is for servicing oil change work on Hydra-matic and Dynaflow transmissions. Supplied in metal box as illustrated.

CONTENT OF HY10 SET

No.	Description	Use
T128	7/8" D.H. Socket	Hydramatic Oil Pan Plug
TH18	9/16" S.H. Socket	Flywheel Cover Bolts
TH16	1/2" S.H. Socket	Flywheel Cover Bolts
TH14	7/16" S.H. Socket	Hydramatic fluid plug
TS9	9/32" S.S. Socket	Dynaflow Torque Con- verter drain plugs
T4	6" Extension	Wrench extension
T35	3/8" DR. Ratchet	For above wrenches
W6	3/16" H.S.wrench	Hydramatic old type fluid cplg drain plugs
04	4" Screw Driver	To rotate flywheels
2895A	15/16" x 1" Box	Wrench for dynaflow trans. oil pan plug

Torque Wrenches

NF Series



These permanently accurate Torque Wrenches are available in six different sizes, each of a different torque capacity. This enlarged size range will serve the majority of gasoline and diesel type engines. The double scale is easily read from almost any position.

No.	Sq. Drive	Scale Range (Ft. Lbs.)
NF25	3/8"	25 Ft. Lbs.
NF50	1/2"	50 Ft. Lbs.
*NF100	1/2"	100 Ft. Lbs.
NF150	1/2"	150 Ft. Lbs.
NF200	1/2"	200 Ft. Lbs.
†NF300	3/4"	300 Ft. Lbs.


*The range of Model NF100 is ideal for most automotive applications.

†NF300 is recommended for diesel engine service.

NOTE-Other capacities available, information on request.

See inside back cover for torque application information.

GRAY-BONNEY HEAVY DUTY SERIES 3/4" SQUARE DRIVE SOCKET ATTACHMENTS



No.	Description	No.	Description
86	17-1/2" Slide T. Hdle. 4" Forged Extension 8" Forged Extension 15-1/2" Forged Extension Ratchet Plug Connector 19" Ratchet Bar Type Stud Remover with Wedges (9/16" to 1")	2590-1	Lt. Wedge for 2590
88S		2590-2	Heavy Wedge for 2590
88		4284	Speeder
87		*4285	20" Reversible Ratchet
89		4288	22" Flex. Handle
*98		4289	Cross Bar
2590		4295	Univ. Joint

*Order Ratchet Repair Kits under Number Applying to Ratchets

3/4" HEAVY DUTY SOCKETS

11	uare"	"Double Se	11/2/11/21	ragon"	"Double Hex	
17.00	Description	Number	Opening	Description	Number	Opening
1	D. Sq. Socket "" "" "" "" "" "" "" "" ""	S4228 S4232 S4234 S4240 S4246	7/8" 1" 1-1/16" 1-1/4" 1-7/16"	D. H. Socket	HD28 HD30 HD31 HD32 HD34 HD36	7/8" 15/16" 31/32" 1" 1-1/16" 1-1/8"
	agon''	"Single He			HD38 HD40 HD42	1-3/16" 1-1/4" 1-5/16"
	S. Hex. Socket	4266 4268 4272	2-1/16" 2-1/8" 2-1/4"	:::	HD44 HD46 HD48 HD50	1-3/8" 1-7/16" 1-1/2" 1-9/16"
Heavy	le Hexagon''	a Deep Sing	"Extr		HD52 HD54	1-5/8" 1-11/16"
Dou	S.H. Deep Socket	LH32 LH34 LH36 LH40	1" 1-1/16" 1-1/8" 1-1/4"	4 4 4 4 4 4	HD56 HD60 HD64 HD70	1-3/4" 1-13/16" 1-7/8" 2" 2-3/16"



Heavy Duty Socket Double Hex.

GRAY-BONNEY HEAVY DUTY SERIES 3/4" SQUARE DRIVE SOCKET SETS

HD25 Set

Contains 25 Pieces 7/8" to 2-3/16"

Approximate Weight 41-1/2 lbs.



This is an extremely fine heavy duty socket wrench set. It contains a complete range of the heavy duty alloy steel forged sockets with double hexagon openings in sizes from 7/8" to 2-3/16", a super heavy reversible ratchet and the other heavy duty attachments as listed below. This is a deluxe set built for hard usage. All pieces are chrome plated and contained in a strong metal box. Set includes one each of:

Open.	No.	Description	Open.	No.	Descr	iption
7/8"	HD28	H.D. Sock.	1- 1/2"	HD48	H.D.	Sock.
15/16"	HD30	H . H	1- 9/16"	HD50		**
1"	HD32	# #	1-5/8"	HD52	- 4	
1- 1/16"	HD34	4 4	1-11/16"	HD54	- 46	46
1-1/8"	HD36	4 4	1-3/4"	HD56	#	#
1- 3/16"	HD38	4 4	1-13/16"	HD58	- 66	84
1- 1/4"	HD40		1- 7/8"	HD60	- 4	44
1- 5/16"	HD42	14 16	9"	HD64	-	#
1- 3/8"	HD44	4 4	2- 3/16"	HD70	- 4	44
1- 7/16*	HD46		2 0/10			

plus the following attachments:

No.	Description	No.	Description
86	17-1/2" Slide T Handle	88S	4" Extension
87	15-1/2" Extension	4285	Reversible Ratchet
88	8" "	4288	22" Flex. Handle

HD21 Set

Contains 21 Pieces-7/8" to 2"

Approx. Weight 33-1/2 lbs.



This heavy duty set contains a broad range of the heavy duty alloy steel sockets, including sizes from 7/8" to 2". It was designed to handle the heavy work on busses, trucks, tractors and all types of heavy industrial machinery. It is packed in a strong metal box and contains one each of the following:

Open.	No.	Description	Open.	No.	Description
7/8"	HD28	H.D. Sock.	1- 3/8"	HD44	H.D. Sock
15/16"	HD30	# #	1- 7/16"	HD46	
1"	HD32	# #	1- 1/2"	HD48	
1- 1/16"	HD34	# #	1- 5/8"	HD52	
1- 1/8"	HD36		1- 3/4"	HD56	
1- 3/16"	HD38		1-13/16"	HD58	
1- 1/4"	HD40		1-7/8"	HD60	
1 5/16"	HD42	4 4	2"	HD64	W W

and following attachments:

No.	Description	No.	Description
86 88 88S	17-1/2" Slide T Handle 8" Extension 4" "	87 4285	15-1/2" Extension Reversible Ratchet

GRAY-BONNEY HEAVY DUTY SERIES 3/4" SQUARE DRIVE SOCKET SETS

The HD15 Set consists of fifteen well selected pieces chosen to provide a wide range in heavy duty types and sizes with a minimum investment. Supplied in strong metal box.

Content includes

Open	No.	Description	Open	No.	Description
7/8"	HD28	H.D. Socket	1-3/8"	HD44	H.D. Socket
1"	HD32	"	1-7/16"	HD46	
1-1/16"	HD34	ш	1-1/2"	HD48	- 44
1-1/8"	HD36	44	1-5/8"	HD52	**
1-1/4"	HD38	"	1-3/4"	HD56	- 44

and following attachments

No.	Description	No.	Description
86	17-1/2" Slide T handle	98	19" Ratchet
87	15-1/2" Extension	89	Ratchet Connector
88	8" Extension		

The HD13 Set is the same as No. HD11 with the addition of a No. 98 Ratchet and the No. 89 Connector. Supplied in metal box shown with HD11 below.

HD15 Set

Contains 15 Pieces—7/8" to 1-3/4" Approx. Weight — 241/2 lbs.



HD13 Set

Contains 13 Pieces—1" to 1-5/8" Approx. Weight 23¾ lbs.

This set is especially valuable for the user who requires heavy duty tools at a minimum investment. It can be built up into the big HD21 set as the same box is used for both sets. It contains one each of the following:

Open.	No.	Descr	iption	Open.	No.	Desc	ription
1" 11/4" 11/4"	HD32 HD34 HD36 HD40	D.H. S	Socket "	13/6" 11/6" 11/2"	HD44 HD46 HD48 HD52	D.H.	Socket "

and following attachments

No.	Description	No.	Description
86 88	171/2" Slide T Handle 8" Extension	87	15½" Extension

HDII Set
Contains II Pieces—I" to 1-5/8"
Approx. Weight 18-3/4 lbs.





GRAY-BONNEY EXTRA HEAVY DUTY SERIES 1" SQUARE DRIVE SET AND SOCKETS

Extra Heavy-Duty Hexagon Sockets Chromium Plated

	Regular Series		Heavy Series	Light Series	C	
No. Opening	Bolt Size	Nut Size	Bolt & Nut Size	Nut Size	Cap Screw	
X46 X48 X52 X58 X60 X64 X70 X72 X74 X78 X80 X82 X84 X88 X84 X88 X94	1-7/16" 1-1/2" 1-5/8" 1-13/16" 1-7/8" 2-3/16" 2-1/4" 2-5/16" 2-7/16" 2-7/16" 2-5/8" 2-1/2" 2-5/8" 2-15/16" 3-3/8"	1" 1-1/4" 1-1/2" 1-5/8" 1-3/4"	1" 1-1/4" 1-1/2" 1-5/8" 1-3/4"	7/8" 1" 1-1/8" 1-1/4" 1-3/8" 1-1/2" 1-5/8" 1-5/8"	1" 1-1/8" 1-1/4" 1-3/8" 1-1/2"	1-1/8"

Extra Heavy-Duty Handles and Attachments

No.	Description	No.	Description
X29 X30 X31	Extension, 8-1/2" long Extension, 17-1/2" long Sliding Bar, 22" long	X32 X33	Drive Head, Male Drive Head, Female

No. XH Extra Heavy-Duty Socket Set 12 Pieces

The Bonney XH Set contains all the most useful 1" square drive hexagon sockets and

Designed for extra heavy-duty work on buses, trucks, tractors, marine engines and equipment, and industrial machinery. Packed in a metal box 23" x 6" x 5", with carrying handle, padlock hasp, and end catches, the set includes one each of the following:



No.	Description
X46	1-7/16" Hexagon Socket
X48	1-1/2" Hexagon Socket
X52	1-5/8" Hexagon Socket
X58	1-13/16" Hexagon Socket
X64	2" Hexagon Socket
X70	2-3/16" Hexagon Socket
X76	2-3/8" Hexagon Socket
X29	Extension, 8-1/2" long
X30	Extension, 17-1/2" long
X31	Sliding Bar, 22" long
X32	Drive Head, Male
X33	Drive Head, Female

Net Weight 42 lbs.



GRAY-BONNEY CHROME VANADIUM ENGINEER'S WRENCHES

Drop Forged 15° Angle Opening — Chrome Plated With Polished Heads

Wrench No.	Openings Milled	U.S.S. Bolt Size	Hex. Head Cap Screw	S.A.E. Standard Screws and Nuts	Extreme Length	Thick- ness of Head	eshi h		1 0
1019	3/16 & 1/4				2-3/4	7/64			
1020	1/4 & 5/16	& 1/8	& 1/8	& 1/8	3	9/64			
1721 1021 1722 1723	5/16 & 3/8 5/16 & 13/32 5/16 & 7/16 3/8 & 7/16	1/8 & 1/8 & 3/16 1/8 &	1/8 & 3/16 1/8 & 1/8 & 1/4 3/16 & 1/4	& 1/4 & 1/4	5	3/16			
1022 1023 1723A	5/16 & 1/2 13/32 & 1/2 3/8 & 1/2	1/8 & 1/4 3/16 & 1/4 & 1/4	1/8 & 5/16 & 5/16 3/16 & 5/16	& 5/16 & 5/16 & 5/16	5	3/16	A		
1024 1725 1725B 1025 1725A	13/32 & 19/32 7/16 & 1/2 1/2 & 9/16 1/2 & 19/32 7/16 & 9/16	3/16 & 5/16 & 1/4 1/4 & 1/4 & 5/16	1/4 & 5/16 5/16 & 3/8 5/16 & 1/4 & 3/8	1/4 & 5/16 5/16 & 3/8 5/16 & 1/4 & 3/8	6-1/4	7/32		ADE IN CA	
1726 1026 1727 1027 1027C 1027C	1/2 & 5/8 1/2 & 11/16 9/16 & 5/8 19/32 & 11/16 9/16 & 11/16 5/8 & 11/16	1/4 & 1/4 & 3/8 1/4 & 3/8 5/16 & 3/8 & 3/8 & 3/8	5/16 & 7/16 5/16 & 3/8 & 7/16 3/8 & 7/16 &	5/16 & 7/16 5/16 & 3/8 & 7/16 3/8 & 7/16 &	7	1/4		GRAY	
1028S 1729 1029	5/8 & 25/32 5/8 & 3/4 11/16 & 25/32	& 7/16 3/8 & 7/16	7/16 & 7/16 & 1/2	7/16 & 7/16 & 1/2	8	9/32		CHRO	
1028 1728 1730 1030	19/32 & 25/32 9/16 & 3/4 5/8 & 13/16 11/16 & 7/8	5/16 & 7/16 	3/8 & 1/2 7/16 & 9/16 & 5/8	3/8 & 1/2 7/16 & & 9/16	8	9/32		CHEOME-VANADIUM	
1731 1731A 1033	3/4 & 13/16 3/4 & 7/8 7/8 & 31/32	& 1/2 1/2 & 9/16	1/2 & 9/16 1/2 & 5/8 5/8 &	1/2 & 1/2 & 9/16 9/16 &	9	11/32		ANA	
1031 1731B 1732A 1032 1732 1033A	25/32 & 7/8 13/16 & 7/8 3/4 & 1 25/32 & 31/32 13/16 & 1 7/8 & 15/16	7/16 & 1/2 & 1/2 7/16 & 9/16 1/2 &	& 5/8 9/16 & 5/8 1/2 & 3/4 9/16 & 3/4 5/8 &	& 9/16 & 9/16 1/2 & 11/16	9	11/32		DIUM	
1033C 1034A 1035 1735	15/16 & 1 15/16 & 1-1/16 31/32 & 1-1/16 1 & 1-1/8	& 5/8 9/16 & 5/8	& 3/4 3/4 & 7/8	5/8 & 11/16 5/8 & 3/4 & 3/4 11/16 &	10-3/4	3/8	1		
1733 1034 1734	7/8 & 1 7/8 & 1-1/16 7/8 & 1-1/8	1/2 & 1/2 & 5/8 1/2 & 5/8	5/8 & 3/4 5/8 & 5/8 & 7/8	9/16 & 11/16 9/16 & 3/4 9/16 &	10-3/4	3/8			V
1736 1037 1737 1037A	1 & 1-1/4 1-1/16 & 1-1/4 1-1/8 & 1-1/4 1-1/8 & 1-5/16	5/8 & 3/4 & 3/4 & 3/4	3/4 & 1 & 1 7/8 & 1 3/4 & 7/8	11/16 & 7/8 3/4 & 7/8 & 7/8 3/4 & 7/8	12 12	7/16		•	
1038A 1738 1739 1039 1739A 1739B	1-5/16 & 1-7/16 1-1/8 & 1-3/8 1-1/4 & 1-3/8 1-1/4 & 1-7/16 1-1/4 & 1-1/2 1-3/8 & 1-1/2	& 7/8 3/4 & 3/4 & 7/8 3/4 &	1 & 1-1/8 7/8 & 1-1/8 1 & 1-1/8 1 & 1/1/4 1-1/8 & 1-1/4	& 7/8 7/8 & 7/8 & 1 7/8 &	14	1/2			
1041	1-7/16 & 1-5/8	7/8 & 1	& 1-3/8	1 & 1-1/8	15-1/2	9/16			


GRAY-BONNEY ENGINEERS' WRENCHES AND SETS

No. 12ALR Automotive Wrench Set



No. 12ALR set contains twenty different openings in sizes from 1/4" to 1-1/4". This is an ideal set for general repair service. The following twelve popular usage wrenches are included—1020, 1723, 1024, 1725B, 1725A, 1027S, 1730, 1731, 1031, 1033C, 1035, 1737.

Set 12 ALR in leatherette roll as illustrated.



No. 10E set contains fifteen different openings in sizes from 5/16" to 1-1/16". The following ten wrenches are supplied—1721, 1723, 1725, 1725B, 1727, 1027, 1729, 1031, 1732, 1034A.

Set 10 ELR in leatherette roll as illustrated. Set 10 ECB supplied in fibre box.

Right Angle Wrenches



Openings in the most necessary sizes for wrenches of this type. Drop forged of alloy steel and chrome plated with polished heads. These right angle open end wrenches are ideal for working in close quarters.

No.	Openings	Length	Head Thickness
2723	3/8" & 7/16"	4-1/4"	7/32"
2725B	1/2" & 9/16"	5-1/2"	15/64"
2729RA	5/8" & 3/4"	7-1/2"	5/16"

No. 8ALR Automotive Wrench Set



No. 8ALR set contains sixteen different openings in sizes from 1/4" to 1-1/4". This is a good set for the man who desires a wide range with minimum investment. The following 8 wrenches supplied—1020, 1723, 1725B, 1027S, 1731, 1033A, 1735, 1037.

Set 8 ALR in leatherette roll as illustrated.



No 6E contains twelve different openings in sizes from 3,8" to 1". The following six wrenches are supplied—1723, 1025, 1027C, 1028S, 1731A, 1033C. Set 6ELR in leatherette roll as illustrated. Set 6ECB supplied in fibre box.



No.	Openings	Length	
2509	9/16" 45° & 90°	6-3/8"	

ELECTRICAL AND IGNITION WRENCHES AND SETS

Gray-Bonney Ignition Wrenches are correctly designed, and have the heads offset at angles of 15 and 60 degrees. Each size is available in either angle head. They are forged from alloy steel, giving extreme lightness with the necessary strength.

No. 16 Ignition Wrench Set



Gray-Bonney Ignition Wrenches are available in handy leatherette rolls. The No. 16 Set, shown above, contains nine wrenches ranging from 13/64" to 1/2". The set is designed so that each opening is duplicated, one having 15" angle and the other a 60" angle. In leatherette case.

No.	Openings		Land	Thickness	
NO.	15° End	60°End	Length	1 nickness	
E14 E16 E18 E20 E22 E24 E26 E28	13/64" 15/64" 7/32" 1/4" 9/32" 5/16" 11/32" 3/8"	15/64" 13/64" 1/4" 7/32" 5/16" 9/32" 3/8" 11/32"	3" 3" 3" 3" 3-1/2" 3-1/2" 4"	7/64" 7/64" 7/64" 7/64" 1/8" 1/8" 9/64" 9/64"	
E.30	7/16"	1/2"	4-1/2"	5/32"	

No. 21LR Extra Small Box Wrench Set




Ideal for work on radios, ignition systems, generators, starters, heaters, etc. E40 and E42 have single hexagon openings; E44 and E46 have double hexagon openings.

No. 21LR Set, 1 each of above 4 Wrenches in a leatherette roll.

Extra Small Box Wrenches

No.	Openings	Length
E40	3/16" & 13/64"	2-7/8°
E42	7/32" & 15/64"	3-1/8°
E44	1/4" & 9/32"	3-3/8°
E46	5/16" & 11/32"	3-3/4°

No. 17 Ignition Wrench Set



No. 17 Set contains the same wrenches as No. 16, with the addition of No. 517 pliers and No. 001 screwdriver. In leatherette roll.

No. 20LR Zenel Miniature Wrench Set



Delicate jobs on magnetos, generators, radios, timers, oil cleaners, carburetors, electrical parts and similar jobs are quickly done with Gray-Bonney Miniature Wrenches. The No. 29 Set contains one each of Nos. H10, H12, H14, H16 and H18 listed below. They are made of ZENEL, have panelled handles and are chrome plated. In leatherette roll,


Zenel Miniature Wrenches

No.	Openings Milled	Length	Thick Heads
H10	3/16" & 7/32"	2-1/2"	3/32"
H12	1/4" & 9/32"	3"	5/32"
H14	5/16" & 11/32"	3-3/4"	3/16"
H16	3/8" & 7/16"	4-1/8"	7/32"
H18	13/32" & 15/32"	4-1/8"	7/32"

GRAY-BONNEY BOX WRENCHES AND SETS

No. 2311 Box Wrench Set

3/8" to 7/8"



The 2300 (Long) Series Box Wrenches, having one end straight and one offset, are used to good advantage when tightening the manifolds or servicing hard-to-get-at nuts. They are time savers for the motor mechanic.

No. 2311LR.—2300 Series Box Wrench Set contains one each of the 2300 Series Long and Short Wrenches listed below. Supplied in leatherette roll as illustrated.

No. 2307LR.—This set includes one each of the seven Long Type 2300 Series Box Wrenches listed below. Supplied in leatherette roll as illustrated.

Long Type Box Wrenches

2300 Series

No.	Double Hexagon Openings	Length
2316	1/2"	9"
-2318	9/16"	9-1/2"
2320	5/8"	10"
2322	11/16"	11"
2324	3/4"	11-1/2"
2326	13/16"	12"
2328	7/8"	12-3/4"

Short Type Box Wrenches



This series of Short Box Wrenches will appeal very strongly to the mechanic who enjoys using fine tools. They are drop forged from high grade alloy, and are brightly polished all over. The heads are thin and cleanly broached and will give the utmost in service under all conditions.

No. 270LR.—Set of these four Short Box Wrenches in leatherette roll.

No.	Double Hexagon Openings	Length
276	3/8" x 7/16"	4-1/2"
277	1/2" x 9/16"	5-1/4"
278	5/8" x 11/16"	6"
279	3/4" x 13/16"	6-1/4"

Tu-Type Wrench Sets



This type of wrench is very popular where speed is required. The box end is handy to loosen tight nuts and get in around manifolds and carburetors. The open end is used for faster turning. Forged from Chrome-Vanadium Steel. Sizes 3/8" to 1" polished and chrome plated; larger sizes satin plated.

No. TU7—This set contains seven wrenches, Nos. 3114 to 3128 providing openings from 7/16" to 7/8", not including 13/16" size. Supplied in leatherette roll

No. TU9—Contains nine wrenches including the seven supplied in the TU7 set plus Nos. 3112 and 3132. Contained in leatherette roll.

No. TU11—Contains eleven wrenches Nos. 3112 to 3132 (not 3129) providing openings from 3/8" to 1". Supplied in leatherette roll.

Tu-Type Wrenches

No.	Openings	Length	No.	Openings	Length			
3112	3/8"	5"	3128	7/8"	10-1/2"			
3114	7/16"	5-3/8"	3129	29/32"	13-1/2"			
3116	-1/2"	6"	3130	15/16"	13-1/2"			
3118	9/16"	6-3/4"	3132	1"	13-1/2"			
3120	5/8"	7-3/4"	3134	1-1/16"	14-3/4"			
3122	11/16"	8-3/8"	3136	1-1/8"	14-3/4"			
3124	3/4"	9-1/2"	3140	1-1/4"	16-1/4"			

Short Type Box Wrenches



2300 Series

No.	No. Double Hexagon Openings	
2384	3/8" & 7/16"	5-1/8"
2386	1/2" & 9/16"	5-1/2"
2387	9/16" & 5/8"	5-3/4"
2388	5/8" & 3/4"	8-1/2"

GRAY-BONNEY BOX WRENCHES AND SETS

No. DO 6 Double Offset Set



The No. DO6 set contains one each of Nos. 2804L, 2805L, 2807A, 2808, 2809B and 2810 listed below.

Double Offset Box Wrenches

45° Angle

The long, smooth, round handles will give plenty of leverage to loosen the toughest nuts. These wrenches have a deep offset to clear obstructions and give plenty of finger room.


No.	Double Hexagon Openings	Length
2804L 2804C 2805L 2807A	3/8" & 7/16" 7/16" & 1/2" 1/2" & 9/16" 5/8" & 11/16"	8-9/16" 8-1/2" 9"
2807 2808 2809 B	5/8" & 3/4" 3/4" & 7/8" 25/32" & 13/16"	11" 11-1/2" 12"
2809 2810	7/8" & 15/16" 15/16" & 1"	12-1/2"

	INDUSTRIAL SIZES
2811B	15/16" & 1-1/16"

2811B	15/16" & 1-1/16"	14-1/2"
2811	1" & 1-1/8"	14-1/2"
*2811E	7/8" & 1-1/16"	14-1/2"
*2812B	1-1/16" & 1-1/4"	17"
*2812C	1-1/8" & 1-1/4"	17"
2812	1-1/4" & 1-3/8"	17"
*2812A	1-1/4" & 1-7/16"	19-5/8"
2812E	1-5/16" & 1-1/2"	19-5/8"
2813	1-7/16" & 1-5/8"	19-5/8"
2813A	1-1/2" & 1-11/16"	19-5/8"
2815	1-13/16" & 2"	24"
2815B	1-7/8" & 2"	24"
2815A	2" & 2-3/8"	26"
2819	2-3/16" & 2-3/8"	26"
2821	2-9/16" & 2-3/4"	28"

^{*}Will discontinue when stocks depleted.

No. 15 Box Wrench Set



No. 15 Box Wrench Set contains one each of the following wrenches: Nos. 2890, 2891, 2892, 2893, 2894, and 2895. In leatherette roll as illustrated.


15 Deg. Angle Box Wrenches

The No. 2890 Series Box Wrenches are for work with low overhead clearance. Heads are at angles of from 10 degrees to 15 degrees, depending on the length of the wrench. All have double hexagon openings and are chrome-plated with polished heads. Chrome Vanadium Steel.

No.	Double Hexagon Openings	Length
2890	3/8" & 7/16"	7-5/8*
2891	1/2" & 9/16"	8-5/8*
2892	5/8" & 11/16"	9-5/8*
2892A	5/8" & 3/4"	9-5/8*
2893A	3/4" & 25/32"	11"
2893	3/4" & 13/16"	11"
2894A	13/16" & 7/8"	13-1/4"
2894	7/8" & 15/16"	13-1/4*
2895A	15/16" & 1"	15-1/2*
2895	1" & 1-1/16"	15-1/2"
2896	1-1/8" & 1-3/8"	17"
2897	1-1/4" & 1-7/16"	17"

GRAY-BONNEY TAPPET WRENCHES MANIFOLD AND CASTOR-CAMBER

Standard Tappet Wrench Sets




No. 6T Set consists of 6 Chrome-Vanadium Tappet Wrenches, 2 each Nos. 122A, 124A and 124B, covering openings 7/16" & 1/2", 9/16" & 5/8", 11/16" & 3/4". In leatherette roll as illustrated.

No. 4T Set consists of 4 Wrenches, 2 each Nos. 122 and 124, covering sizes 1/2", 9/16", 5/8" and 11/16". In leatherette roll.

No. 2883

Manifold Wrench for Chrysler



A special tool of Chrome-Vanadium Steel designed for use on the manifold nuts of Chrysler-made cars. This tool is chrome plated with heads buffed to a high and permanent lustre. The double hex openings are 5/8" and 9/16". Length 9".


No. 2319 Starter and Manifold Wrench



Standard Tappet Wrenches


No.	Size Openings	Length	Thickness Heads
122A	7/16" & 1/2"	8"	5/32"
122B 122	17/32" & 21/32"	8"	5/32"
124A	9/16" & 5/8"	8-1/2"	3/16"
124	5/8" & 11/16"	8-1/2"	3/16"
124B 426	11/16" & 3/4" 3/4" & 7/8"	8-1/2"	3/16" 7/32"
428	15/16" & 1"	9-1/2"	7/32"

Extra Long Tappet Wrenches



No. 2884

Starter and Manifold Wrench



No. 2586 Carburetor Wrench

A special tool for adjusting Ford V-8 Carburetor Jets. It is an accurate tool for the precision adjustments required. Made from Chrome-Vanadium Steel but not guaranteed.

Castor-Camber Crowfoot Type 1/2 Square Drive Wrenches



These 1/2 inch square drive attachments fit between arms on either side of the adjusting nut, ellminating need for removal of arms in order to obtain clearance to adjust camber and castor.

No.	Opening	Application	
1203 1205 1207 1209	1-3/16" 1-5/16" 1-7/16" 1-1/2"	Meteor and Ford (also use 1205) Monarch, Mercury, Meteor, Ford Chrysler Cars, 1941-49, except 7 pass, models Chrysler 7 pass Sonatons and New Yorkon	

Castor adjustment is most satisfactory handled on the following 1949 cars by using the thin single end wrench No. 1238.

No.	Openings	Fits
1238	1-3/16"	Ford, Lincoln, Mercury



GRAY-BONNEY ADJUSTABLE AND HEAD SCREW WRENCHES

Dreadnaught Adjustable Wrenches



These Adjustable Wrenches are drop forged from special analysis tool steel. Fully tempered and heat treated, with polished heads and nickel plating.

No.	Size	Max. Opening	Std. Box Quantity	Weig Box	
DAW6	6"	3/4"	6	2-1/2	Lbs
DAW8	8"	15/16"	6	4	44
DAW10	10"	1-1/8"	6	6	-
DAW12	12"	1-5/16"	6	11	*

Gray-Alloy Adjustable Wrenches



The Gray-Alloy light weight Adjustable Wrench is forged from high-grade alloy steel. It is thinner and lighter, yet much stronger than the standard pattern.

No.	Size	Max. Opening
91-4	4"	1/2"
GA6	6"	3/4"
GA8	8"	15/16"
GA10	10"	1-1/8"
GA12	12"	1-5/16"
GA15	15"	1-11/16"
GA18	18"	2-1/16"

Pipe Wrenches Straight Pattern

No.	Size	Grips Pipe
NSP6	6*	1/8" to 3/4"
NSP8	8"	1/8" to 1"
NSP10	10"	1/8" to 1-1/2"
NSP14	14"	1/4" to 2"
NSP18	18"	1/4" to 2-1/2"
NSP24	24"	1/4" to 3"
NSP36	36"	1/4" to 4-1/2"
NSP48	48"	1" to 6"



These Pipe Wrenches have long been famous for their remarkable durability under hard usage. They are drop forged from specially selected steel and carefully heat treated. The unbreakable housing and free-moving nut are features that will be appreciated by all good mechanics.

TW Series 3/8" Sq. Drive Head Screw Wrenches

The TW Set contains one each of the following

Tool No.	Size Hex. Bit	Size Drive	For Set Screw	For Cap Screw
TW4	1/8"	3/8"	1/4"	#10 & #12
TW5 TW6	5/32" 3/16"	3/8"	5/16"	1/4"
TW7	7/32"	3/8"	7/16"	5/16"
TW8 TW10	5/16"	3/8"	5/8"	3/8"& 7/16
TW12	3/8"	3/8"	3/4"	1/2"
W2-1/2	Fits Allen S	Set Screw	on all abov	e wrenches



These wrenches, made with replaceable bits, cover all the popular sizes of set screws and cap screws. The TWCB set contains one each of the listed wrenches.

Packed in fibre box

Head Screw Wrenches

No.	Hex. Across Flats	No.	Hex. Across Flats	
W1	.050	W8	1/4° 5/16*	
W2 W2-1/2	1/16" 5/64"	W10 W12	3/8"	
W3 W4	3/32"	W16 W18	1/2" 9/16"	
W5	5/32"	W20	5/8"	
W6 W7	3/16" 7/32"	W24	3/4"	



These wrenches are practically indispensible in modern shops. All late model motors are using hollow head cap screws and set screws on which these wrenches must be used.

W11LR Set of 11 Head Screw Wrenches W1 to W12 inclusive in leatherette roll

BUSHING DRIVERS AND EXPANSION REAMERS

Bushing Driver Set No. BU40:



This Bushing Driver Set is designed to drive all passenger car bushings and many truck and tractor bushings.

These tools are made of alloy steel carefully hardened and tempered to give the best of service. Guaranteed against defects in workmanship and

Packed in a metal box 7-7/8" long; 4-1/8" wide;

high.

Set includes

Solution 1	Bushing I.D.	Drive O.D.	Fits Handle No.
40-1 Driver	13/32	7/16	42-1, 42-2
40-2 Driver	7/16	1/2	42-1, 42-2
40-3 Driver	1/2	9/16	42-1, 42-2
40-4 Driver	1/2	5/8	42-1, 42-2
40-5 Driver	9/16	5/8	42-1, 42-2
40-6 Driver	9/16	11/16	42-1, 42-2
40-7 Driver	(39/64	43/647	42-1, 42-2
	15/8	11/16	
40-8 Driver	5/8	3/4	42-1, 42-2
40-9 Driver	11/16	13/16	42-1, 42-2
41-1 Driver	(47/64	55/64)	42-3
	13/4	7/8 1	
41-2 Driver	13/16	15/16	42-3
41-3 Driver	(55/64	63/64)	42-3
	17/8	1 1	1000
41-4 Driver	15/16	1-1/16	42-3
41-5 Driver	1	1-1/8	42-3
41-6 Driver	1-1/16	1-3/16	42-3
41-7 Driver	1-1/8	1-1/4	42-3
41-8 Driver	1-1/4	1-3/8	42-3
42-1 Handle	7/16 Dia.	x 5" Long	
42-2 Handle	5/8 Dia.	x 6" Long	
42-3 Handle		x 7-3/8" Le	ong
43-1 Nut	fits 42-1	& 42-2	10.77
43-2 Nut	fits 42-3		

40-7 will drive Chevrolet Six Water Pump Bushing. 41-1 will drive Chevrolet Six King Bolt Bushing. 41-3 will drive Chevrolet Six King Bolt Bushing.

(Knee action car.)

Expansion Type Reamers and Pilots

Improved Design - 50% Faster

Individual Reamer Specifications

No.	Size	Length	No. of	
	Size	Reamer	Blades	Blades
8A	1/4" to 9/32"	3-1/2"	1-5/8"	4
7A	9/32" to 5/16"	3-3/4"	1-5/8"	4
6A	5/16" to 11/32"	4"	1-5/8"	4
5A	11/32" to 3/8"	4-1/4"	1-7/8"	4
4A	3/8" to 13/32"	4-1/2"	1-7/8"	4
3A	13/32" to 7/16"	4-3/4"	1-7/8"	6
2A	7/16" to 15/32"	5"	1-7/8"	6
A	15/32" to 17/32"	5-1/4"	2"	6
В	17/32" to 19/32"	5-3/4"	2"	6
C	19/32" to 21/32"	6-1/4"	2-1/4"	7
D	21/32" to 23/32"	6-3/4"	2-1/4"	7
E	23/32" to 25/32"	7-1/4"	2-1/2"	7
F	25/32" to 27/32"	7-3/4"	2-1/2"	7
G	27/32" to 15/16"	8-1/4"	3"	7
H	15/16" to 1-1/16"	8-3/4"	3"	7
î	1-1/16" to 1-3/16"	10"	3-1/2"	7
j	1-3/16" to 1-11/32"	11"	3-1/2"	7
K	1-11/32" to 1-17/32"	12"	4"	7
L	1-17/32" to 1-25/32"	13"	4"	7
M	1-25/32" to 2-7/32"	15"	5-1/4"	7
N	2-7/32" to 2-3/4"	17"	5-3/4"	7
0	2-3/4" to 3-11/32"	19"	6-1/2"	7

NOTE-When ordering pilots only, simply specify the reamer size. Shanks used for reamers 8A to 2A.

The improved design of these expansion type reamers is a very definite improvement over the old reamers is a very definite improvement over the old type. The staggered or unevenly spaced blades set at the correct angle, together with the special retaining collars, eliminates chatter and doubles the life of the reamer. They are constructed so that pilots may be quickly and easily attached, thus doubling the utility of the reamer. The pilots may be purchased sep-arately and will fit all Critchley type reamers.



Set No. LO3 (with Pilots Attached)

No. LO1 Set contains 8 reamers without pilots from 15/32" to 1-1/16" (sizes A-H) in wood box. As illustrated.

No. LO3 Set contains the same reamers as LO1 Set, but with pilots attached.

GRAY-BONNEY PULLERS, SCREW EXTRACTORS AND THREAD RESTORERS

Gear Pullers



This improved Gear Puller with special gripping feature, will handle all types of gears, pinions, etc., better than anything previously offered. The double end jaws are thin and shaped so that slipping is impossible. Light in weight, yet strong enough for the toughest job.

No. 1001 with 1/2" screw 6" long, and jaws having a spread of 6", by 3-1/2" in length, is ideal for small work.

No. 1002 is an "all purpose" tool which will handle a wide range of work. Jaws are 5-1/2" long, with a spread of 8". Screw is 9" long by 5/8" diameter.

No. 1003 is equipped with 9" jaws—spread 12". Screw is 12" long by 13/16" diameter.

"LonGriP" Screw Extractors



Ridgid 'LonGriP' Extractors are positive in operation and easy to use. Simply drill the screw to be removed with the correct size drill (as shown below), deep enough so that the extractor will grip, insert the corresponding extractor, and turn.

Set No. RE3 — Extractors Nos. 3, 4 and 5.

				1400			
							ctractors
N	os.	1,	2,	3,	4	and	5.

No.	Fits Screw	Use Drill	O.D.	Length	Depth
SE1	1/4"	1/8"	.139	2-5/16"	1° 1° 1° 1° 1° 1° 1° 1° 1° 1° 1° 1° 1° 1
SE2	5/16"	3/16"	.205	2-3/4"	
SE3	3/8"	1/4"	.272	3-1/16"	
SE4	7/16"	5/16"	.338	3-5/16"	
SE5	1/2-9/16"	11/32"	.374	3-3/4"	


Thread Restorers

Thread Restorers will save you much time and trouble when you have damaged threads to contend with. A few strokes across battered threads produce a true new thread—nut will then go on easily. Add a pair to your service kit.

No. TR1—has 8 thread sizes—11, 12, 13, 14, 16, 18, 20 and 24 threads to the inch.

No. TR2—has 8 thread sizes—9, 10, 15, 16, 20, 26, 28 and 32 threads to the inch.

No. 827 Universal Wheel Puller



The best, simplest, and sturdiest wheel puller ever developed. Has tremendous power, yet cannot bend or otherwise damage the wheel lugs.

With the three regular legs, shown above, it works perfectly on over 98% of all makes of cars.

The screw has very fine threads, which give it an extremely powerful leverage. In addition, the puller is equipped with a sliding bearing through which the driving screw rides. This feature makes it possible for the operator to attach the puller to the study, then draw the screw tightly against the axle and with a light blow of a hammer, remove the most stubborn hub. Extends to include 8 inch bolt circle.

Another feature is the floating cap on the screw end. This centers on the axle, avoiding injury to either axle or puller.

The driving end is forged with a hexagon head which firmly holds the driving handle. The handle driving bar can be eliminated if it is desired to turn the screw up with an ordinary socket or open end wrench.

No. 827L-Extra Leg for Above

No. 827H Handle



Designed especially for No. 827 Wheel Puller. Drop forged and heat treated.


No. 827V Wheel Puller Adaptor



This adaptor will work on all Ford V-8 hubs from 136 to date. Engage two of the puller arms in the bolts and slide the adaptor over the hub groove. Apply pressure by means of the pressure screw, and a straight steady pull will result.

GRAY-BONNEY VALVE TOOLS

No. CF49 Stubby Type Valve Lifter



The little stubby has many outstanding features to make it the most popular universal valve lifter on the market to-day. It will service any "L" Head motor having the cylinders in one line and straight stemmed valves. It is so small that it gets in all the tight corners with ease. It has no catches to wear and slip; no pinching of fingers, etc. Not necessary to remove manifolds when you use a Gray-Bonney stubby.

No. CF4 Valve Spring Compressor



Services all Chevrolet and many low horse-power motors including some of British origin. Also well adapted to many L head motors when manifolds are removed. Heavy bar-steel with adjustable jaws, oil tempered. Screw adjustment for plunger depth. Safety over-center lock, allows both hands free when spring is raised. Throat 4%" x 644".


No. CF2 Split Lock Replacer



The No. CF2 is just the tool for replacing all types of split keys on hard-to-get-at motors—Chrysler, Dodge, DeSoto, Plymouth, Studebaker, Oldsmobile and all late model cars. The sliding base prevents the keys from dropping into the motor. Simple to load; easy to operate; much safer than grease.

No. CFII Valve Lifter

UNIVERSAL "C" CLAMP TYPE



Height 10-1/4", Width 9-1/2", Handles 1-1/8" to 1-3/4" spring.

Equipped with CF21 Straight Jaws. CF22 Offset Jaws are included in package.

Recommended for all Valve-in-Head Automotive Motors and L-Head Motors which allow working Motors and L-Head Motors which allow working control. Designed for use with Split Lock Replacer CF2 for easy and sure handling of Locks without a fumble.

Extra Jaws and Adapter for CFII



CF21 Straight Jaws-1-1/8" to 1-3/4" capacity. Designed to work with CF2 Lock Replacer.

CF22 Offset Jaws 1-5/8" to 1-3/4" capacity. Designed to work with CF2 where Tappet Chamber opening is limited.

CF23 Large Straight Jaws—1-5/8" to 2-3/4" capacity. Designed for use with Heavy Duty Equipment. Contains large spring openings.

CF26 Special Adapter—Designed for Cadillac Cars, Minneapolis-Moline Tractors. For use with CF11. Equipped with CF21 Straight Jaws, and CF2 for replacement of the Valve Locks.

No. FT57 V-8 Universal Valve Lifter



A Ford Valve Lifter especially designed to fit all models. The double end feature is a definite improvement over the old type and eliminates he necessity of buying two tools. Drop forged from alloy steel and 27" long. Not guaranteed against breakage.

GRAY-BONNEY PISTON AND SPECIAL TOOLS

Piston Ring Compressors



These improved ring compressors are a definite improvement over anything previously offered. The self locking pawl will hold the compression band at point, and double addition a tension band is pro-vided. This band of high grade spring steel will reduce breakage to a mini-mum, and will eliminate flare out at the bottom of the com pressor. The handle

is made of 1/4" stock and can easily be replaced if lost. The beaded edge will prevent the compressor from entering the cylinder. These tools are made in four sizes, as follows:

No. RC1 for cars 21/2" to 5"-Non-locking.

No. RC2 for cars 21/8" to 5".

No. RC3 for trucks and Diesel engines with range of 31/2" to 7".

No. RC4 same as RC3 but 61/2" in height with four tension bands.



A handy and practical tool which should be in every garage. The cutter can be instantly adjusted to the desired size of 3/32", 1/8", 5/32" or 3/16", and will handle pistons from the smallest to 6" O.D. Where a groove has to be deepened for the installation of inner rings this tool is ideal.

Shop Knife




For cutting shims, gaskets, packing, top and upholstery materials, this Knife is unsurpassed. Five razor edge blades fit inside the handle, and a new one can be inserted in an instant.

No. 199 Die Cast Aluminum Handle, Complete With Blades.

Extra Blades are available for these Knives in packages of five.

Universal Cylinder Ridge Reamer

No. L0173



This ridge reamer removes the unworn ridge from the cylinders of all cars with bores from 2 %" to 4%". The supporting lugs are mounted on the blades and expand with them. This eliminates the necessity of removing studs. For cars with recessed heads the lugs are replaced by small plates and the tool rests on the top of the piston while reaming.

No. L0173 Set, as illustrated, contains one set of three blades with lugs to ream 2%" to 3%", one set of three blades with lugs to ream 3%" to 4%", one set of three plates and one operating knob, in metal box.

No. 839 Carbon Scraper



Made from spring steel wire to assure long life and flexibility. Permits scraping uneven contours on cylinder head blocks.

Clutch Alignment Set No. CA41

This is a complete set will that handle the clutches of nearly all The cars. assortment of pilots included each set results in one toolthatwill



give quick, accurate clutch alignment. Supplied in a metal box 104" x 14" x 14". Net weight approximately 5 lbs.

GRAY-BONNEY BRAKE TOOLS

Nos. 2566 and 2566A Brake Tools

~

For making brake adjustments on cars equipped with Bendix brakes. Forged from alloy steel.

No. 2566 has 1/2" blades, is 71/2" long.

No. 2566A has $\frac{1}{2}$ " blades with one straight end, is 8" long.

No. 2599 Hydraulic Brake Wrench




No. 2357D Ford Brake Wrench



For making adjustments on brakes on Ford cars and trucks. Has double square openings in 7/16" and ½" sizes. Drop-forged of alloy steel and chrome plated. Length 10%".

No. 2629 Brake Wrench For Chrysler Built Cars



This single head drop-forged alloy steel box end wrench has a double hexagon opening of 1-1/16". It is designed especially for making brake adjustments on Plymouth, Dodge, DeSoto and Chrysler cars.

No. 2612 and 2618 Brake Tools



Slotted box wrenches for use when removing or installing brake line flare nuts. Drop-forged of alloy steel and chrome plated.

No. 2612 has 3/8" and 1/2" openings required for servicing Ford, Mercury, Monarch and Lincoln.

No. 2618 has openings of 7/16" and 9/16" for use on most other hydraulic brake systems.

No. 51 Brake Set

This is a very practical set of Specialized Tools for use in servicing automotive brakes.



This kit contains the six most often required Specialized Brake Service Tools. The types provided will enable the mechanic to service brakes on practically all makes and models of cars and trucks.

Contents include one each:

Nos. 2566 Bendix brake tool.

- " 2566A " " "
- " 2357D Ford " " " 2680 Brake spring plier.
- " zooo brake spring piler.
- " K50 Brake feeler gauge.

Supplied in a strong leatherette tool roll with a pocket for each tool as illustrated above.



GRAY-BONNEY BRAKE TOOLS

No. L0925 Hydraulic Brake Cylinder Hone

Simple but sturdy construction makes it easy and inexpensive to operate and assures long, satisfactory service.

Each of the two small bodies has one set of three blade slots. The one body has shallow slots and the other has slots 1/32" deeper. One set of blades expands 1/16 of an inch in each set of slots or, moving them from one set of slots to another gives 1/8 of an inch expansion; using the three sets of blades in this manner gives 3/16 of an inch expansion in each of the small bodies, and 3/8 of an inch expansion in the medium and large bodies so that the set illustrated with the four bodies has a range of from 3/4" to 1-1/8" which covers most pleasure cars and trucks.



No. L0925—Range 3/4" to 1-7/8", contains four bodies, three sets of three blades (small, medium and large), with abrasives mounted, eighteen extra abrasives (nine coarse and nine fine). Special 1" cup screw to be used on medium size body when honing step bore cylinders and flexible driving shaft adaptable to 1/4" or 1/2" electric drill, put up in neat metal box.


Individual parts for L0925 set: L0899C—Coarse hone abrasives (1 dozen). L0899F—Fine hone abrasives (1 dozen). L0920—Flexible driving shaft.

No. 531 Brake Spring Compressor



Place tapered end of tool on steel cup, then place index finger of other hand on head of pin located on rear of back-up plate. Push in on tool until arrow head of pin is uncovered. Make one quarter turn—release pressure and the cup comes off the spring. Fits all regular and flat cups.

No. 2680 Brake Spring Plier



An unusually efficient brake spring plier designed especially for the removal and replacement of internal brake springs on all types and sizes of trucks, and many passenger cars. Size 13".

No. 525 Brake Spring Plier



An extra slim, light brake plier designed for use on all passenger cars and light trucks. Not guaranteed. Size 13".

No. 530 "C" Washer Brake Pliers



This special tool is for removing, installing and crimping hydraulic brake "C" lock washers. The most stubborn "C" lock washer can be easily removed with the tool. Size 7%".

No. B21 Lock Ring Pliers




Designed especially to spread the snap lock rings and horse shoe type of brake key in order to remove them from brakes, transmissions, pedal, clutch and fan pulley shafts when removing them from assembly. Drop forged of chrome alloy steel. Outside of jaws are toothed to prevent any possibility of slipping. Plier will spread any lock ring washer up to 1½" diameter. Size 8".

GRAY-BONNEY AUTOMOTIVE PLIERS

















No. 513 Mechanics Slip Joint Side Cutting Pliers

Forged from Chrome-Vanadium Steel, hardened and tempered, this plier is designed for hard usage. The sharp cutting side knives are ground to assure their longer life. The well designed head has a flush rivet on one side. Polished head and fully chrome plated.

Size...

No. B16 General Purpose Slip Joint Side Cutting Pliers

A well balanced medium priced Plier. It provides strong gripping power and has excellent side cutter knives. Forged from Chrome-Vanadium Steel with knurled handles, polished and fully finished in lustrous chrome. . 6" Size.

Nos. B6 and B8 Combination Pliers

These General Purpose Slip Joint Pliers are sturdily built for general service. They are drop forged, heat treated and nickel plated. Available in the two following popular sizes.

B6-Size. B8—Size.....

No. B28 Heavy Duty Slip Joint Pliers

Here is a good alloy steel long service Slip Joint Plier with notch type cutter. All mechanics should own a pair of these long heavy duty pliers.

No. 523 Thin Angle Nose Slip Joint Gripping Pliers

A powerful Gripping Plier with teeth set as in a pipe when that will not slip on a smooth round surface. This tool is for gripping frozen nuts or bolts and odd shaped objects. There are three different opening adjustments and the jaws open to take up to one inch. The angle nose gets into those "hard-to-get-at" places. Drop forged of high grade alloy steel, polished head.

Size_

No. 522 Angle Nose Battery Pliers

The handiest drop forged alloy steel plier ever designed for use when loosening or tightening the terminal nuts or battery cables. Polished head and fully finished in chrome. . 7%"

No. 258 Water Pump and Electricians' Lock Nut Pliers

This quality multi-use drop forged alloy steel Plier is for use on adjustable packing and lock nuts. It has a positive grip action with six different opening adjustments. Maximum opening two inches. Polished head and fully chrome plated.

91/2" Size.

No. B33 Body Trimmers' Pliers

This body trimmers' Hog Ring Plier is used for closing the prongs of metal lock rings used on body hardware and other installations requiring use of locking rings.

Size.

GRAY-BONNEY AUTOMOTIVE PLIERS

No. 517 Slip Joint Ignition Pliers

This delicate Ignition Plier is designed for use on all ignition units and on other equipment where small nuts and bolts are encountered. Drop forged from Chrome-Vanadium Steel, the head is correctly designed providing three opening adjustments. It is spring tempered and fully chrome plated. Not Guaranteed. Factory repairs 45c net.

No. B17 Diagonal Cutting Pliers

A high grade medium size Diagonal Cutting Plier with accurately ground cutter jaws. Drop forged from Chrome-Vanadium Steel, polished head and fully chrome plated. A sure cutter and a real cotter key puller.

Size 6"

No. B18 Heavy Duty Diagonal Cutting Pliers

This high leverage Diagonal Cutter Plier is for heavy duty service. The accurately ground cutting edges assure easy cutting. Drop forged of Chrome-Vanadium Steel, polished head and finished in chrome.

Size 7"

No. 41-4 Diagonal Cutting Pliers

Drop forged of the finest quality alloy steel, this fourinch Electrician's Diagonal Cutting Plier is a practical addition to any tool kit.

Size_____ 4

No. 39 Diagonal Cutting Pliers (Heavy Duty)

Drop forged of fine alloy steel, this plier has handhoned cutter knives that cut clean and will stand up. Designed to give great leverage in cutting as well as pulling cotter keys.

Size...... 7

No. 654 Long Nose Side Cutting Pliers

This is a long, fine, spring tempered nose, side cutting Plier, drop forged from alloy steel and carefully heat treated. The long nose of this plier will reach into tight places inaccessible with any other plier, and the keen edged cutter will cut practically any wire found in automotive work except the heavier ignition wires and battery cables. Not Guaranteed.

Size_____ 6'

Nos. B22 - B23 Lineman's Pliers


General utility standard Cutting Pliers for linemen and other electricians. Drop forged from alloy steel and carefully heat treated. Available in two sizes.

B22—Size_______6"
B23—Size______8"

No. B30 Duck Bill Pliers

This is a very practical Plier for use when working on equipment where little operating space is available. The long leverage grips provide for powerful leverage. Ideal for use when working on carburetors, ignition or similar units.

Size 8"



GRAY-BONNEY PUNCH AND CHISEL SETS

No. C46 Chisel and Punch Set



Set No. C46 contains a compact assortment of nine Chisels and four Punches to serve everyday needs. Content includes: Flat Chisels Nos. C2, C3, C4, C5, C6; Cape Chisels Nos. C12, C13; Diamond Point Chisels Nos. C15, C16; Pin Punches Nos. C28, C29, C30; Center Punch No. C34. Every piece is forged from high quality alloy steel and properly heat treated. The heads and working bits are full finished with shafts in baked blue ename!.

Set No. C46-CB-In cardboard box. Set No. C46-LR-In leatherette roll.

No. C47 Chisel and Punch Set



Set No. C47 is for the man requiring a complete set of Chisels and Punches. It contains thirteen Chisels, ten Punches, a Rivet Buster and a Pinch or Pry Bar. Content includes: Flat Chisels Nos. C2, C3. C4. C5, C6, C7; Cape Chisels Nos. C12, C13; Long Flat Chisel No. C10; Diamond Point Chisels Nos. C15, C16; Round Nose Chisels Nos. C18, C19; Long Taper Punches Nos. C25, C26; Prick Punch No. C32; Solid Punches Nos. C21, C22, C23; Pin Punches Nos. C28, C29, C30; Center Punch No. C34; Rivet Buster No. C36 and Pry or Pinch Ro. No. C38. Every piece is forged from high quality alloy steel and properly heat treated. Full finished heads and working bits with shafts in baked blue enamel.

Set No. C47-CB-In cardboard box. Set No. C47-LR-In leatherette roll.

No. C45 Flat Chisel Set



This set of Gray-Bonney Flat Chisels completely covers the range required in everyday service work. It contains the following Flat Chisels: Nos. C2, C3, C4, C5, and C6, having cutting blade widths of 1/2", 5/8", 3/4", 7/8", and 1". All are forged from the highest quality alloy steel of a specification most suitable for this type of tool. They are properly heat treated to assure hard, tough cutting ability. Their octagon baked blue enamel shafts offer a easy, secure grip. Cutting blades and striking heads are full finished.

Set No. C45-CB-In cardboard box. Set No. C45-LR-In leatherette roll.

No. PC39 Dealer's Merchandiser



Here is an ideal Punch and Chisel counter type Merchandiser. It contains the most popular tools of this type. It was created on popular demand as an aid to sales and service. The unit is constructed with a red masonite back panel mounted on a varished maple base bearing part numbers. This Merchandiser complete with tools is contained in a strong shipping carton. Conten includes: two each Pin Punches Nos. C28, C29, C30; two each Solid Punches Nos. C21, C22, C23; two Prick we day tool. C32; four Center Punches No. C32; two Prick three each Flat Chisels Nos. C2, C3; two Flat Chisels No. C41; one each Flat thisels Nos. C5, C6; two each Cape Chisels Nos. C12, C13; two Round Nose Chisels No. C18, one Round Nose Chisel No. C19.

GRAY-BONNEY PUNCHES AND CHISELS

Gray-Bonney has spared no effort to offer the best in these types of tools. All are forged of special alloy steel and are carefully heat treated. Mechanics find that the bits are hard and tough enough to work on any untempered material, but still sufficiently soft to be resharpened with a file. They have well crowned comparatively soft heads, which reduce chipping and allow them to be readily redressed when battered. Blades, tips and heads full polished, handles finished in baked blue enamel.

ORAY C DO CANADA

PIN PUNCHES

No.	Size Stock	Point Diameter	Length
C28	3/8*	1/8"	5"
C29	1/2*	3/16"	5-5/8"
C30	5/8*	1/4"	6-3/8"

LONG TAPER PUNCHES

No.	Size Stock	Point Diameter	Length
C25 C26	3/8"	5/32* 3/16*	8"

GRAY C 23 CANADA

SOLID PUNCHES

No.	Size Stock	Point Diameter	Length
C21 C22 C23	3/8" 1/2" 5/8"	1/16" 3/32" 1/8"	5-1/2" 6-1/4"

PRICK PUNCH

No.	Size Stock	Length
C32	3/8"	5"

to a District

GRAY C CAHADA

CENTRE PUNCH

No.	Size Stock	Length
C34	3/8"	5*

PRY OF PINCH BAD

No.	Size Stock	Length
C38	5/8*	16*

Lining-Up Punches (Silico-Manganese Steel)



FLAT CHISELS

No.	Stock Stock	Width of Cut	Length
C2 C3 C4 C5 C6	3/8" 1/2" 5/8" 3/4" 7/8"	1/2* 5/8* 3/4* 7/8*	5-1/2* 6* 6-1/2* 7-1/2*

LONG ELAT CHISEL

LONG PEAT GITTEE			
No.	Size Stock	Width of Cut	Length
CIO	3/4"	7/8"	14"

GRAY -C12 CANADAC

CAPE CHISELS

No.	Size Stock	Width of Cut	Length
C11	3/8"	1/8*	4-1/2°
C12	1/2"	1/4"	
C13	5/8"	3/8*	

DIAMOND POINT CHISELS

MAMOND TONY OF HISLES			
No.	Size Stock	Width of Cut	Length
C15	1/2"	1/4"	6"

CRAY CTO CANAS

ROUND NOSE CHISELS

No.	Size Stock	Width of Cut	Length
C18	1/2"	1/4°	6.
C19	5/8"	3/8°	

RIVET BUSTER

No. 8386—Lining-Up Punch, 5/8" stock, 5/16" point. Length, 15".
No. 8385—Lining-Up Punch, 3/4" stock, 5/16" point. Length, 18".

GRAY-BONNEY FEELER GAUGES

Gray-Bonney Feeler Gauges are made from the finest imported Swedish Steel, carefully Heat-Treated and Tempered to withstand wear. Each blade is tested to insure the exact thickness which is etched on it.



No. K50 Brake Adjusting Gauge

For measuring clearance between brake and shoe, 9 blades 4" long in the following thicknesses—.006; .008; .010; .012; .015; .018; .020; .022 and .032.




No. K51 General Purpose Gauge

Especially for tappet and ignition work—the most popular gauge on the market. 10 blades 1-12" long, 10 blades 3-5/8" long and 3" point file. Short blades in the following thicknesses—012; .013; .014; .018; .020; .022; .024; .025; .028; .032. Long blades in following thicknesses—002; .003; .004; .005; .006; .007; .008; .010; .013 and .015.



No. K52 Ignition Gauge

Contains 10 narrow blades 1-1/2" long for ignition distributor points and spark plugs. Thickness of blades included as follows—.012 .013; .014; .018; .020; .022; .025; .028; .032 and .035.



No. K53 Universal Master Gauge

Has full range of spacers—25 blades, each 3.5/8" long in following thicknesses—0015; .002; .003; .004; .005; .006; .007; .008; .009; .010; .011; .012; .013; .014; .015; .016; .018; .020; .022; .024; .025; .028; .030; .032



No. K54 Standard Feeler Gauge

Contains 10 blades 3-3/8" long in following sizes—.002; .003; .004; .005; .006; .007; .008; .010; .012 and .015.

GRAY-BONNEY FEELER GAUGES

Gray-Bonney Feeler Gauges are made from the finest imported Swedish Steel, carefully Heat-Treated and Tempered to withstand wear. Each blade is tested to insure the exact thickness which is etched on it.

No. K55 Extra Long Feeler Gauge

Exceptionally useful for pistons, etc. Has 8 blades, each 9" long in the following sizes—.002; .003; .004; .005; .006; .008; .010; .015.

No. K57 Chevrolet Feeler Gauge

This Gauge, especially designed for the Chevrolet cars and trucks, has eight blades, an ignition file and 3-inch steel rule. It also includes: Float Level Gauge; Gauges for valve setting; Round Wire Stock Gauge for spark plug gaps. This is a tool every Chevrolet mechanic will find very convenient.

No. K58 Ford Feeler Gauge

A ten blade Gauge for the service man that works on Ford cars and trucks. Each of the ten blades is marked with the thickness. Ends of blades have been carefully ground to provide for the accurate adjustments necessary to assure satisfactory operation of all Ford cars and trucks, including latest models.


No. K59 Spark Plug Gap Gauge

This Gauge is designed specifically for use when adjusting spark plug gap settings. The feelers are of round wire gauge stock and permit very accurate settings.

No. K56 Single End Feeler Gauge

Positive Adjustable Lock Stock Holder.

Any thickness of feeler gauge stock coils within the handle and can readily be pulled out for use. Any desired length of strip stock or standard 12" blades may be used. Positive sliding lock securely holds blades. Made from hard drawn, cold rolled steel and satin nickel plated. Length, 4-1/2". Weight, 1 oz.



Feeler Gauge Stock

Made from the same high quality Swedish Steel as used in the Gray-Bonney Gauges. Supplied in handy 12" lengths, each marked as to size and wrapped in cellophane. 12 pieces to carton. Available in following sizes:—.0015; .002; .003; .004; .005; .006; .008; .010; .012; .013; .015; .018; .020; .022; .024; .025 and .032.



GRAY-BONNEY SERVICE STATION TOOLS

No. M8 Tire Spreader

(Adjustable)



This is a desirable time-saving tool for the tire service department. It rides easily around the entire circumference of the casing on revolving rollers which are grooved to prevent slipping. Adjustable to spread tires from 5-1/2" to 7-3/4". Nickel plated. Length 17". Weight 2 lbs. 6 oz.

No. M9 Grease Bar (Universal)



Frozen shackles are easily freed up for greasing by using this one man grease bar. The bar end slips over the spring applying side pressure and is set at an angle of 25° to give easy access to any type of spring. It firmly grips all three spring leaves. The long thin end is knurled to prevent slippage. The use of this bar will eliminate bending, distorting or otherwise damaging shackles in an effort to force lubricant through the bushings. Heat treated and nickel plated. 3/4" hex. steel, 2-1/2' long, weight 4 lbs, 6 oz.

No. 840 Wire Scratch Brush



A good quality brush for removing dirt and grease and carbon.

No. 522 Angle Nose Battery Plier



The handiest plier ever designed for battery work. Chrome plated and 7-1/2" long.

No. 526 Round Nose Battery Plier



For those who prefer a Battery Plier with the round nose. Nickel plated and painted handles. 7-1/4" long.

No. 524 Battery Terminal Spreader



Spreads battery cable terminals. A great help when removing or installing battery cables. Heat treated nickel plated with painted handles. 7-3/8" long.

No. 6481 Battery Terminal Wrench



Double end box wrench with 9/16" and 5/8" double hexagon openings. Designed for servicing battery terminal nuts and bolts, 6" long.

No. 1000 Battery Terminal Puller

A sure grip miniature puller which will remove the most stubborn battery cable terminal. It is a real time saver when removing storage batteries.



GRAY-BONNEY SERVICE STATION TOOLS

Four Way Rim Wrenches



No. 308-Forged steel. 10. 308—Forged steel.
Deep sockets, 5/8",
3/4", 13/16" and 7/8"
openings. Arms 9/16"
diameter and 16-1/2"
long. Nickel plated
and forged from
Chrome Vanadium
steel. Not Guaranteed.

No. 309-Special 4-way rim wrench for trucks. See details given below.

Truck Rim Wrenches



The truck rim wrenches shown below will cover practically all wheel nuts on present day trucks.

1258 7940 7943A 7944 7944B 1258B 309	1-1/2" Hex. x 13/16" Sq. 13/16" Sq. x 1-1/8" Hex. 13/16" Sq. x 1-1/8" Hex. 13/16" Hex. Crank Type. 15" Hex. x 1-1/16" Hex. Cross Bar for 7944 only. Cross Bar for 7944 only. Cross Bar for 1944 only. Cross Bar sp. 16" Hex. x 1-3/16" Hex. x 1-3/16" Hex. x 1-3/16" Hex. x 1-3/16" Hex. x 1-1/2" Hex. Two of the arms incorporate double size openings thus providing six different socket sizes. Arms 1" Rd.; 25-1/2" long. Nickel plated.

No. 1258—Fits Ford, Dodge, Fargo and Budd wheels, No. 7940—Fits Budd wheels, No. 7943A—Fits Chevrolet.

No. 7944—Fits International, White.
No. 7944A—Fits G.M.C., Diamond T, Reo, Federal.
No. 309—A special 4-Way Universal Truck Wrench. See above for size openings.

No. M6T Spoon Type Tire Iron

Straight pattern for trucks and passenger cars. Length 23".

No. M7T Spoon Type Tire Iron

Curved pattern for trucks and passenger cars. Length 23".

No. M5 Special Lock Ring Tool (Improved Type)

For service on trucks with solid and split rings. Length 20". Not guaranteed.

No. PHI9 Tire And Rim Hammer



Drop forged from high grade steel and carefully heat treated. This tire and rim hammer is specially designed for all types of work where such a tool is needed. Weight, 3 lbs. Length overall, 16".

No. HCI Hub Cap Remover



The new Hub Cap Removing Tool proves indispensable for servicing many of the late passenger cars and light truck models. Prevents chipping of the propular accessory side walls. To operate simply place the blade under the hub cap lip and pull on the handle. Complete with rubber face pad and grip. This new tool will be a fast seller to the Dealer and Tire Trade. Overall length 15%. Approx. weight 1½ lbs.

No. 842 Drain Plug Wrench



A sturdy, well cast Wrench to service practically all cars. Nickel plated.

No. 2626 Drain Plug Wrench




Designed especially for removing and replacing the drain plug on 1939 Fords and Mercurys.

Has 2" double hexagon opening, head offset 20° , 10-3/4'' long. Made of Bonaloy Steel, Chrome plated.

GRAY-BONNEY MISCELLANEOUS TOOLS

No. L0200 Honing Set

For Piston Pins and King Bolt Bushings



No. L0200 Complete set as illustrated, consisting of 3 Hones with coarse abrasives mounted, 9 coarse refills (3 sets), one set of shims (3), and one set of burnishers (3), range 3/4" to 1.115". Each tool has 1/8" expansion, 1/16" with the blades resting solid in the grooves and 1/16" more with a set of shims under the blades.

No. L0201-Coarse abrasives (1 dozen).

No. L0201F-Fine abrasives (1 dozen).

No. L0202-Set of three burnishers.

No. L0203-Set of three shims.

No. 70 Gasket Cutter Set



This set consists of seven circular socket type cutting knives complete with 4-1/4" lock-on drive shaft, These cutters will do a host of cutting operations. They are ideal for cutting holes or intricate patterns in gaskets, linoleum or rubber mats. Cutter sizes range from 7/32" to 1/2". All pieces are hardened and plated. Supplied in small wood box.

Screw Starters

The time-saving answer to exasperating fumbling with short screws in tight places. Starts or removes all size slot type screws in difficult, inaccessible places with no interfering claws. Grips the screw inside the screw slot with a 15 pound pull. . . Releases automatically and re-sets as screw is

Regular Aluminum

	Regular	Aluminum	Nylon No	n-conductor
	No.	Length	No.	Length
Ī	125	2-1/2"	NH6	6"
	127	5"	NH9	9"
	129 215 224	9" 15" 24"	Special lengths upo	

Holding Tools

For starting screws, in-serting and removing removing small washers, pins and similar objects, this tool is invaluable. The two spring steel fingers are forced open by pressure on plunger. When



pressure is released, jaws grip object firmly. This tool is finished in attractive nickel plate, and will be a useful addition to any tool kit. For starting pan screws on Chevrolet, the No. K8 is unequalled.

No.	Reach	Length
K4 K6	3" 6"	5-3/4" 8-3/4"
K8	10"	12-3/4"

Magnetic Pick-Up Tools

		-
Tool No.	Length	
K 1	9"	
K 2	27" extended	-

The larger tool (K2) has a telescope type extension handle. These extremely useful tools have a powerful magnet in the hinged end. They are designed for extracting metal objects from tight places and work equally well on screws, washers, nuts, bolts, taper pins, valve pins, etc.

GRAY-BONNEY SCREW DRIVERS



Gray-Bonney Square Shank Screw Drivers are made with forged onepiece blades, from special alloy steel. carefully heat treated over their entire length. The handles are of the popular transparent type, which combines toughness and durability with attractive appearance. Screw drivers in the square series are primarily designed for strength and are confidently recommended for heavy work. Blades are formed with an upset shoulder, against which the handles are forced, and the method of anchoring the shank eliminates the possibility of loose handles.

No.	Length of Blade	Width of Tip	Overall Length
S04 S06	4"	5/16"	7-3/4*
S08 S012	8"	1/2"	12-3/4"

Guarantee - Screwdrivers

Screwdriver Blades are heat treated throughout; broken blades can be reground or returned to factory for regrinding. We cannot accept responsibility for acrewdrivers which have been abused.

Electricians'

Gray-Bonney Electricians' Screw Drivers are designed with the care and precision so necessary in screw drivers of this type. The blades are forged from special alloy steel, and are heat treated over their entire length. All drivers, regardless of length, are made from 3/16" stock, which makes them invaluable for reaching hard-to-get-at-screws. The handles are made of tough transparent composition, and are non-conductors of electricity.

No.	Length of Blade	Width of Tip	Overall Length
003	3"	3/16*	6-1/2*
006	6"	3/16"	9-1/2"
0010	10"	3/16"	13-1/2"

Round Shank

Gray-Bonney Round Shank Screw Drivers are somewhat lighter than the square type, and are ideal for automotive mechanics. They are made with blades ranging from 4" to 12", and all tips are taper ground, with the entire length of the blades finely polished. The handles are made of moulded composition, and in addition to being extremely durable, are designed to give the user a secure yet comfortable grip. The blade is forged from alloy steel and carefully heat treated over its entire length.

These screw drivers are ideal for electrical work as the handles are non-conductors of electricity.

No.	Length	Width	Overall
	of Blade	of Tip	Length
04	4"	1/4"	7-3/4"
06	6"	5/16"	10-1/4"
08	8"	3/8"	13"
012	12"	7/16"	17-1/2"

Care of Screwdrivers

We frequently receive acrewdrivers for grinding which have been used where a tire iron or chisel would have been more suitable. This practice does not save time and usually results in spoiling a good screwdriver.

Wood Handle

Gray-Bonney Wood Handle Screw Drivers are made with the same high grade materials as used in the more expensive drivers. Blades are forged from alloy steel, and are securely anchored in the handles, which are of selected hardwood and beautifully finished.

Tips are taper ground, and the fluted handles give a firm yet comfortable grip. These screw drivers are ideal for mechanics, carpenters and electricians, and are excellent value.

No.	Length	Width	Overall
	of Blade	of Tip	Length
W03 W04 W06 W08 W010	3" 4" 6" 8"	7/32" 1/4" 5/16" 3/8" 7/16"	7-1/4" 9" 11-3/4" 14-1/2" 16-1/2"

GRAY-BONNEY SPECIAL SCREW DRIVERS



Phillips' Screw Drivers

Wood Handle

Phillips' screws are rapidly becoming very popular, and every mechanic should have one or more screw drivers of this type. The sizes listed below will take care of all screws. Blades are forged from alloy steel, and are carefully heat treated. The handles are of hardwood, and attractively finished. Not guaranteed.

No.	Bla	de		
No.	Length	Diam.	Length	Fits Phillips Screwa
WP1 WP2 WP3 WP4	3" 4" 6" 8"	9/64" 1/4" 5/16" 3/8"	8-3/4"	No. 4 and smaller No. 5 to No. 8 inc. No. 10 to No. 16 inc. No. 18 and larger

For the mechanic who needs a full set, No. WP Set contains one of each above size. Packed in cardboard box.

Phillips' Screw Drivers

Composition Handle



Where extreme strength is required, these new Phillips' Screw Drivers will be ideal. They have the popular transparent handles, with the blades securely anchored to prevent turning. Not guaranteed.

No.	Bl	ade	0 "	1
NO.	Length	Diam.	Overall Length	Fits Phillips Screws
CP1 CP2 CP3 CP4	3" 4" 6" 8"	9/64" 1/4" 5/16" 3/8"	6" 7-3/4" 10-1/4" 11"	4 and smaller 5 to 9 Inc. 10 to 16 Inc. 18 and larger

Short Phillips' Screw Drivers

For cramped quarters — in tightening wind-shield mouldings and on similar jobs—that cannot be reached with regulation length



that cannot be reached with regulation length screw drivers, these short screw drivers will be found convenient. Of quality equal to regulation length wood handle screw drivers for Phillips' Screws. Not guaranteed.

No.	BI	ade	Fits	
No.	Length	Diameter	Phillips Screw	
SP1 SP2	1" 1-3/8"	9/64"	No. 4 and Smaller No. 5 to No. 9 Inc.	

No. 0672 Offset Screw Driver Set



The Offset Screw Drivers illustrated are well adapted for work in the "hard-to-get-at" places and are well suited for ignition, carburetor, generator and starter work. Forged from selected alloy steel, correctly hardened and tempered to withstand strain. Can be purchased singly or in complete sets of three in leatherette roll, as illustrated.

No. 0672 Set in Roll.

No.	Size Stock	Length
0669	1/4"	4"
0671	3/8"	6"
0673	1/2"	7"

ROBERTSON SCREW DRIVERS-Wood Handles

The extensive use of Robertson screws makes it necessary for all mechanics to own a set of Robertson Screw Drivers. Hand Drivers may be distinguished by different color handles. Green for the No. 1 or smallest point; Red for No. 2 or medium point; and Black for No. 3. Chart showing sizes of various Socket Screws Drives by sead driver





Stubby Type



Regular Type



GRAY-BONNEY SPECIAL SCREW DRIVERS

No. 001 Pocket Size



A very handy screw driver for the mechanic. Clip for holding driver in pocket supplied with each driver. Blade heat treated and handle non-conducting composition. Tip 1/8", length 4-3/8" overall. Not guaranteed.

No. 00A Midget

A tiny screwdriver that is ideal for use on delicate electrical and ignition apparatus. The blade is only 1-1/2" long with a 1/16" tip, with an overall length of 2-7/8". Handle is of non-conductor type. Not guaranteed.

No. E02 Neon Tube Pocket Type



Neon Tube in the handle for testing spark plugs; a tough composition handle that is a non-conductor of electricity, a magnetized tip; and a strong pocket clip. The blade is made of alloy steel and is firmly anchored in the handle. Length of blade, 2-1/4"; width of tip, 1/8". Not guaranteed.

No. E03 Neon Tube Electrical Type



A most useful tool for automotive and electrical work. Built to stand hard usage. Has Neon Tube in handle.

When testing spark plugs, a brilliant orange fash shows plug is O.K. Completely shorted plugs produce no flash. A stringy flash shows plug is partly fouled. Size, 3"; width of tip, 3/16". Not guaranteed.

Extra Neon Tubes can be supplied.

NOTE—Owing to the delicate construction of the blades in 001, 00A, E02 and E03 drivers and the Neon Tubes in E02 and E03, they are not guaranteed against breakage.





This short, sturdy screw driver is invaluable for work in confined spaces and on overhead tappet ad-justments. The blade is formed from alloy steel and carefully heat treated.

No.	Length	Width	Overall
	of Blade	of Tip	Length
S01 S02	1-3/4"	1/4"	3-3/4" 2-3/4"

Hold-E-Zee Screw Drivers



Hold-E-Zee Screw Drivers will hold screws firmly, and will save much valuable time. Handles are of tough composition, with blades carefully heat treated.

No.	Blade Size	Overall Length
R2	5/32" x 2"	4-3/4"
R3	5/32" x 3"	5-3/4"
TR4	5/32" x 4"	7-1/4"
TR6	5/32" x 6"	9-5/8"
TR8	5/32" x 8"	11-5/8"
TR10	5/32" x 10"	13-5/8"
TC2	7/32" x 1-3/4"	4-1/4"
TS4	7/32" x 4"	8-1/4"
TH6	5/16" x 6"	9-3/4"
TS7	7/32" x 7"	11-1/4"
TH8	5/16" x 8"	12-7/8"

Hold-E-Zee D17 Merchandiser

This popular attractive Display Stand is an ideal counter type merchandiser. It was created as an aid to dealer sales and contains the following fast selling Hold-E-Zee screw drivers"

Front Panel—1 each RH2, TR4, TR6, TR8, TS4, TS7 and TH6. Back Panel stock consists of ten screw drivers—two each of RH2, TR4, TR6, TS4 and TS7.

Clutch Head Screw Drivers

Made of alloy steel carefully heat treated to withstand severe usage. Handles are of transparent, non-conducting composition.





GRAY-BONNEY HAMMERS AND BODY AND FENDER TOOLS



Gray-Bonney No. 212 Series Ball Pein Hammers Gray-Bonney No. 212 Series Ball Pein Hammers are drop forged from selected steel and carefully heat treated. The handles are of straight grain hickory, securely fastened in the head, with our special iron S wedge. The No. 212 Series have head, pein and sides polished, with the balance finished in black enamel.

No.	Weight	Replacement Handle No.
212 212A 212C 212E 212E 212G 212H 212I 212J 212J	3 Lbs, 2-1/2 " 2 " 1-1/2 " 1 " 3/4 " 8 oz. 6 "	7 6 5 4 3 3 2 2 1

Multi-Head Hammer



This hammer is designed so that the changing of faces is a matter of seconds. The head is made of forged steel carefully machined, so that the heads are locked firmly in position. The hammer comes complete with five tips: Pyralin, copper, lead, rubber and composition.

No. PH5M-Complete with tips.

No. PHP-Extra Pyralin tip.

No. PHR-extra rubber tip.

No. PHB-Extra composition tip.

No. PHL-Extra lead tip.

No. PHC-Extra copper tip.

Bumping Hammer



No. PH22-This hammer has polished faces and black body. Head, 4-1/4" long. Round face, 1-1/4" in diameter. Square face, 1-1/4" square. Overall length, 12" Weight, 14 ozs. Replacement Handle

Soft Face Hammers



Gray - Bonney Soft Face Hammers are useful for fitting piston pins and similar jobs, and for body

and fender work. The tips are of a tough, ambercolored composition material that will not mar a finely finished surface. New tip may be attached by turning the old one loose with a pipe wrench and pressing on the new tip. The hammer is properly balanced and the hickory handle is securely locked in the head.

No.	Weight
*PH18	1/4 lb.
PH15	1/2 lb.
PH20	1 lb.

*Supersedes PH17.

Extra Tips are available for all hammers. To order, simply specify number of hammer,

Light Bumping Hammer



No. PH23 - A light weight finishing hammer with head having polished faces and black body. Head, 4" long.

Round face, 1-1/4" in diameter. Square face, 1-1/8" square. Overall length, 11-1/2". Weight, 9 ozs. Replacement Handle No. 3.

Dinging Hammer



No. PH24-A finishing hammer with faces crowned and polished; body of head finished in black, Head, 6" long. Large face, 1-5/8"

Small diameter. face, 1-1/4" diameter. Overall length, 12". Weight, 13 ozs. Replacement Handle No. 3.

Light Dinging Hammer



No. PH25 — A sturdily made, light weight finishing hammer. Head 6-1/2" long. Large face 1-1/4" square. Small face, 1-1/16" in diameter. Overall

length, 11-1/2". Handle No. 3. Weight, 10 ozs. Replacement

The Finest That Money Can Buy

GRAY-BONNEY BODY AND FENDER TOOLS

Special Bumping Hammer



No. PH26 — The head is drop forged with bullet shaped end which makes it easy to remove small dents. Face of the

dents. Face of the head is polished with body finished in black. Strong hickory handle. Head, 4" long. Weight, 7 ozs.

Upholsterers' Magnetic Hammer



No. PH27—Head is polished all over and one end is magnetized. Head is 5-1/2" long. Overall length 12". Weight, 7 ozs.

Fender Bumper Mallet



No. PH30— Has rubber composition head which excels hickory for durability. It will not

shatter, chip or split. Handle is of hickory. Head 2-1/2" in diameter, 4-1/2" long. Handle is 11-1/2" long. Weight 1-3/4 lbs.

Regular or Toe Dolly Block



No. F2—Drop forged of selected steel and full surface ground and polished. Length, 4-3/4". Width, 2-1/4". Thickness, 1-1/16". Weight, 2-1/2 lbs.

Heel Dolly Block



No. F3—Drop forged of steel most suitable for this type tool. Full surface ground and polished. Length, 2-1/2". Width, 3-1/8". Thickness, 1-1/2". Weight, 2-1/4 lbs.

Bar Dolly



No. F4—Drop forged steel and full surface ground and polished. Length, 4-1/4". Width, 2". Thickness, 1-1/2". Weight, 3 lbs.

Wedge Dolly Block



No. F5—Especially designed for work on turret tops. Drop forged of selected steel, with working surfaces highly polished. Length, 5". Width, 2-1/2" lbs.

General Purpose Dolly Block



No. F6—Full surface ground and polished. Weight, 3 lbs. Drop forged steel.

Budd Dolly Block



No. F7—Drop forged of selected steel. Full strates ground and polished. Its curved surfaces are designed so that it will take care of any repair on a Budd body. Each block is carefully gauged after it is polished to insure correct radii of the curves. Weight, 3 lbs.

Small Hand Hold Dolly



No. F10—Working surfaces are ground and polished. Weight, 2-1/4 lbs.

GRAY-BONNEY BODY AND FENDER TOOLS

Large Hand Hold Dolly



No. F12-Working surfaces are ground and polished. Weight, 3-1/2 lbs.

Special Door Panel Spoon



No. F13—In addition to work on door panels, this spoon will be found handy for working on the quarterdeek of turret tops and between the headlining strainer and roof panels. It is also handy for work between the fender bracket and fender metal where a dolly block can't be used.

Blade is 2-1/4" wide, 5-1/2" long. Handle is 7/8" diameter. Weight 23 ozs.

Wide Body Spoon



No. F15—Blade ground and polished. Dimensions of blade: 2-1/16" wide, 5" long. Overall length, 10-1/2". Weight, 1 lb.

Panel Spoon



No. F16—Used in general body repair work and on turret tops. Forged of selected steel with polished working surfaces. Blade 2-1/4" wide, 6-1/4" long. Overall length, 11-1/4". Weight, 22 ozo.

Flat File Holder



No. F24—This inexpensive file holder for the regular 14" flat file has long proved very popular with body workers. It is light in weight, yet has the strength of a metal holder. The comfortably shaped hand grip and perfect balance give the operator perfect control, resulting in quick satisfactory work.

Flexible Body File

No. F25.—The application of the milling cutter principle to body files has produced a file that will last longer and do better work. Each tooth is individually milled, and the U shaped groove provides maximum clearance allowing the ribbon like shavings to be cleared quickly and easily. The elimination of packing and loading is a feature of this new file, and the teeth will maintain their razor like sharpness several times as long as the old V tooth file.

File and Holder Set

Overall length, 14".

Holder Supplied Free

No. F26—For the shop using the F25 14" file, this combination will prove to be excellent value. Six general purpose 14" files and a No. F24 Holder for the ordinary cost of the files.

Adjustable File Holder



No. F31—Can be used on 12" and 14" files. This holder is strongly made, yet is light and handy. Can be adjusted for curving the file either outward or inward.

GRAY-BONNEY BODY AND FENDER SETS

FB10 Set

Approx. Weight 38 lbs. Contains 10 Pieces



A compact set of body and fender tools ustable for taking care of the mino bumps which the averagishop is called on to straighter out. Contain 10 pieces pack din an attractively finishemetal cas measuring 21' 7" * 6".

No.	Description
F2	Regular or Toe Dolly Block
F3	Heel Dolly Block
F4	Bar Dolly
F6	General Purpose Dolly Block
F10	Small Hand Hold Dolly
F25	Flexible Body File
F31	Adjustable File Holder
PH22	Bumping Hammer
PH24	Dinging Hammer
PH26	Special Bumping Hammer

FB14 Set

Approx. Weight 45 lbs. Contains 14 Pieces



Contains 14 essential pieces for body and fender repair work. Packed in a strong, attractively finished metal box with removable tray, padlock hasp and carrying handle. The box is sufficiently large to take care of tools you may have on hand or wish to add later. It measures 21" x 7" x 6".

No.	Description	
F2	Regular or Toe Dolly Block	
F3	Heel Dolly Block	
F4	Bar Dolly	
F5	Wedge Dolly Block	
F6	General Purpose Dolly Block	
F12	Large Hand Hold Dolly	
F13	Special Door Panel Spoon	
F16	Panel Spoon	
F25	Flexible Body File	
F31	Adjustable File Holder	
PH22	Bumping Hammer	
PH24	Dinging Hammer	
PH25	Light Dinging Hammer	
PH26	Special Bumping Hammer	

FB19 Set

Contains 19 Pieces

Approx. Weight 54 lbs.



A complete set of fender hammers, dollies, spoons. files, etc., for the specialist in body and fender repair work. Each tool has been carefully selected so that any job can be done with speed and thoroughness. Packed in attractive metal chest with tote tray and strong padlock hasp. Chest size, 21" x 7-1/2" x 8-1/8".

No.	Description
F2	Regular or Toe Dolly Block
F3	Heel Dolly Block
F4	Bar Dolly
F5	Wedge Dolly Block
F6	General Purpose Dolly Block
F7	Budd Dolly Block
F10	Small Hand Hold Dolly
F12	Large Hand Hold Dolly
F13	Special Door Panel Spoon
F15	Wide Body Spoon
F16	Panel Spoon
F25	Flexible Body File
F31	Adjustable File Holder
PH22	Bumping Hammer
PH23	Light Bumping Hammer
PH24	Dinging Hammer
PH25	Light Dinging Hammer
PH26	Special Bumping Hammer
PH27	Upholsterers' Magnetic Hamme

GRAY-BONNEY BRITISH SIZE OPENINGS

Gray-Bonney Engineers' Wrenches, Socket Sets and Box Wrenches are available with B.S.F. and Whitworth size openings. The increasing use of cars, trucks, motorcycles and other mechanical devices of British origin make tools of this type a necessity. All are processed from the finest alloy steels, designed and finished to assure maximum user satisfaction.

WB 49 Combination Set

"BRITISH SIZES"



49 Pieces

- 20 Double Hexagon Sockets
- 15 Handles and attachments
- 8 Box Wrenches
- 6 Engineers' Wrenches

This WB49 Set has been created to meet the requirements of mechanics responsible for the maintenance of cars, trucks and other mechanical equipment built to British specifications. It is a general purpose set, contained in a metal chest measuring 21" x 7" x 6".

Contains the following 49 Pieces:

No.	W	Whitworth Bolt Size	
MW1	4BA	Double	Hex. Socket
IW2	3BA		
IW3	2BA	"	**
IW4	1/8"	"	**
MW5	1BA	"	"
IW6	OBA	**	"
IW7	3/16"	**	"
AW8	1/4"	**	"
MW9	5/16"	**	44
4W10	3/8"	"	**
3 36 5 4 31 9 30 32	Slidin 11" E 6" 3" Speed 10" F Cross	rsal Joir g T Han xtension " Handle lex Hand Bar sible Rat	idle

1/2" Square Drive

No.	Whitworth Bolt Size			
W155 W156	3/16"	Double "	Hex.	Opening
W157	5/16"	44		66
W158	3/8"	**		**

1 /9"	Samara	Drivo	Cant	hanni

No.	Whitworth Bolt Si	ze
W159 W160	7/16" Double Hex. Op	ening
W161	9/16" "	**
W162	5/8" "	- 44
W163	11/16" "	**
W164	3/4" "	**
718 719A 653 655 686 4897	5" Extension 10" Swivel Grip Extens 15" Flex Handle Cross Bar 19" Speeder Reversible Ratchet	sion

Also included

Engineers' Wrenches.—Set of six wrenches as contained in WB6 on page 51.

Long Box Wrenches—Double Offset.—Set of five wrenches as contained in WB95 Set on page 51.

Short Box Wrenches—Double Offset.—Set of three wrenches, W176, W177, W178, as shown on page 51.


No. WB49 Set containing 49 pieces comes complete in steel chest as illustrated. Chest measures 21" x 7" x 6".

GRAY-BONNEY BRITISH SIZE OPENINGS SOCKET WRENCHES

Gray-Bonney Sockets, Handles and Attachments used in British size sets are of the same high quality so characteristic of the entire Gray-Bonney line. The sockets are of the thin wall type and are forged from the finest alloy steel. All pieces are finished in lustrous chrome.

WB12 British Size Socket Set

1/2" Sq. Drive



This Spinner Set includes all sockets as contained in Set No. WB16 illustrated below. It also contains a 15" flexible handle No. 653 and Cross Bar No. 655.

WB16 British Size Socket Set



The sockets and handles in this set are all 1/2" square drive. The sockets are of the straight thin wall type, and range in size from 29/64" to 1-19/64" nominal openings. All parts are forged from high grade alloy steel and are attractively nickel plated.

This set in steel box (as illustrated) contains all the sockets and attachments listed below.

No.	Whitworth Bolt Size
W155	3/16" Double Hex. Socket
W156 W157	1/4" " " "
W157 W158	5/16" " " "
W159	7/16" " "
W160	1/2" " "
W161	9/16" " "
W162	5/8" " "
W163	11/16" " "
W164	3/4" " "
653 655 686 718 719A 4897	15" Spinner Handle Cross Bar 19" Speeder 5" Extension 10" Swivel Grip Extension Reversible Ratchet

WB312 British Size Socket Set



This handy little set contains all the sockets in the WB19 set illustrated below, together with the T30 flex handle and T32 cross bar. In steel box as illustrated.

WB19 British Size Socket Set



The sockets are extra thin with straight walls, and all handles are extranely light and easy to handle. The reversible ratchet with this set is of the highest quality, and can be used with 1/4" drive sockets by the use of a 1/4" drive connector. In steel box as illustrated.

The following sockets and handles are included:

No.	Whitworth Bolt Size		
MW 1	4 BA Double I	Iex. Socket	
MW 2	3 BA "	"	
MW 3	2 BA "	**	
MW 4	1/8" "	**	
MW 5	1 BA "	"	
MW 6	0 BA. "	"	
MW 7	3/16" "	"	
MW 8	1/4" "	"	
MW 9	5/16" "	"	
MW10	3/8" "	"	
T3 T36 T5 T4 T31 T9 T30 T32 T35	Universal Join' Sliding T Hand 11" Extension 6" " Speed Handle 10" Flex Hand Cross Bar Reversible Rat.	lle le	

GRAY-BONNEY BRITISH SIZE SOCKET WRENCHES

Gray-Bonney Sockets and Wrenches for British sizes are manufactured with extreme care and precision. A complete set should be available in every shop to service the many types of British cars, trucks, aircraft and other popular equipment.

HDW14 British Size Socket Set 3/4" Sq. Drive

Packed in Strong Metal Carrying Case

A Heavy Duty Set designed to service Heavy Equipment

CONTENTS

No.	w		S.W." n Bolt Six	ze	No.	w	V/10	S.W." n Bolt Si:	ze	No.	Attachments Description
WH160 WH161	1/2" 9/16"	Double "	Hexagon "	Socket	WH166 WH167	7/8" 15/16"	Double "	Hexagon	Socket	86	Sliding T Handle
WH162	5/8"	**	"	"	WH168	1"	44	**	"	88 87	15-1/2" Extension
WH163	11/16"	"	"	"		1				98	19" Ratchet
WH164 WH165	3/4"	"	"	"						89	Ratchet Connecto

Sockets with British Size Openings

1/4" Sq. Drive

W153 Fits 1/4" BSF, 3/16" BSW

W154 Fits 2BA

3/8" Sq. Drive

Double Hexagon Type

1/2" Sq. Drive

Extra Deep Double Hexagon Type No Nom Open BSW BSF.

No.	Nom. Open.	Whitworth	B.S.F.
MW 1	1/4"	4BA	
MW 2 MW 3	9/32"	3BA 2BA	
MW 4	11/32"	1/8"	1
MW 5	23/64"	1BA	The first of
MW 6	13/32"	0BA	
MW 7 MW 8	29/64"	3/16"	1/4"
MW -9	39/64"	5/16"	3/8"
MW10	23/32"	3/8"	7/16"

2101	Promit a bank		
WL154 WL155 WL156 WL157 WL158 WL159 WL160 WL161 WL162	11/32" 29/64" 17/32" 39/64" 23/32" 23/64" 59/64" 1-1/64"	1/8" 3/16" 1/4" 5/16" 3/8" 7/16" 1/2" 9/16" 5/8"	1/4" 9/32" & 5/16" 3/8" 7/16" 1/2" 9/16" 5/8" 11/16"

Above sockets 3-1/4" overall length.

1/2" Sq. Drive Double Hexagon Type

- No.	Nom. Open.	B.S.W.	B.S.F.
W152 W155 W156 W157 W158 W159 W160 W161 W162 W163 W164	13/32" 29/64" 17/32" 39/64" 23/32" 53/64" 1-1/64" 1-17/64" 1-13/64"	O.B.A. 3/16" 1/4" 5/16" 3/8" 7/16" 1/2" 9/16" 5/8" 11/16"	1/4" 5/16" 3/8" 7/16" 1/2" 9/16" 5/8" 11/16" 3/4" 7/8"

3/4" Sq. Drive Double Hexagon Type

No.	Nom. Open.	B.S.W.	B.S.F.
WH160 WH161 WH162 WH163 WH164 WH165 WH166 WH167 WH168	59/64" 1-1/64" 1-7/64" 1-13/64" 1-19/64" 1-25/64" 1-31/64" 1-37/64" 1-43/64"	1/2" 9/16" 5/8" 11/16" 3/4" 13/16" 7/8" 15/16"	9/16" 5/8" 11/16" 3/4" 7/8" 15/16" 1"

GRAY-BONNEY BRITISH SIZE OPENINGS

British Size Open End Wrenches



Gray-Bonney Engineers Wrenches with British openings are correctly designed and combine lightness with strength and durability. They are drop forged from Chrome-Vanadium alloy steel, carefully heat treated and attractively plated, with buffed heads.

No. Nominal Open.		B.S.W.	B.S.F.	Length
W775	11/32 & 29/64	1/8 & 3/16	1/4	5
W781	21/64 & 29/64	2BA & 3/16	1/4	5
W774	29/64 & 17/32	3/16 & 1/4	1/4 & 5/16	6-1/4
W782	17/32 & 39/64	1/4 & 5/16	5/16 & 3/8	7
W776	39/64 & 23/32	5/16 & 3/8	3/8 & 7/16	8
W783	23/32 & 53/64	3/8 & 7/16	7/16 & 1/2	8
W784	53/64 & 59/64	7/16 & 1/2	1/2 & 9/16	9
W793	59/64 & 1-1/64	1/2 & 9/16	9/16 & 5/8	10-3/4
W794	1-7/64 & 1-19/64	5/8 & 3/4	11/16 & 7/8	12
W795	1-1/64 & 1-7/64	9/16 & 5/8	5/8 & 11/16	10-3/4
W796	1-19/64 & 1-31/64		7/8 & 1	13-1/2
W797	1-31/64 & 1-43/64	7/8 & 1	1 & 1-1/8	15-1/2

British WB6LR Engineers' Wrench Set

This set includes wrenches to service most popular British sizes. Content includes W781, W782, W783, W784, W774 and W776. The size of mild openings may be determined by referring to chart above. Supplied in leatherette roll.

British Size Tappet Wrenches

No.	B.S.W.	B.S.F.
W122 W122A W124	1/8" x 3/16" 3/16" x 1/4" 5/16" x 3/8"	1/4" x 5/16" 3/8" x 7/16"

British No. W4T Tappet Set

This set includes two No. W122 and two No. W124 complete in leatherette roll.

British Size Ignition Wrenches

The WE Series Miniature Ignition Wrenches listed below are similar to the E series on page 24. They are drop forged from alloy steel, heat treated and chrome plated with polished heads.

No.	Nominal Opening	Whitworth
WE01	13/32" & 23/64"	0BA & 1BA
WE10	23/64" & 13/32"	1BA & 0BA
WE23	21/64" & 9/32"	2BA & 3BA
WE32	9/32" & 21/64"	3BA & 2BA
WE45	1/4" & 7/32"	4BA & 5BA
WE54	7/32" & 1/4"	5BA & 4BA
WE67	3/16" & 11/64"	6BA & 7BA
WE76	11/64" & 3/16"	7BA & 6BA

British No. WE8 Ignition Set

The WES set contains one each of all WE series ignition wrenches listed above. Supplied in a leatherette roll.

British Size Box Wrenches

Long Type

This new series of Gray-Bonney Box Wrenches with British size openings should be in every tool kit. The usefulness of this type of wrench has long been appreciated by mechanics, and their ability to reach hard-to-get-at places is unequalled. The offset heads (with different opening at each end) and the leanly broached 12 point openings make them ideal for practically every job. These wrenches are drop forged from Chrome-Vanadium alloy steel, and are light in weight, they will stand up under the most exacting conditions. They are attractively plated with polished heads and panels.

No.	Nom. Opening	Whitworth	B.S.F.
W70	21/64 x 13/32	2BA x 0BA	7/32
W71	11/32 x 29/64	1/8 x 3/16	1/4
W72	17/32 x 39/64	1/4 x 5/16	5/16 x 3/8
W73	39/64 x 23/32	5/16 x 3/8	3/8 x 7/16
W77	53/64 x 59/64	7/16 x 1/2	1/2 x 9/16
W79	1-1/64 x 1-7/64	9/16 x 5/8	5/8 x 11/16
W87	1-7/64 x 1-19/64	5/8 x 3/4	11/16 x 7/8
W89	1-31/64 x 1-43/64	7/8 x 1	1 x 1-1/8

British Box Wrench Sets-Long Type

The WB96 Set contains six wrenches W70 to W79, with a range of British sizes from 2BA to 5/8" Whitworth, and 7/32" to 11/16" B.S.F. The set comes complete in heavy fibre box.

WB95 Set contains five wrenches W71 to W79 inclusive, with openings from 1/8" to 5/8: Whitworth and 1/4: to 11/16: B.S.F. Packed in fibre box.

British Short Type Box Wrenches

Both Ends Offset

Different Opening in Each End



These handy short type box wrenches are ideal for getting into confined spaces. The heads are correctly offset with 12 point openings and plated.

No.	Nom. Opening	Whitworth	B.S.F.
W176 W176A W177 W178 W179	11/32 & 29/64 21/64 & 29/64 17/32 & 39/64 39/64 & 23/32 23/32 & 53/64	2BA & 3/16 1/4 & 5/16 5/16 & 3/8	5/16 & 3/8 3/8 & 7/16

British W190 Box Wrench Set

The W190 Set is made up of one each of Nos. W176, W177, W178 and W179. Packed in cardboard box.

GRAY-BONNEY REFRIGERATION SOCKET WRENCH SET



RF85 Set - 73 Pieces Weight 25 Lbs.

The RF85 Set is designed particularly for refrigeration mechanics and service men. It is a complete set and consists of special refrigeration tools, an assortment of sockets and attachments, combination wrenches and other necessary service tools.

PLIERS

Description

No.

	654	Long Nose Side Cutting, 6"
	B8	Heavy Duty Slip Joint, 8"
	258	Pump Plier, 11"
		SCREW DRIVERS
	001	Pocket Size, Composition Handle, 2" blade
	003	Electricians', Composition Handle, 3" blade
_	04	Round Shank, Composition Handle, 4" blade
	06	Round Shank, Composition Handle, 6" blade
U-	CP2	For Phillips Screws Nos. 5 to 9 inclusive
	CP3	For Phillips Screws Nos. 10 to 16 inclusive
		MISCELLANEOUS
	RF46	Flaring Tool for 1/4", 5/16", 3/8", 1/2", 5/8" tubing
gs	RF54	Flare Nut Wrench, 3/4" & 1" openings
gs gs	RF55	Flare Nut Wrench, 7/8" & 1-1/8" openings
	RF59	Tube Cutter for tubing from 1/8" to 1" O.D.
	К6	Handy Holding Tool, 6" reach
	212-1	Ball Pein Hammer, 1/2 lb. Head
	199	Shop Knife
	II	

	Packed in metal tool box,	003	Electricians', Composition Handle, 3" blade		
No.	Description	No.	Description	04	Round Shank, Composition Handle, 4" blade
W11LR RF80 T4 T5 T14 T16 T18 T20 T22 T35	In leatherette roll. Page 25 In small metal box. Page 53 3/8" SQ. DRIVE SOCKETS AND ATTACHMENTS Extension, 6" long Extension, 1" long 7/16" Double Hex. Socket 1/2" Double Hex. Socket 9/16" Double Hex. Socket 5/8" Double Hex. Socket 11/16" Double Hex. Socket 11/16" Double Hex. Socket 11/16" Double Hex. Socket Sliding "T" Handle.	3112 3114 3116 3118 3120	Description COMBINATION (TU-TYPE) WRENCHES 3/8" Openings 1/2" Openings 1/2" Openings 6/8" Openings RIGHT ANGLE WRENCHES 3/8" & 7/16" Openings 5/8" & 3/4" Openings	CP2 CP3 RF46 RF54 RF55	Round Shank, Composition Handle, 6° blade For Phillips Screws Nos. 5 to 9 inclusive For Phillips Screws Nos. 10 to 16 inclusive MISCELLANEOUS Flaring Tool for 1/4", 5/16", 3/8", 1/2", 5/8" tubing Flare Nut Wrench, 3/4" & 1" openings Flare Nut Wrench, 7/8" & 1-1/8" openings
2384	DOUBLE OFFSET BOX WRENCHES	RF60	TUBE BENDERS For 1/4" tubing	RF59	Tube Cutter for tubing from 1/8" to 1" O.D.
2386	3/8" & 7/16" Short Type, Dble. Hex. Opening 1/2" & 9/16" Short Type,	RF61 RF62	For 5/16" tubing For 3/8" tubing	K6	Handy Holding Tool, 6" reach
2388	Dble. Hex. Opening 5/8" & 3/4" Short Type, Dble. Hex. Opening	RF63 RF64 RF65	For 7/16" tubing For 1/2" tubing For 5/8" tubing	199	Ball Pein Hammer, 1/2 lb. Head Shop Knife

GRAY-BONNEY REFRIGERATION SOCKET SETS

In this RF81 Set will be found practically all of the Sockets and Attachments, including the popular RF22 Ratchet, that the refrigeration service man will need on all ordinary jobs. In addition three thin wall, double hexagon special Refrigeration Box Wrenches are included. All are packed in a steel box which measures 15-7/8" L x 3-3/8" W x 1-3/4" D.


RF81 Set Content

No.	Description
V8 V9 V10 V11 V12 V14 V17 V18	1/4" Hexagon Socket (1/4" Square Drive) 9/32" Hexagon Socket (1/4" Square Drive) 5/16" Double Hexagon Socket (1/4" Square Dr.) 11/32" Double Hexagon Socket (1/4" Square Dr.) 3/8" Double Hexagon Socket (1/4" Square Drive) 7/16" Double Hexagon Socket (1/4" Square Drive) 7/16" Double Hexagon Socket (1/4" Square Dr.) Sliding "T" Handle, 4-1/2" long (1/4" Square Dr.) Extension 6" long (1/4" Square Drive)
T4	
T16	1/2" Double Hexagon Socket (3/8" Square Drive)
T18	9/16" Double Hexagon Socket (3/8" Square Dr.)
T20	5/8" Double Hexagon Socket (3/8" Square Drive)
T36	Sliding 'T' Handle 8" long (3/8" Square Drive)
RF2	Valve Stem Socket (1/4" Male Drive) Valve Stem Socket (1/4" Male Drive)
RF3	Valve Stem Socket (1/4" Male Drive)
RF4	Valve Stem Socket (1/4" Male Drive)
RF6	alp 1: Cland Nut Socket (1/4" Male Drive)
RF7	
RF7	a loadsing Cland Mut Socket (1/4" Male Drive)
RF6	7 Kerotest Valve Packing Nut Socket (1/4 Maie Di
RF4	9 1 /4" x 1 /4" Adaptor
D 174	1 1/4" x 2/8" Adentor
RF2	2 Refrigeration Ratchet (1/4" Sq. Ratchet Opening
2384	19/8" & 7/16" Double Hexagon Box Wrench
238€	1/2" & 9/16" Double Hexagon Box Wrench
2388	5/8" & 3/4" Double Hexagon Box Wrench

RF81 Set

Contains 28 Pieces

Weight 4 lbs. 9 ozs.



A new, up-to-the-minute, pocket size kit of Refrigerator Sockets and Ratchet for use on practically any repairs requiring tools of this type. All pieces are made of selected steels and heavily plated. One each of the following 20 pieces are packed in a sturdy metal box which measures 7½" x 3¾" x 1¾".

Content of RF80 Set

Tar.	
V8	1/4" Hexagon Socket (1/4" Square Drive) 9/32" Hexagon Socket (1/4" Square Drive)
V9	5/16" Double Hexagon Socket (1/4" Sq. Dr.)
V10	11/32" Double Hexagon Socket (1/4" Sq. Dr.)
V11	11/32" Double Hexagon Socket (14 Sq. Dr.)
V12	3/8" Double Hexagon Socket (1/4" Sq. Dr.)
V14	7/16" Double Hexagon Socket (1/4" Sq. Dr.)
V17	Sliding 'T' Handle, 41/2" long, (1/4" Sq. Dr.)
V18	Extension, 6" long (1/4" Square Drive)
RF2	Valve Stem Socket (1/4" Male Drive)
RF3	Valve Stem Socket (1/4" Male Drive)
RF4	Valve Stem Socket (1/4" Male Drive)
RF5	Valve Stem Socket (1/4" Male Drive)
RF6	Packing Gland Nut Socket (1/4 Male Drive)
RF16	Dealing Cland Nut Socket (1/4" Male Drive)
RF71	Packing Gland Nut Socket (1/4" Male Drive)
RF72	Deaking Cland Nut Socket (1/4" Male Drive)
RF73	Packing Gland Nut Socket (1/4" Male Drive)
RF67	Kerotest Valve Packing Socket (1/4" Male Dr.
RF49	1/4" x 1/4" Adaptor
RF22	Ratchet Handle (1/4" Sq. Ratchet Opening)

RF80 Set Contains 20 Pieces

Weight 2 lbs. 2 ozs.



GRAY-BONNEY REFRIGERATION TOOLS



Open End-Box Type

These open end, box type wrenches have been designed especially for making flare nut adjustments. They are drop-forged of Bonaloy Steel, chromium plated with polished heads. They are long, thin and with panelled handles, permitting a firm, comfortable grip. Heads have double hexagon openings.

No.	Openings	S.A.E. Flare Size	Length
	3/4" & 7/8" 3/4" & 1"	3/16", 1/4", 5/16" & 3/8" 3/16", 1/4", 5/16", 7/16"	8"
	7/8" & 1" 7/8" & 1-1/8"	& 1/2" 3/8", 7/16", 1/2"	8" 9-1/2" 9-1/2"



Open End-Box Type

Drop-forged of Bonaloy Steel these two wrenches are especially for copper tube fittings with 3/8", 7/16", 1/2" and 9/16" hexagon. The wrenches are fully chrome plated with polished heads, have panelled handles and

double hexagon openings.

No. 2618 is designed specially for the removal of the copper tubing flare nut on the back of the expansion valve on all Kelvinator models previous to the hermetically sealed units. Heads are at 15° angles.

No.	Openings	Length	
2612	3/8" & 1/2"	4-3/4"	
2€18	7/16" & 9/16"	5"	

Spinner Wrenches



Designed especially for reaching small nuts that can Designed especially for reacting small notes. Made handled only with exceptionally small sockets. Made like a screw driver with a hexagon socket on the end that grips the nut firmly. Shanks and sockets have plated finish. The composition handles are fluted for a firm grip.

No.	Hexagon Opening	Overall Length	Drill Depth
CH06	3/16"	6"	2-1/4"
CH08	1/4"	6"	2-1/4"
CH10	5/16"	6"	2-1/4"
CH11	11/32"	6"	2-1/4"
CH12	3/8"	6"	5"
CH14	7/16"	7-1/8"	5"
CH16	1/2"	7-1/8"	5"

Reversible Ratchet No. RF45



This ratchet is primarily designed for refrigeration work. It has an easy action, is light in weight, has trim lines, is strong and can be instantly reversed by a touch of the thumb. The ratchet opening is $1/4^{\circ}$ square, the openings in the handle are $3/16^{\circ}$ and $1/4^{\circ}$ square and $1/2^{\circ}$ hexgon socket. The tool is drop forged and plated. Overall length 6° .

Non-Reversible Ratchet



This type of ratchet, made with four different size ratchet openings, is forged of Bonaloy Steel with plated finish. The ratchet is fully enclosed to keep out all

They are specially adapted to work on small refrigerant cylinders, shut-off and reducing valves, compressors, motors, etc.

No.	Ratchet Opening Square	Handle Openings Square	Handle Opening Hexagon	Length
RF21 RF22	3/16"	3/16" & 1/4"	1/2"	6"
RF23	1/4" 5/16"	3/16" & 1/4" 3/16" & 5/16"	1/2"	6" 6"
RF25	3/8"	3/16" & 1/4"	1/2"	6"

Socket Wrench for Fedders Needle Seat Assembly



This "T" handle socket wrench is drop-forged of selected This "I" handle socket wrench is grop-lorged of selected steel, carefully heat-treated and has plated finish. It is designed especially for inserting and removing Fedders cartridge type needle seat assembly. Has single hexagon opening.

No.	Opening	Diameter of Head	Length
RF 57	7/16"	19/32"	4-7/8"

GRAY-BONNEY REFRIGERATION TOOLS

"S" Type Flare Nut Wrenches



These wrenches are for those who prefer the open end to the box type wrench in making flare nut adjustments. They are drop-forged of selected steel, carefully heat-treated and have plated finish.

No.	Openings	S.A.E. Flare Size	Length
72A	3/4" & 1"	3/16", 1/4", 5/16" & 7/16", 1/2"	5-1/2"
73A	7/8" & 1-1/8"	3/8" & 5/8"	6-1/8"

Switch Adjusting Wrench



Forged of Bonaloy Steel with plated finish, this wrench is designed especially for switch adjustments on the "W" line of Frigidaire cabinet up to and including 1933. This wrench is exceptionally thin for working in close quarters and has panelled handle. Openings are at 15° angle.

No.	Openings	Length	Thickness of Head
H18S	7/16" & 9/16"	4"	1/8"

Open End Wrench for Superior Packless Valve



A single head service wrench forged of Bonaloy Steel, chrome-plated and with polished head designed especially to fit the hexagon on the auxiliary body of the Superior Diaphragm Packless Valve.

No.	Opening	Length	Thickness of Head
1964	2"	12-1/4"	5/16"

Right Angle Wrenches



Openings in the most necessary sizes for refrigeration service work. Drop-forged of Bonaloy Steel, fully chrome-plated and with polished heads.

No.	Size Openings	Length	Thickness of Heads
2723 2725B	3/8" & 7/16" 1/2" & 9/16"	4-1/4" 5-1/2"	7/32" 15/64"
2729RA	5/8" & 3/4"	7-1/2"	5/16"

Packing Gland Nut Sockets

"T" Handle Type

Not guaranteed					
No.	Prong Depth	Prong Width	Inside Diameter	Outside Diameter	Overall Length
RF17 RF18	14"	364"	21/64"	15/2" 3/16"	2"

1/4" Male Drive

Designed for use with No. RF22 and No. RF45 ratchets or any ratchet handle having 1/4" opening. Not guaranteed.

No.	Prong	Prong	Inside	Outside	Overall
	Depth	Width	Diameter	Diameter	Length
RF6 RF16 RF71 RF72 RF73	16" 16" 16"	1/8" 1/8" 3/2" 1/8"	3/8" 1/64" 5/6" 21/64"	5/8" 15/2" 7/6" 15/2"	138" 134" 158" 1116"



Valve Stem Sockets "T" Handle Type

No.	Size	Outside	Diameter	Tomato
No.	Square Opening	Nose	Shank	Length
RF10 RF11 RF12 RF13 RF14	3/16" 1/52" 1/4" 5/16"	27.64 " 27.64 " 1.2 " 9.6 " 5.8 "	1/2" 1/2" 1/2" 1/2" 1/2" 1/6"	178" 178" 178" 178" 178"



1/4" Male Drive

For use with any ratchet handle having 1/4" opening and Gray-Bonney ratchets Nos. RF22, and RF45.

No.	Size	Outside	Diameter	Length
140.	Square Opening	Nose	Shank	Length
RF2 RF5 RF3 RF4	3/6" 7/62" 1/4" 5/6"	27,64 " 1,2 " 1,2 " 2,6 "	1/2"	13/8" 13/8" 13/8" 13/8"



Kerotest Valve Packing Nut Socket

These sockets have been specially designed for repairs and adjustments on Kerotest valves.

No.	Obround	Opening	Outside	Length
No.	Length	Width	Diameter	Length
RF67	1/2"	3/8"	5/8"	196"



Ratchet Plug Adaptors

For use with Nos. RF22 and RF45 ratchets. made of Bonaloy Steel, heat-treated and plated.

No.	Plug End	Drive End
RF49	1/4"	1/4"
RF40	1/4"	9/32"
RF41	1/4"	3/8"





GRAY-BONNEY MISCELLANEOUS TOOLS

No. RF46 Flaring Tool




A simple, fast, efficient tool for quickly and accurately flaring copper and other tubing having 3/16", 1/4", 5/16", 3/8", 1/2" and 5/8" O.D. Oversize wing nuts securely lock tubing in holes threaded to prevent slipping. Open side flaring yoke attaches instantly to flaring bars. The flaring head is of the self-centering type, assuring easy, perfect flaring. A fine tool, reasonably priced for working in close quarters on gas lines, etc. Net weight 2-1/4 lbs.

No. RF59 Tube Cutter



A compact, efficient tube cutter for all tubing from 1/8" to 1" O.D. Body is an alloy die casting. Wafer-tapered, hardened cutting blade makes cutting easy and with practically no burr. The slide-lock safety reamer opens instantly and protects the hands when not in use. It may be safely carried in your pocket. Net weight 1/2 lb.

No. RF47 Pinch-Off Tool



The primary use of this tool is in refrigeration service work and is used to pinch off refrigeration tubing as well as restoring the tubing to correct shape and diameter after the service work has been completed.

The outstanding feature of this handy tool is the quick-operating freeing and locking action. This tool is made for use with 1/4, 5/16, 3/8 and 1/2 inch tubing.

Tube Benders




Ideal for bending copper and other tubing by hand to any desired shape without collapsing the tube. Made of special, oil-hardened spring steel, cadmium plated. The belled end assures ease in removing the tubing after the bend has been made.

No.	For Size Tubing
RF60	1/4"
RF61	5/16"
RF62	3/8"
RF63	7/16"
RF64	1/2"
RF65	5/8"

No. RF66 Tube Bender Set

Every service man should have a complete set of tube benders in his kit. The set consists of one each of the above sizes.

Snap-Lock Plier-Wrench



Locks onto work—Holds on after you let go. Grips better because of patented swivel jaw that adapts itself to shape of piece to be held. Affords firm grip on short ends. Removes stubborn stubs and then re-sets them. Ideal for clamping pattern to work when scribing. Provides secure grip for small objects in drill press. Heavy gauge pressed steel with extra strength where stress requires. Replaceable jaw of hardened tool steel. Bright nick.: handles with non-slip scoring.

No. 1607 7" size Wt. 14 lbs. per doz. No. 1610 10" size Wt. 9 lbs. per doz.

GRAY-BONNEY MISCELLANEOUS TOOLS

Snips Straight Pattern



These snips are of excellent quality. They are made from a one-piece drop forging, precision ground and hand polished. The cutting edges are keen and will give long and satisfactory service.

No.	Length	Cut
507	7"	2"
510 512	10" 12"	2-3/4" 3-1/4"

Snips
Combination Circle Pattern



The combination circle pattern snip is an allpurpose snip. It will cut either right or left-hand direction. This extra slim snip is ideal for garage mechanics, as well as metal workers.

707	7"	1-7/8"
710	10"	2-3/4"
712	12"	3-1/8"

No. 535 Hand Seamers



An excellent tool for hand seaming. Overall length 8", working surfaces 1" x 3-1/2". Fully heat treated. Weight 1 lb.

No. 2628 Adjustable Hack Saw Frame



A sturdily built hack saw frame with comfortable hard rubber pistol grip handle. Adjustable from 8" to 12". Full nickel finish.

High Speed Steel Hack Saw Blades

These HIGH SPEED blades are made from the finest steel obtainable, and will give the utmost in service under the most exacting conditions. Due to careful heat-treating they are extremely flexible, thus ensuring long life and protection against breakage.

No.	Width	Length	Gauge	Teeth per inch
HS1018	9/16"	10"	.025	18
HS1024	9/16"	10"	.025	24
HS1032	9/16"	10"	.025	32
HS1218	9/16"	12"	.025	18
HS1224	9/16"	12"	.025	24
HS1232	9/16"	12"	.025	32

Tungsten Alloy Steel Hack Saw Blades

An excellent alloy steel blade that will give good service under all conditions.

No.	Width	Length	Gauge	Teeth per inch
TA1018	1/2"	10"	.025	18
TA1024	1/2"	10"	.025	24
TA1032	1/2"	10"	.025	32
TA1218	1/2"	12"	.025	18
TA1224	1/2"	12"	.025	24
TA1232	1/2"	12"	.025	32

GRAY-BONNEY TOOL BOXES



The No. SB tool box is built to give you a big tool box at low cost. Heavy gauge steel with spot welded construction and with the convenience of a separate toot tray. This is real box value and large enough to hold the average mechanic's hand tool kit. Furnished with large carrying handle, padlock hasp, and finished in blue baked enamel. Measures inside: 21" x 7-1/2" x 8-1/8".



This job box is for the junior mechanic or apprentice who is beginning to build up his set, it is a little smaller than the No. SB, but is built of the same heavy gauge steel and spot welded construction. Equipped with lift out socket tray, strong carrying handle, padlock hasp. Finished in blue baked enamel. Measures inside 21° x 7/x 6°.

Mechanics' Tool Boxes

Steel boxes as used in socket sets make excellent tool chests. Their sturdy steel construction makes them ideal for automotive mechanics, millwrights and plant engineers. Listed below is a complete assortment of boxes of this type. All are finished in attractive baked enamel.

No.	Length	Width	Depth
80B 82B 461B 1400B TG20B SB	21" 22-1/2" 20-1/4" 15-7/8" 17-1/4"	7" 5-3/8" 6-1/2" 3-3/8" 5" 7-1/2"	6" 3-5/8" 1-11/16" 1-3/4" 1" 8-1/8"

Duplex Tool Boxes

The Gray-Bonney Duplex "all steel" tool boxes have rugged construction and ample strength, yet by a slight pressure on the handle, the box opens and the tools are ready to lift out.

No. 100 Series

High quality boxes, having two trays on each side of handle. Three sizes available.



No. 114B—14" x 8" x 7-3/4"—Weight 9 lbs. No. 119B—19" x 8" x 7-3/4"—Weight 17-1/2 lbs. No. 121B—21" x 8" x 7-3/4"—Weight 20 lbs.

No. 500 Series

Specially designed for the mechanic having a limited amount of tools to carry around.



No. 514B—14" x 8" x 6"—Weight 7 lbs. No. 517B—17" x 8" x 7"—Weight 11 lbs. No. 521B—21" x 8" x 6"—Weight 16 lbs.

New Model MB82 Chest Mounted on CC Roller Cabinet

Safeguards Tool Investment Rolls Right Up to the Job

Rolls R

Reflects efficiency and promotes Customer Confidence!

> DIMENSIONS CHEST ONLY Height - 144" Width - 134" Length - 26%"

COMPLETE Height - 40 ¼ " Width - 13 ¼ " Length - 26 % "

WEIGHT Roller Cabinet Complete (less tools and crate) 92 lbs.

NUMERICAL INDEX . NEW ITEMS

o. Page	No. Page	No. Page	No. Page	No. Pa
A	514B 58 517 33	1497 8	2890	C45LR
		1607 56 1610 56	2891 23 2892 23	C46CB
6 41	5178 58 521B 58	1721 19	2892A 23	
10 41	522	1722 19	2893	C47CB
41	523	1723 19	2893A 23	CA41
41	524	1723A 19	2894	cc-
41	525	1725 19	2894A 23	CF1-(CF49)
2 41	526 38	1725A 19	2895 23	CF2
69 42	530 31	1725B 19	2895A 23	CF3-(CF11)
71 42	531 31	1726 19	2896 23	CF4
72 42	535* 57	1727 19	2897 23	CF11"
73 42	603 8	1728 19	3112 22	CF21'
CB 20		1729 19	311422	CF22
				CF23
	653L 8 654 33			CF26*
	655 8	1731A 19		CF49
LR 20 ECB 20	685 8	17315 19	3122 22 3124 22	CH06
ELR 20	686	1732A 19	3126 22	CH10
ALR 20	687 8	1733 19	3128 22	
23	699 8	1734 19	3129	CITTO
21	707 57	1735 19	3130 22	
21	709 8	1736 19	3132 22	CARLO
LR 21	710 57	1737 19	3134 22	CH16
LR 21	712 57	1738 19	3136	CLS
UJ 7	718 8	1739 19	3140 22	CL7
UJ 7	7185 8	1739A 19	3413* 7	CL13
UJ7	719 8	1739B 19	3414" 7	CL15
	719A 8	1964 55	3432 7	CP1
		2307LR 22 2311LR 22	3434" 7	CP2
A			4002 7	CP3
	827H 27 827L 27		4202 8 4206 8	CP4
	827V27			CS48
	839 29			D17
55	840 38	2320 22	4213 8 4215 8	D406S
55	842 39	2324 22	4266	D407S
58	1000 38	2326 22	4268 15	D408S
3 58	1001 27	2328 22	4272 15	
15	1602 27	2357D 30	4284 15	D410S
15	1003 27	2384 22	4285 15	
15	1019 19	2386	4288 15	
5 15	1020 19	2387 22	4289 15	D4148 D4325*
15	1021 19	2388 22	4295 15	DAW6
15 18 58	1022 19	2407 7	4298 8	DAWS
		2408 7	4299 8	DAWIG
	1004	2409 7	4897 8	DAW12
1.D		2410 7	6481 38	D06
ZA 24	1026 19	2411 7	6481 38 7940 39 7943A* 39	E02
2B 24	1027C 19		7944 39	E03
š 24	10275 19		1044	E14
1A 24	1028 19	2414 7	7944A 39 7944B 39	
4B 24	10285 19	2509 20	8385 35	E18
5* 40	1029 19	2000	8386	E20
40	1030 19	2566A	AT4 4	
* 40	1031 19	2590 15	AT5 4	
29	1032 19	2590-1 15	B6 32	E26
44	1033 19	2590-2 15	B8 32	E30
ZA 44	1033A 19	2591 8	B16	E40
C 44	1033C 19	2599 30	B17 33	E42
2E 44	1034 19	2612 30	B18 33	E44
		2618	B21 31	E46
		2626 39	B22 33	F2
3		2628 57	B23 33	F3
K 44		2629 30	B28 32	F4
* 40	1038A 19 1039 19	2680 31	B30 33	F5
29	1041 19	2723 20 2725B 20	B33	F6
* 40	1203 24			F7
32	1205 24			F10
LR 22	1207 24		C3	F12
22	1209 24		C5	
22	1238* 24		C6	
22	1258	2807 23 2807A 23	C7	F16
	1258B 39	2808 23	C10	F25
39	1400B 58	2809	C11	F26
	1406 7	2809B 23	C12 35	F31
7	1407 7	2810 23	C13 35 **	FB10
7	1408 7	2811 23	C15 35	FB14
7	1409 7	2811B 23	C16	FB19
7	1410 7	2811E 23	C18 35	FT57
7	1411 7	2812 23	C19 35	GA6
	1412 7	2812A 23	C21 35	GA8
2 7	1413 7	2812B 23	C22 35	GA10
3 7	1414 7	2812C 23	C23 35	GA12
1 7	1415 7	2812E 23	C25	GA15
7	1419 7	2813 23	C26 35	GA18
24	1421 7	2813A 23	C28 35	H10
24	1425 7	2815 23	C29 35	H12
B 58	1431 7	2815A	C30 35	H14
7	1432 7			H16
7 57	1433 7		C34	H18
57 2 57	1434 7	2821	C38 35	HC1

NUMERICAL INDEX . NEW ITEMS

No. Page	No. Page	No. Page	No. Page	REAMERS
HD13 17	MS	RF64 56	TS8 4	All 26
HD1817	MET 38		TS9 14	A 220
HD2118	M7T	RF71 55	TS10 4	
HD25 16	Ma' 38	RF72 56	TS14 4	BRITISH
HD3015	MB82 58	RESD 53	TS18 4	No. Page
HD31 16	MB82CC 58	Krat 63	1 TSLB 4	HDW14 50
HD32	MS79 10 MS102 9	Kr K5	T5204	MW1 50
HD34	MSR—(MR82)	54228 15 54232 15	TU7	MW2 50
HD3815	MSB— (MB82) MSC - CC	54234	TU11' 22	MW3
HD40 18	MSEC—(MB82CC)	S4240	TUI4	MW6
HD42	MSBC—(MB82CC) N50—(NF50) N100—(NF100)	54248 15 58 55	TU164	MW6 50
HD4616	I N150—(NF150)	SE1	TU16 4	MW7 80
HD48 15	NF25' 14	SE2 27	TW 25	MWs 50 MW9 50
HD5015	NF50 14 NF100 14	SE3 27	TW4 25	MW10 80
	NF150* 14	SE4	TW8 28	W4T 81
HD54 15		501	TW6 26	W70 31
HD64	NF300*14	502 43	TW7 25	W71 81
HD6015	NH6* 40	504	TW10 25	W73 81 W77 51
HD64	NHS' 40	306	TW12 25	W27 51
MEIDIA 5/	N3P6 26	5012 41	V43	W79 51
HS1024 57	NSP10 26	SP1 42	V7	W87* 51
HS1032 57	NSP14 25	SP2 42 SW1 8	VP	W123 83
H51224 57	NSP18 25 NSP24 25	5W1413	V10	W122A 51
H51232 57	NSP36 25	5W16	V11	W124 53 W152 50
HW6*	NSP48	SW18T 7	V12	W163 50
HW10	PC3934	SW18	I V17 3	W154
HY1014	PH15 44	SW2312	V18 3	W185 50 W188 50
K1 40	PH16 44	SW35 11	V19	W158 50 W157 50
	PH19 39	5W44 11	V22 3	11/166 50
22 40	PH2044	T1 ‡	V20	W15P 50
KB 40	PH22	T44	V273	W16050
K.160	PH24 44	Т5 4	V27 3 VG7(1607) VG10(1610)	W162 50
KB1	PH2544	TO4		W183 50
K63	PH26 45 PH27 45	TID 4	V\$10 3	W164 50
K84 38	PH3048	T14 *	VS12	W176 51
K.55	PHB44	<u> </u>	VS13 3	W177 51
KB6	PHC 44	TIB	VS24	W178 51
K.50	PHL44	T20	V\$30 3	W179 51
K.50	PHR 44	T22 4	W1 23 W2 25	W774 51 W775 51
L401A24	R2 43	T24 4	W2 25	W776 51
1402 24	R3	T26 4	W3 25	W78L 51
L404	RB2 42	T30 4	W4 25 W8 25	W762 \$1 W763 51
LDB	RB3 42	T314	W5	TV784 51
LDIS	RB12142	T32 4	W7	W793 51
LDIS	RB122 42 RB123 42	T35	Ws25	W794 51
LD20	RCL	T34 4	W111.R25	W795 51
LD24	RC2 28	T42 4	W12	W797 51
LD26	RC329	T128 4	W16 25	WBALR 61
LD28	RE329	T160 4		WB12 49 WB15 49
LD30 1	RZ6 27	T160	W2025 W2425	WB19 49
LD32	RF2 58	T200 4	W03	W 2549 44
ID36	RF3 55 RF4 66	T240 4	W0441	TUTIES 51
LH32 16	RF6 56	T260 4	W0641	WB96 51 WB190 51
LH3416	RF6 66	T280 4	W010 41	WB312 40
LH3516 LH4018	RF10 85	TA1018 57	WP42	WE01 51
L01 26	RF12 55	TA1032 57	W7-1	WES 51
LO325	RF13 55	TA1218 \$7	WP242	WF91 BI
L0173 29 L0200 40	RF14 55 RF16 55	TA1224 57 TA1232 57	WP442	WE32 B1
L0201 40	RF17 65	TC2 43	X29 18	
L0201F 40	RF18 58	TG12 5	X3618	WE54 51 WE67 51
1.0202 40	RF21 54	TG15 5 TG20B 58	X3118 X3218	
L0203 40 L0675—(BU40)	RF22	TG20B58 TG20—(TG21)	X3318	WH160 50
LoseeC 31	RF25 54	TG21 5	i X44 18	WH181 50
Lessof 31	RF40 85	THE 43	X48	WH162 50 WH163 50
L0820 31 C0826 31	RF41 55	TH8 43 THIO 4	X52	WHI64 50
LT9	BPAR SR	THI2 4	X6018	WH188 60
LT18 4	RF47 56	TH14 4	X64	WH166 50
III4	RF49 55	THIS 4	X7018	WH167 50
LTIS 5	RF64 54	THIS 4	X72 18	WH168 50
LTIS	PF65	TH20 4	X7815	WL154 50
LT22	RF55A 54	TH24 4	X7818	WL155 50
LT24 4	RF67 54	TRI 27	X8018 X8219	WL156 50
LTM	RF60 56	TR2	X44	WL187 50 WL158 50
LTSIS	RF61 56	TR6 43	X8810	WL158 50
LT814 4	RF62 56	TRS 43	X94	WL160 50
LT3164	RF63 56	TR:0	X96	WL161 50
LT316 4	RF64	TS4 43	XH 18	WL183 50

IT IS JUST AS EASY TO USE A TORQUE TORQUE CHART WRENCH AS ANY SOCKET HANDLE

MANUFACTURERS' RECOMMENDATIONS FOR PROPER TORQUES

Footpounds of torque for threads clean and dry. If threads are cleaned and oiled, applied torques should be reduced about 10%.

===	about 10	_ ,		·· 			_			SPAF	=
	MODEL N	EAR-	YLINDER HEADS	MOTOR	BEARINGS	FLYWHEEL		MANIFOLDS		Cast	25 _
KE	MODEL Y		Cast Iron	Connecting Rods	Main Bearings	TO CRANK. SHAFT	Intake	Exhaust	Water	[ron_	Size
-L &6	0-54-1942-4		65-70	45-50	120-130	45-55	25 30	28-30			14MM 10MM
6	0.70.00-194	2-46	65-70	60-65	120-130	45-55	25-30	25-30		22-28	14MM
- 4	0.50-1947-4	9	65.70	40-45	90-100	35-40	25-30	25-30		22-28	14MM
- 7	0-1947-49		65.70	6D-65	90-100	45-50	25-30	25.30	25-30	22 · 26 12 · 15	LOMM
dillaci	-All 1942-4	5	70.75	50-80	140-150	65-70	25-30	25-30		12-15	LUMB
	All 1946		70-75	60-65	130-140	Std. 65-70 Hyd. 70-75	25-30	25-30		7-1D	MMO
				60.65	130-140	Std. 65-70 Hyd. 70-75	25-30	25-30	15-18	7-10	10MM
	AIL 1947-4		70-75 65-70	40-45	90-100	Sid. 65-70 Hyd. 70-75	25-30	25-30	25-29	20-25	14MM
4	All 1949				*100-110	*50-65		5tod Nut 25-30 Clamp Boit 15-20	25.30	12-15 20-25	14MM
EVrol	Trucks, 12	10 Z	70-60	40-50				Stud Nut 25-30 Clamp Holt 15-20		12-15 20-25	10MM
	Ten1940-	49	70-80 Nut 55-60	40.50 3.8 45.50	*100-110 Nut 75-80	*50-65			25-30	30-32	14M)
			Ap. 5. 65-70 Nut 55-60	7/16" 50-75	Cap. S. 80-85	55-65	15-20	15-20	25-30	30-32	34MN
	All 1939-49		nu 5. 65-70 Nut 52-57	3/8" 45-50 7/16" 50-75 3/6" 45-50	Nut 75-80 Cap. S. 60-65 Nut 60-65	65-85	15-20	18-20		26-32	14M3 14M3
od ze A	-All Cars-1	939-49 939-45 (Nut 52-57	7 16" 50-75	Cap. S. 85-90	55-60	15 20	15-20 Brass Nut 12-1	25-30	30-32	
	rucks-1949		55-60	50-75	85-90	65-60	25-30	30-35 3/8-1623-28	Wir Pint	30-32	14MJ
	Cyl.—All to	1949	65-70	45-50	\$80-90 995-105	75-85	23-28	7/16-14-45-50	23-28	25-30	14M
-	ii 8 Cyl., 142		Nut 50-55 Cap. S. 65-70	52-60	#120-130	75-65	23-28	23-28	23-28	24-28	34M
• F	erguson-Ford		65-70	45-50	580-90 195-105	75-65	23-28	23-28	23-28	25-30 27.5	14M L4M
udson	6 & 8 Cyl.	Alumin	46	52	92		15-20	20-30	Aluminum	22-26	
· A	1) 1942-46	A.C.	6 Cyl. 40 8 Cyl. 60	40-45	55-75	40-50	16-20	20-30	15-20	25-30	14M
	UI 19 46-4 9		r Cvl.—70-75		75-80		12-15 15-20	20-30	12-15 15-20	20-25	14M
-			8 Cyl.—45-50	40-45	70-80 85-96	40-45 35-40	30-35	30-35	30-35	20.30	14M
AISCT	Frazer-194	7-49	30-35 45-50	40-45	60-70	45-55	30-38	30-35		28-32	14M
incolr	All to 194			40.48	00.70				Aluminun	24-28	
		Alumin	um 35-40 Nut 50-55				_				1439
incult	n—All to 194	19	Cap. S. 65-70	52-60	₿120-130	75-85	23-28	23-28 23-28	23-28	24-28 24-28	
dercus	y-All to 15	49	65-70	45-50	§80-90	76-85	23-25				
ash '	L" Head 6-	-	57-60	27-30	68-70	62-56				25.30	14 N
	Over Hd.—Al	16	65-70	52-56	68-70	P6-100				25-30	148
Oldsm	obile	41.47.1			Front & Int.—10	00 Std. 55-60					
	Cyl.—1948-4	(9)	60-70	l 45-50	Rear Brg14	0 Hydru. 60	11-14	22-26	22-26	28-35	143
	8 Cyl.—1948				Front & Int 10	00 Std. 85-95		22-26	22-26	28-35	143
	6 Cyl —1949		60-70	45-50	Rear Brg 14	0 Hydra. 95	22-26		25-30		
*nckar	-d—6 & 8 Cyl	1942-4	6 60-62	45-46	82-85	65-70	25-30		25-30		
	Super 6-194	2-46	60-62	56-56	82-85	65-70	25-30	23-30		100	
	All Models	1946-48	7,16-20- 60-62	7/16-2860 3 8-2445	3-65 Cmp. S. /s- 46 90-95	-13 ½-2070 7/16-20-55-6	.80 0 25-30	25-30	25-30	10-14	10
¹ly mo	uth—All 193	9-49	Nut 52-57 Cap. S. 65-70	80.75	80-85	55-60	15-20	15-20	25-30	30-32	140
						6 Cyl105				25-30	14
Pontia	c-All befor	1946	60	45	85	8 Cyl.—70				25-30	
	All 1946-48		60	45	Front & Int.—I						
	Ali 1949		60	45	Rear Brg1					25-30	
Stude	baker Preside Çom'der-	nt &	80-85	52-54	88-93	<u> </u>				33-42	
ji	Champion-1 Truck M5, M	D42-49	46-50	26-32	85-93	33-35	25-30		25 · 30		
	Cmdr. & Lat 1947-49			52-54	88-93	33-35	25.30				
	Truck M16	941 47	80-85	\$2-54	85-93	33-35	25-36		25:30		
	Truck 14A.	2R10,	46-50	28-32	88-93	33-35	25-30		25-30		
	2R15—19		40 HA PE	52-54	88-93	33-35	25-3		25-34		
	Truck 2R16,	2K17—L9		50-55	65-70	36-40	31-3	31-35	20-2	5 25-3	0 14
	-All to 19		Nut 60 65								

Rocker-arm Shaft Balte-Buick 30-35. Chevrolet-25-30. Nash-15-20. *Threade Oiled.
*Inch Pounds. \$Boilt and Leckwasher. 'Ball-Lucking Boil.
Torque requirements are given in both fost pounds and inch pounds. One foot pound is the same as twelve inch pounds.
Torque requirements are given in both fost pounds and inch pounds. Torque is twist, the standard unit of measure being TORQUE and TENSION are design twely different and must not be confused. Torque is twist, the standard unit of measure being fost pounds; teasion is straight pull, the unit of measure being pounds. Weathes designed for measuring the tightness of a nut are distinctly Torque wreaches and not teasing screeches.



CHART OF WRENCH AND SOCKET OPENINGS AND SIZES

Wrench Opening	American Standard Reg. Bolts	American Standard Reg. Nuts; Size Bolts	Amer. Std. Heavy Nuts (U.S.S.); Size Bolts	Amer. Std. Light Nuts (S.A.E.); Jam Nuts, Castle Nuts and Slotted Nuts; Size Bolts	Cap Screws	Set Screws	Machine Screw Nuts and Stove Bolt Nuts	Wrench Opening
5/32							No. 0 & No. 1	5/32
3/16		***************************************		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			No. 2 & No. 3	3/16
1/4		************		Berramina		1/4	No. 4	1/4
5/16		,				5/16	No. 5 & No. 6	5/16
11/32	***************************************	***************************************					No. 8	11/32
3/8	1/4					3/8	No. 10	3/8
7/16		1/4		1/4	1/4	7/16	No. 12 & No. 14	7/16
1/2	5/16	***************************************	1/4	5/16	5/16	1/2		1/2
9/16	3/8	5/16		3/8	3/8	9/16	5/16	9/16
19/32			5/16	****				19/32
5/8	7/16	3/8		. 7/16	7/16	5/8	3/8	5/8
11/16	1/2		3/8	1./2				11/16
3/4	1/2	7/16		1/2	1/2	3/4		3/4
25/32			7/16					25-32
13/16	9/16	1/2		9/16	9/16			13/16
7/8		9/16	1/2	5/8	5/8	7/8		7/8
15/16	5/8		9/16	5/0				15/16
		5/8		3/4	3/4	1		
1-1/16	3/4	2/4	5/8	3/4				1-1/16
-1/8	3/4	3/4		7/8	7/8	1-1/8		1-1/8
1-1/4	7/8	7/8	3/4	1/0		1-1/4		1-1/4
-5/16	1/0	1/8			1	1.2/0	******************************	1-5/16
-3/8 -7/16	2		7/8	1	***************************************	1-3/8		1-3/8
-1/10	1	1	1/0		1-1/8	1-1/2		1-1/10
-5/8	A CONTRACTOR	6	1	1-1/8	1-1/8	1-1/2	***************************************	1-5/8
-11/16	1-1/8	1-1/8		7 7 7 7 7	1-1/4			1-11/16
-13/16	1-170	1-1/0	1-1/8	1-1/4	1-1/4		**************************************	1-13/16
-7/8	1-1/4	1-1/4	,.					1-7/8
	-		1-1/4	1-3/8				2
-1/16	1-3/8	1-3/8	1000					2-1/16
-3/16	100 No. 100 No.		1-3/8	1-1/2				2-3/16
-1/4	1-1/2	1-1/2				2 2000000000000000000000000000000000000		2-1/4
-3/8			1-1/2		C. Elegan			2-3/8
-7/16	1-5/8	1-5/8						2-7/16
-9/16			1-5/8					2-9/16
2-5/8	1-3/4	1-3/4						2-5/8
2-3/4	gan	ž	1-3/4					2-3/4
2-13/16	1-7/8	1-7/8						2-13/16
2-15/16			1-7/8					2-15/16
	2	2	***************************************					3
I-1/8			2					3-1/8
3-3/8	2-1/4	2-1/4				•		
3-1/2			2-1/4					
1-3/4	2-1/2	2-1/2			e			
3-7/8	2.2/4	0.074	2-1/2				***************************************	
⊢ 1/8	2-3/4	2-3/4			***************************************		***************************************	
-1/4	3	3	2-3/4					
1-1/2	3	3	3	(((((((((((((((((((((((((((((((((((((((*			
4-5/8								
5-3/8		***************************************	3-1/4	***************************************				
		***************************************	3-1/2	***************************************				
5-3/4			4		***************************************	· · · · · · · · · · · · · · · · · · ·		
5-1/8		***************************************			£0000000000000000000000000000000000000		***************************************	



GRAY-BONNEY AUTOMOTIVE HAND TOOLS

Numerical and Alphabetical Price List PLA-1

Applying to Catalogue No. 51 also previous Catalogues Nos. 50, 550, 49 and 48.

Supersedes Issue Dated Dec. 30, 1950 Effective April 27, 1951.

Tool	List	Net	Tool	List	Net	Tool	List	Net	Tool	List	Net
0A	,35	.30	212C	3.15	2.40	718	2.40	1.85	1421	1.40	1.1
01	.45	.35	212E	2.70	2.10	718S	2.00	1.55	1425	1.40	1.1
0.3	1.40	1.10	212G	2.30	1.80	719	2.80	2.15	1431	1.80	1.4
06	1.55	1.20	212H	2.10	1.60	719A	3.40	2,60	1432	1.80	1.4
010	1.75	1.35	2121	2,00	1.55	720	3.60	2.75	1433	2.00	1.5
	1.60	1.25	212J	2.00	1.55	827	26.00	18.90	1434	2.20	1.7
4	2.10	1.20	212K	2.00	1.55	827H	2.80	2.15	1435	2.20	1.7
0	2.10	1.60			2.95	827L		2.60	1436	2.40	1.8
0		2.05		3.80	2.33	827V		3.65	1497	10.40	7.5
		2.90	220	4.20	3.20			3,93	1907/VC(7)	3.20	2.4
000		.70	August	4.80	3.65			.90	1607(VG7)	3.20	
041	1.10	.85	490	3.60	2.75			.60	1610(VG10)	3.80	2.9
672	3.90	3.00	270LR	9.70	7.45		2.40	1.85	1721 1722	1.20	.9
672	1.30	1.00	276	1.90	1.45	1000	4.40	3.35	1722	1,20	.9
T	7.60	5.80	277	2.10	1.60	1001	13.80	10.05	1723 1723A	1.20	.9
ECB	13.05	9.50	278	2.30	1.80	1002		17.45	1723A	1.20	1.1
ELR	14.25	10.35	279	2.60	2.00	1003	38.00	27.55	1725	1.45	1.1
T	11.40	8 30	308	4.00	3.05	1019	1.00	.75	1725A	1.45	1.1
T ALR	21.05	8.30 15.30	309	11.60	8.45	1020	1.00	.75	1725B	1.45	1.1
ALLE	20.30	14.75	403	.90	.70	1021	1.20	.90	1726	1.80	1.4
OFFER				1.80	1.40	1022	1.20	.90	1726 1727	1.80	1.4
0ELR	22.50	16.35	400		1,40		1.20	90	1728	2.20	1.7
2ALR	30.15	21.90	401	1.20	.90	LUAG			1728 1729	2.20	1.7
5	16.50	12.00	400	1.20	.90			1.10	1730		1.7
0	13.60	9.90	403	8.1.60	.90		1.45	1.10		2.20	1.6
7	16.85	12.25	410	1.20	.90	1026		1.40		2.80	2.1
OLR	10.80	7.85 6.05	411	1.40	1.10	1027		1.40		2.80	2.1
1LR	7.90	6.05	412	1.40	1.10	1027C	1.80	1.40	1731B	2.80	2.1
LITP	4.80	3.65	413	1.60	1.25	1027S 1028	1.80	1.40	1732	2.80	2.1
3111	4.80	3.65	414	1.80	1.40	1028		1.70	1732A	2.80	2.1
7UJ	5.00	3.85	415	1.80	1.40	1028S	2.20	1.70 1.70	1733	3.60	2.7
0	5.40	4.15	426	2.60	2.00	1029	2.20	1.70	1734	3.60	2.7
9 1-4		2.10	428	3.00	2.30	1030	2.20	1.70	1735	3.60	2.7
1-4	3.90	3.00	1440		3.85		2.80	2.15		4.60	3.5
103	5.00	3.85	4010	5.00	3.80	IOOL	2.80	2.15	1736 1737	4.60	3.5
	0.40	4.00	900	1.40	1.10			2.15	1738	7.80	5.9
9UJ	0.00	4.30	13/11/4		2.75			2.15		7.00	5.9
	17.00	12.35	310	9.00	3.50			2.15		7.80	
0	7.00	5.40		5.40	4.15	1033C		2.75		7.80	5.9
24	1.80	1.40	513	4.80	3.65	1034		2.75 2.75	1739B	7.80	5.9
24	2.40	1.85	514B	11.00	8.00	1034A		2.75	1964	7.60	5.8
OR	10.60	7.70	517	2.80	2.15	1035	3,60	2.75	2307LR	17.80	12.9
9D	00.3	4.60	517R	15.40	11.20	1037	4.60	3.50 3.50	2311LR	26.30	19.1
6	6.40	4.90	521B	17.60	12.80	1037A	4.60	3.50	2316	1.80	1.4
			522	3.00	2.30	1038A	7.80	5.95	2318	2.00	1.5
	0.00	4.60	523		2.95	1039	7.80	5.95	2319	2.20	1.7
0	5.20	4.00	040	0.00	2.30		12.00	8.70	2320	2.20	1.7
00	4.40	3.35	0.44	3.00	2.30 3.80			0.70	2322	2.40	1.8
3	1.60	1.25	020	5.00	3.80			1.85 1.85		2.40	1 1
0	17.60	12.80		2.80	2.15			1.85			1.8
IAD	17.60	12.80	930	4.50	3.45	LAVE		1.85		2.70	2.1
19B	23.00	16.70	531	1.80	1.40	1209		1.85	2328	2.90	2.2
21R	24.00	17.45	535	6.20	4.75	1238	3.20	2.45	2357D	2.60	2.0
22	1.60	1.25	603	7.20	5.50	1258	2.60	2.00	2384	1.50	1.1
99A	1 60	1.25 1.25	652	6.60	5.05	1258B	1.40	1.10	2386	1.80	1.4
22B	1.60	1 25	653	7.20	5.50	1400B	2.80	2.15	2387	2.00	1.0
CAD		1.25 1.40	653L	7.60	5.80	1406	1.20	.90	2388	2.20	1.3
24	1.80	1.40					1.20	.90	2407	1.20	. 5
24A	1.00	1.40	00.8		4.00	T.W. 1	1.20			1.20	
	1.00	1.40	600	.80	.60	1400		.90		1.20	
25		1.70	909	2.00	3.05			.90		1.20	.5
24	2.55	1.95	000	3.60	2.75	1410		.90	2410	1.20	- 1
29	2.65	2.05	687	3.20	2.45	1411		1.10	2411	1.40	1.1
99	2,60	2.00	600	3.20	2.45	1412	1.40	1.10	2412	1.40	1.1
99 Blades	1.00	.75	707	3.60	2.75	1413	1.40	1.10	2413	1.60	1.2
Diego of K	1.00		709	4.80	3.65	1414	1.60	1.25	2414	1.60	1.2
Pkgs. of 5)	3.80	2.95	710	5.20	4.00	1415	1.60	1.25	2509	2.10	1.6
2.0	3.45	2.65	712	6.60	5.05	1419	1.20	,90	2566	1.90	1.4
212A											



Numerical and Alphabetical Price List

Tool	List	Net	Tool	List	Net	Tool	List	Net	Tool	List	Net
2566A	1.90	1.45	3414	2.25 2.70	1.70	C38	2.65	2.05	F13	4.60	3.50
2586	1.60	1.25	3432	2.70	2.05 2.60	C45CB	7.85	6.00	F15	3.40	2.60
2590	17.40	12.65	3434	3.40	2.60	C45LR	9.45	7.20	F16	3.40	2.60
2590-1	4.00	3.05	4002	2.20	1.70	C46CB	18.00	13.10	F24	4.60	3.50
2590-2	4.00	3.05	4124	See	D412S	C46LR	20.40	14.85	F25	6.00	4.60
2591	7.00	5.40	4128	See	D414S	C47CB	38.10	27.70	F26	36.00	26.15
2599	2.40	1.85	4132	See	D4328	C47LR	42.90	31.20	F31	4.20	3.20
2612	2.40	1.85	4202	2.20	1.70 1.70	CA41	16.00	11.65	FB10	58.35	42.40
2618	2.60	2.00	4206	2.20	1.70	CC	78.00	56.70	FB14	75.95	55.20
2626	3.60	2.75	4211	5.80	4.45	CF2	4.40	3.35	FB19	107.25	78.00
2628	2.80	2.15	4213	7.20	5.50	CF3	Use	CF11	FT57	2.80	2.15
2629	2.80	2.15	4215	2.20	1.70	CF4	11.50	8.35	H10	1.80	1.40
2680	5.00	3.85	4266 4268	9.40	7.20	CF11		12.05	H12	2.00	1.40
2723 2725B	1.80 2.40	1.40		10.00	7.20 7.25 10.45	CF21 pr. CF22 pr.	1.75	1.35 1.35	H14 H16	2.00	1.5
2729RA	3.50	2.70		14.40	8.30	CF23 pr.	1.75	1.35	H18	2.00	1.58
2804C	1.80	1.40		26.40	19.20	CF26 pr.	4.50	3.45	H18S	2.20	1.70
2804L	1.80	1.40		14.50	10.55	CEAO		3.85	HC1	4.50	3.45
2805L	2.00	1.55	1000	2.00	1.55		1.40	1.10	HD11	51.60	37.50
2807	2.20	1.70		15.20	11.05		1.40	1.10	HD13	70.80	51.45
2807A	2.20	1.70		2.60	2.00			1.10	HD15	79.00	57.45
2808	2.40	1.85		2.80	2.15			1.10	HD21	119.70	87.00
2809	2.80	2.15		11.00	8.00			1.10	HD25	154.70	112.40
2809B	2.80	2.15	6481	1.60	1.25	CH12 CH14	1 00	1.25	HD28	2.40	1.85
2810	3.30	2.55	7940	4.80	3.65			1.25	HD30	2.40	1.85
2811	5.10	3.95	7943A	2.00	1.55	CL3	0 00	1.70	HD31	2.40	1.85
2811B	5.10	3.95	7944 with		2100	CL5		2.30	HD32	2.60	2.00
2811E	5.10	3.95	7944B	4.80	3.65	CL7	4.00	3.05	HD34	2.80	2.15
2812	6.00	4.60	70111	5.60	4.30	CL13	2.00	1.55	HD36	2.90	2.20
2812A	7.30	5.60	8385	4.85	3.70	CL15		1.55	HD38	3.00	2.30
2812B	6.00	4.60	8386	3.30	2.50	CP1	1.35	1.05	HD40	3.20	2.45
2812C	6.00	4.60	AT4	3.80	2.90	CP2	1 90	1.40	HD42	3.40	2.60
2812E	8.40	6.45	AT5	4.20	3.20	CP3	0 40	1.85	HD44	3.40	2.60
2813	8.40	6.45	B6	1.20	.90	CP4	2 60	2.75	HD46	3.80	2.90
2813A	8.40	6.45	B8	1.40	1.05	CS48	170 00	125.00	HD48	4.30	3.30
2815	19.80	14.40	B16	2.80	2.15 3.20	D17	94 60	17.90	HD50	4.70	3.60
2815A	25.20	18.30	B17	4.20	3.20	D406S	1.50	1.15	HD52	5.00	3.85
2815B	19.80	14.40	B18	4.90	3.75	D4078	1.50	1.15	HD54	5.60	4.30
2819	25.20	18.30	B21	4.60	3.50	D408S	1.50	1.15	HD56	6.00	4.60
2821	44.40	32.30	B22	4.20	3.20	D409S	1.55	1.20	HD58	6.30	4.80
2883	3.00	2.30	B23	5.20	4.00	D410S	1.55	1.20	HD60	6.60	5.05
2884	3.10	2.35	B28	4.80	3.65	D411S	1.60	1.25	HD64	7.20	5.50
2890	1.70	1.30	B30	4.80	3.65	D412S	2.05	1.55	HD70	10.20	7.40
2891	1.90	1.45	B33	5.00	3.85	D414S	2.05	1.55	(Pkgs. of 10) HS1018 "		
2892	2.10	1.60	BU40	10.00	7.25	D432S	2.70	2.05	HS1018 "	6.60	5.05
2892A	2.10 2.30	1.60	C2 C3	1.00	.75	D06	16.10	11.75	HS1024 "	6.60	5.05
2893	2.30	1.80	C3	1.20	.90	E02	1.20	.90	HS1032 "	6.60	5.05
2893A	2.30 3.00	1.80	C4	1.45	1.10	E03	1.75	1.35	HS1218 "	8.00	6.10
2894	3.00	2.30	C5	2.00	1.55	Tubes	.50	.40	HS1224 "	8.00	6.10
2894A	3.00	2.30	C6	2.20	1.70	E14	1.20	.90	HS1232 "	8.00	6.10
2895	3.90	3.00	C7	2.65	2.05	E16	1.20	.90	HW6	2.00	1.55
2895A	3.90	3.00	C10	2.65	2.05	E18	1.20	.90	HW8		1.70
2896	6.60	5.05	C11	1.20	.90	E20	1.20	.90	HW10	2.40	1.85
2897	6.60	5.05	C12	1.35	1.05	E22	1.30	1.00	HY10	26.60	
3112	2.00	1.55	C13	1.55	1.20	E24	1.30	1.00	K1	2.00 3.90	1.58
3114	2.00	1.55	C15	1.35	1.05	E26	1.30	1.0)	K2		3.00
3116	2.20	1.70	C16	1.55	1.20	E28	1.30	1.00	K4	1.20	.90
3118	2.40	1.85	C18	1.35	1.05	E30	1.45	1.10	K6		
3120	2.60	2.00	C19	1.55	1.20	E40	1.60	1.25	K8	1.40	1.10
3122	2.80	2.15	C21 C22	.90	.70	E42		1.25	K50	1.80	1.40
3124	3.00	2.30	C22	.95	1.00	E44			K51	1.80	1.40
3126	3.20	2.45	C23	1.30	1.00	E46		1.60	K52		2.48
3128	3.40	2.60	C25	1.10	.85 1.05	FZ FD	4.40	3.35	K53	3.20	1.10
3129	4.00	3.05	C26	1.35	1.05	F3	4.40	3.35	K54	1.40	1.10
3130	4.00	3.05	C28	1.00	.75	F4	4.80	3.65	K55	2.40	1.8
3132	4.60	3.50	C29	1.10	.85	F5	4.80	3.65	K56		1.40
3134	5.60	4.30	C30	1.35	1.05	F6	6.00	4.60	K57	1.80	1.40
3136	5.60	4.30	C28 C29 C30 C32 C34	1.00	.75 .70	F7	4.40	3.35	K58	2.40	1.85
3140	7.20	5.50	C34	.90	2.70	F10	5.40	4.15	K59	1.80	3.35
3413	2.10	1.60	C36	2.65	2.05	F12	6.00	4.60	L401A	4.40	0.00



Numerical and Alphabetical Price List

Tool	List	Net	Tool	List	Net	Tool	List	Net	Tool	List	Net
L402	4.40	3.35	N100	Use	NF100	RF54	3.60	*2.75	T35	8.40	6.45
L403	4.40	3.35	N150	Use	NF150	RF54A	3.60	2.75	T36	2.60	1.25
404	4.40	3.35	NF25	31.00	22.55	RF55		3.20	T42	3.20	2.45
DE	14.20	10.35	NF50	33.00	24.00	RF55A		3.20	T128	1.60	1.25
D10	26,00	18.90	NF100	34.80	25.30	RF57		2.00	T140	1.60	1.25
DIG	2.00	1.55	NF150	45.90	33.35	RF59		3.05	T160	1.60	1.25
D18	2.00	1.55	NIESOO	73.20	53.20	RF60		.45	T180		
D20	2.40	1.85	NF300	91.80	66.70	RF61	.60	.45		1.60	1.25
D22	2.40	1.85	NH6					.45	T200	1.80	1.40
D24	2.40	1.00	NHO	3.10	2.35	RF62	.60	.45	T220	1.80	1.40
13344	2.40	1.85	NH9	3.40	2.60	RF63	.60	.45	T240	2.20	1.70
1D26	2.40	1.85	PC39	47.25	32.15	RF64	.60	.45	T260	2.20	1.70
11120	2.40	1.85	PH4M	6.00	4.60	RF65	.60	.45	T280	2.20	1.70
D30	2.40	1.85	PH5M	7.00	5.35	RF66	3.60	2.75	(Pkgs. of 10)		100
D32	2.80	2.15	PH15	3.20	2.45	RF67	2.20	1.70	TA1018 "	1.60	1.20
D34	3.40	2.60	Tips	.80	.60	RF71	1.80	1.40	TA1024 "	1.60	1.20
D36	2.80	2.15	PH18	2.40	1.85	RF72		1.40	TA1032 "	1.60	1.20
H32	3.90	3.00	Tips	.60	.45		1 00	1.40	TA1218 "	2.00	1.55
H34	4.30	3.30	PH19	5.40	4.15	Dren	22 00	23.85	TA1224 "	2.00	1.55
H36	4.60	3.50	PH20	3.40	2.60	DEOI	40 70	34.00	TA1232 "	2.00	
H40	5.80	4.45	Tips	.80	.60	Drog	144.80	105.25	TC2	1.70	1.55
.01	58.00	42.15	PH22	3.75	2.85	C4998				1.70	1.30
03	88.00		PH23		9.60	S4228 S4232	4.20	3.20	TG12	19.15	13.90
		63.95		3.40	2.60		4.80	3.65	TG15	37.55	27.30
.0130 .0131	10.40	7.55	PH24	4.60	3.50	84234	5.00	3.85	TG20B	3.00	2.30
	11.00	8.00	PH25	4.20	3.20	S4240	6.80	5.20	TG21	48.20	35.05
0173	18.90	13.75	PH26	4.20	3.20	84246	8.00	6.10	TH6	2.80	2.15
0200	26.80	19.50	PH27		3.00	SB	21.40	15.55	TH8	2.90	2.25
.0201	2.40	1.85	PH30	3.60	2.75	SEI		1.40	TH10	1.30	1.00
0201F doz.	2,40	1.85	PHB	.90	.70	SE2	1.80	1.40	TH12	1.30	1.00
0202 doz.	6.40	4.90	PHC	1.00	.75	SE3 ·	2 00	1.55	TH14	1.30	1.00
0203	.70	.55	PHL	.90	.70	SEA	2 20	1.70	TH16	1.30	1.00
0875	See	BU40	PHP	1.00	.75	SEE	9 80	2.15	TH18	1.30	1.00
0899C	2.40	1.85	PHR	.90	.70	S01	1.20	.90	TH20		1.00
0899F doz.	2.40	1.85	PT101	5.50	4.20	S02	.80	.60	TH22	1.30	
.0920 dez.	6.40	4.90		.90		S04				1.40	1.10
.0925	32.00	23.25			.70		1.80	1.40	TH24	1.40	1.10
T9	32.00	23.25		1.20	.90	S06	2.40	1.85	TR1	4.40	3.35
	13.60	9.90	RB1	.80	.60	S08	3.30	2.50	TR2	4.40	3.35
T12	1.20	.90	RB2	.80	.60	S012	4.00	3.05	TR4	1.50	1.15
T14	1.20	.90	RB3	.80	.60	SP1	.80	.60	TR6	1.55	1.20
T16	1.20	.90	RB121	.80	.60	SP2	.80	.60	TR8	1.70	1.30
T18	1.20	.90	RB122	.80	.60	SW1	16.00	11.65	TR10	1.70	1.30
T20	1.40	1.10	RB123	.80	.60	SW2		17.10	TS4	1.70	1.30
T22	1.60	1.25	RC1	2.20	1.70	SW12T	18.30	13.30	TS7	1.70	1.30
T24	1.80	1.40	RC2	4.20	3.25	SW14	27.40	19.90	TS8	1.30	1.00
T26	2.00	1.55	RC3	4.80	3.65	SW15	41.20	29.85	TS9	1.80	1.40
mao	2.00	1.55	RC4	11.40	8.30	SW15T	25.20	18.30	TS10	1.30	1.00
TOIN	1.60	1.25	RE3	7.80	5.95	SW18	54.00	39.25	TS12	1.30	1.00
TOTA	1.60	1.25	RE5	10.40	7.55	SW20	55.60	40.45	TS14	2.00	
TRIC	1.60	1.25	73.73.0	1.40	1.10	CITTON		45.20			1.55
TC10	1.80	1.40	TATIO	1.40	1.10					2.00	1.55
TCOO	2.00		W2. W2. 4			CHARLES		67.60		2.20	1.70
W1	2.20	1.55		1.40	1.10	SW44		89.25		2.20	1.70
W1 W2	2.20	1.70	RF5	1.40	1.10	T1		1.30	100	20.00	14.55
	2.75	2.10	RF6	1.80	1.40	T3	4.00	3.05	TU9	27.20	19.75
W3	2.75	2.10	RF10	1.20	.90	T4	2.40	1.85	TU11	34.60	25.15
W4	2.20	1.70	RF11	1.20	.90	T5		2.15	TU14	3.60	2.75
15	2.60	2.00	RF12	1.20	.90	T9		2.60	TU16	3.60	2.75
16T	2.60	2.00	RF13	1.60	1.25	T10		.80	TU18	3.80	2.95
171	2.80	2.15	RF14	1.60	1.25	T12		.80	TU20	3.80	2.95
18	5.25	4.00	RF16	1.80	1.40	T14		.80	TWCB	12.15	8.85
19	5.80	4.45		1.80	1.40			.80	TW4		
IB82	96.00	69.75	TOTALO	1.80	1.40					1.40	1.10
AB82CC	174.00	126.45	TITIOI	5.20			1.05	.80	TW4 Bit	.20	.15
1S79-SB					4.00	T19	1.05	.80	TW5	1.40	1.10
	207.15	150.50	RF22	4.80	3.65	T20	1.10	.85	TW5 Bit	.20	.15
4S102-	329.05	239.00	RF23	5.20	4.00	T22	1.20	.90	TW6	1.40	1.10
MB82		120129	RF25	5.20	4.00	T24	1,20	.90	TW6 Bit	.20	.15
IS102-	407.05	295.80	RF40	1.20	.90	T26	1.70	1.30	TW7	1.40	1.10
MB82CC		T21 PM	RF41	1.20	.90	T27		1.25	TW7 Bit	.20	.15
4S102SB	254.45	185.00	RF45	6.40	4.90	T30	4.80	3.65	TW8	1.40	1.10
4SB	Use	MB82	RF46	8.80	6.75	T31		1.55	TW8 Bit	.20	.15
ASBC		B82CC	RF47	7.20	5.50	T32		.40	TW10		
		NF50	RF49	1.20	.90	T34	2.60	2.00	TW10 Bit	1.60	1.25
150											



Numerical and Alphabetical Price List

ool	List	Net	Tool	List	Net	Tool	List	Net	Tool	List	Net	
Bit	1.60	1.25	X84 X88	31.60 35.60	23.00 25.90	Drea Adjustabl	dnaught le Wrenc	hes	Straight National Wrenche (Ridgid Type)			
. Die	.70	.55	X94	47.60	34.65	redjustion	ic mreme		NSP6 6"	3.00	0.00	
	170	.55	X96	52.00	37.85	DAW6 6"	2.00	1.55	NSP8 8"	3.60	2.30 2.75	
- Da .	.70	.55	X100	57.00	41.45	DAW 0	2.00	1.00	NSP10 10"	4.60	3.55	
65.	.70	.55	XH	127.50	92.65	DAWS 8"	2.50	1.95	NSP14 14"	6.40	4.95	
100	.70	.55	Feel	er Stock		DAW10 10"	3.00	2.30	NSP18 18" NSP24 24"	9.00 15.60	6.95	
105.1	.70	.55	All Sizes	.40	.30	F 100 E 100 S	F 10-30	2000	NSP36 36"	32.80	23.85	
20.	1.80	1.40	Re	amers	5700	DAW12 12"	4.60	3.50	NSP48 48"	48.40	35.20	
	1.80	1.40	1007									
- 65	2.60	2.00	8A 7A	6.20	4.75	100						
	6.00	4.60	6A	6.20	4.75	19.16 (34.)		-				
00.1	3.60	2.75	5A	6.20	4.75		B	RI	ΓISH			
	.40	.30	44	6.20	4.75	Habble Line	-	TAL.	LIVII			
1607)	3.20	2.45	24	6.20	4.75	100,60	OTT	TO F	TOOT	a		
(1610)	3.80	2.95	2A	6.20	4.75		SIL	L	LOOL	3		
21.51	.70	.55	A	6.20	4.75				36, 53 60	2.3		
2001	.70	.55	B	6.20	4.75	0.00		15.00				
05.	12.90	9.40	C	6.60	5.05	Tool	List	Net	Tool	List	Net	
100	18.90	13.75	D E	6.60	5.05	*504	ANIOU	0.1NN		ANOV	4100	
166	33.75	24.50	F	7.00	5.40	HDW14	76.60	54.70	W783	2.20	1.70	
5.106	43.00	31.25	G	7.80	6.00	MW1	1.10	.85	W784	3.00	2.30	
C SE.	.15	.10	H	8.20	6.25	MW2	1.10	.85	W 130	3.60	2.7	
	.15	.10	î	9,60	7.35	MW3	1.10	.85	44.1.0-0	4.60	3.50	
	.15	.10	J	11.20	8.15	MW4	1.10	.85	W795	3.60	2.75	
	.15	.10	IA.	14.00	10.20	MW5 MW6	1.10	.85	W796 W797	8.00 13.60	9.90	
04	.15	.10	L	16.00	11.65	MW7	1.20	.90	WB6LR	12.85	9.35	
	.20	.15	M	21.00	15.30	MW8	1.20	.90	WB12	29.60	21.50	
0.00	.25	.20	O	34.80 48.60	25.35 35.30	MW9	1.20	.90	WB16	52.20	38.00	
100.	.25	.20	0	40.00	00.00	MW10	1.20	.90	WB19	45.35	33.00	
R	.40	#30	2010 03	Pilots		W4T	7.60	5.80	WB49	128.10	93.10	
	3.00	2.30	J. Hilly V.			W70	1.80	1.40	WB95	13.90	10.10	
231	.90	.70	8A	1.40	1.10	W71 W72	1.80	1.40	WB96 WB190 (4)	15.70	11.40	
200	1.20	.90	7A 6A	1.40	1.10	W73	2.20	1.70	shown in cat			
1997	1.60	1.25	5A	1.40	1.10	W77	2.80	2.15	but contains	4 nes.	S TT.A.O.	
Sec. 1	2.20	1.70	4A	1.40	1.10	W79	5.10	3.95	Day contains	Page.	100	
7.66	1.00	.75	3A	1.40	1,10	W87(W187)	6.00	4,60	WB312	18.90	13.75	
18	1.10	.85	2A	1.40	1.10	W89(W189)	8.80	6.75	WE01	1.60	1.25	
1.854	1.20	.90	A	3.20	2.45	W122	1.60	1.25	WE8	12.00	8.75	
18:23	1.60	1.25	B	3.20	2.45	W122A W124	1.60	1.25	WE10 WE23	1.60	1.25	
	4.20	3.20	C	3.20	2,45 2,60	W124 W152	1.20	.90	WE32	1.40	1.10	
1	.80	.60	E	3.40	2.60	W153	1.20	.90	WE45	1.40	1.10	
100	.90	.70	F	4.00	3.05	W154	1.20	.90	WE54	1.40	1.10	
00	1.10	.85	G	4.00	3.05	W155	1.20	.90	WE67	1.20	.90	
(H	1.40	1.05	H	4.40	3.35	W156	1.20	.90	WE76	1.20	.90	
10/9	4.40	3.35	I	4.40	3.35	W157	1.60	1.25	WH160	2.40	1.8	
1.00	5.80	4.45	J	5.80	4.45	W158 W159	1.60	1.25	WH161	2.40	1.8	
100.4	7.80	5.95	K L	7.00	5.40	W159	1.60	1.25	WH162 WH163	2.60 3.60	2.0	
-33	7.80	5.95	M	8.20 12.60	6.30 9.15	W161	2.00	1.55	WH163 WH164	3.60	2.7	
100	6.00	4.60	N	17.60	12.80	W162	2.40	1.85	WH165	4,00	3.0	
5 pm	7.40	5.65	0	22.80	16.60	W163	2.60	2.00	WH166	4.60	3.5	
100	8.20	6.30			10100	W164	2.80	2.15	WH167	5.00	3.8	
100	10.60	7.70	Gra	y-Alloy		W176	.70	.55	WH168	5.60	4.3	
98.	12.00	8.75	Adjustah	le Wrene	ches	W176A	.80	.60	WL154	2.40	1.8	
95.4	13.00	9.50		20000000		W177	.80	.60	WL155	2.40	1.8	
101-2	16.80	12.25 13.10	91-4 4" GA6 6"	3.20	2.45	11.7.1.0	.90	.70	WL156	2.40	1.8	
	20,30	14.80	GA8 8"	3.00	2.00	W179 W774	1.20	.90	WL157	2.40	1.8	
			CA10 10"	3.90	2.95	W774 W775	1.45	1.10	WL158 WL159	2.40 2.60	1.85	
3		15.85										
65. 61.	21.80	15.85 17.45	GA10 10" GA12 12"			11.4.4.0				2 80		
61 61 38 48		15.85 17.45 18.90	GA10 10" GA12 12" GA15 15" GA18 18"	5.80	4.45 6.60	W776 W781	2.00	1.55	WL160 WL161	2.80	2.15	